



US008909248B2

(12) **United States Patent**
Phillips et al.

(10) **Patent No.:** **US 8,909,248 B2**
(45) **Date of Patent:** ***Dec. 9, 2014**

(54) **LOCATION-BASED SERVICES**

(75) Inventors: **Alan Phillips**, Hopkinton, MA (US);
Frank Schroth, Milton, MA (US);
Geoffrey M. Palmer, Newton, MA
(US); **Stefan G. Zielinski**, Watertown,
MA (US); **Allen P. Smith**, Milton, MA
(US); **Colin M. Cunningham**,
Cambridge, MA (US)

(73) Assignee: **eBay Inc.**, San Jose, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 218 days.

This patent is subject to a terminal dis-
claimer.

(21) Appl. No.: **13/361,113**

(22) Filed: **Jan. 30, 2012**

(65) **Prior Publication Data**

US 2012/0126974 A1 May 24, 2012

Related U.S. Application Data

(60) Continuation of application No. 11/690,720, filed on
Mar. 23, 2007, now Pat. No. 8,326,315, which is a
division of application No. 11/140,273, filed on May
27, 2005, now Pat. No. 7,848,765.

(51) **Int. Cl.**

H04W 24/00 (2009.01)
H04W 4/02 (2009.01)
G08B 21/02 (2006.01)
H04W 4/12 (2009.01)
H04W 92/08 (2009.01)
H04W 8/14 (2009.01)
H04W 8/10 (2009.01)
H04W 4/14 (2009.01)

(52) **U.S. Cl.**

CPC **G08B 21/0236** (2013.01); **H04W 4/12**

(2013.01); **H04W 4/021** (2013.01); **H04W**
92/08 (2013.01); **H04W 8/14** (2013.01); **H04W**
8/10 (2013.01); **G08B 21/0269** (2013.01);
G08B 21/0261 (2013.01); **H04W 4/14**
(2013.01); **G08B 21/0272** (2013.01)
USPC **455/456.1**; 455/456.3; 455/414.1;
455/414.2; 455/404.2

(58) **Field of Classification Search**

CPC **H04W 4/02**; **H04W 4/021**; **H04W 64/00**;
H04L 29/08657
USPC **455/456.1**, **456.3**, **414.1**, **414.2**, **404.2**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,559,707 A 9/1996 DeLorme et al.
5,649,114 A 7/1997 Deaton et al.

(Continued)

OTHER PUBLICATIONS

"U.S. Appl. No. 11/140,273, Final Office Action mailed Jul. 15,
2009", 11 pgs.

(Continued)

Primary Examiner — Nghi H Ly


(74) Attorney, Agent, or Firm — Schwegman Lundberg &
Woessner, P.A.

(57)

ABSTRACT

Provided herein are methods and systems relating to location-
based services such as providing a geofencing, outputting
location-based information on a mobile device, varying trans-
missions to and from a mobile device, and providing location-
based alerts. More specifically, a method can include receiv-
ing a task on a mobile device, associating the task with a
location, generating a geofence around the location associ-
ated with the task, tracking a current location of the mobile
device, and generating an alert associated with the task when
the current location is within the geofence.

20 Claims, 28 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,724,521 A	3/1998	Dedrick	7,254,388 B2	8/2007	Nam et al.
5,724,660 A	3/1998	Kauser et al.	7,273,172 B2	9/2007	Olsen, III et al.
5,732,354 A	3/1998	Macdonald	7,385,499 B2	6/2008	Horton et al.
5,848,373 A	12/1998	DeLorme et al.	7,389,919 B2	6/2008	Walker et al.
5,890,068 A	3/1999	Fattouche et al.	7,502,133 B2	3/2009	Fukunaga et al.
5,938,721 A	8/1999	Dussell et al.	7,532,899 B2	5/2009	Wilson et al.
5,946,687 A	8/1999	Gehani et al.	7,657,436 B2	2/2010	Elmore et al.
5,948,040 A	9/1999	DeLorme et al.	7,668,931 B2	2/2010	Parupudi et al.
6,014,090 A	1/2000	Rosen et al.	7,669,759 B1	3/2010	Zettner
6,069,570 A	5/2000	Herring et al.	7,706,740 B2	4/2010	Collins et al.
6,091,956 A	7/2000	Hollenberg	7,715,981 B2	5/2010	Bradley et al.
6,097,958 A	8/2000	Bergen	7,720,436 B2	5/2010	Hamynen et al.
6,122,520 A	9/2000	Want et al.	7,720,844 B2	5/2010	Chu et al.
6,154,172 A	11/2000	Piccionelli et al.	7,747,259 B2	6/2010	Pande et al.
6,157,841 A	12/2000	Bolduc et al.	7,751,971 B2	7/2010	Chang et al.
6,167,274 A	12/2000	Smith	7,848,765 B2 *	12/2010	Phillips et al. 455/456.3
6,198,927 B1	3/2001	Wright et al.	7,909,326 B2	3/2011	Walker et al.
6,204,812 B1	3/2001	Fattouche	8,041,604 B1	10/2011	Glaser
6,208,297 B1	3/2001	Fattouche et al.	8,099,109 B2	1/2012	Altman et al.
6,208,857 B1	3/2001	Agre et al.	8,249,884 B2	8/2012	Turner et al.
6,243,588 B1	6/2001	Koorapaty et al.	8,326,315 B2	12/2012	Phillips et al.
6,246,861 B1	6/2001	Messier et al.	8,355,948 B2	1/2013	Mason
6,246,882 B1	6/2001	Lachance	8,371,502 B1	2/2013	Galit et al.
6,259,381 B1	7/2001	Small	8,463,295 B1	6/2013	Caralis et al.
6,259,923 B1	7/2001	Lim et al.	2001/0055976 A1	12/2001	Couch et al.
6,266,014 B1	7/2001	Fattouche et al.	2002/0046259 A1	4/2002	Glorikian
6,269,361 B1	7/2001	Davis et al.	2002/0065689 A1	5/2002	Bingham et al.
6,314,365 B1	11/2001	Smith	2002/0078444 A1	6/2002	Krewin et al.
6,317,684 B1	11/2001	Roeseler et al.	2002/0082941 A1	6/2002	Bird
6,321,158 B1	11/2001	DeLorme et al.	2002/0111154 A1	8/2002	Eldering et al.
6,330,452 B1	12/2001	Fattouche et al.	2002/0115453 A1	8/2002	Poulin et al.
6,341,255 B1	1/2002	Lapidot	2002/0143930 A1	10/2002	Babu et al.
6,347,230 B2	2/2002	Koshima et al.	2002/0145984 A1	10/2002	Babu et al.
6,356,543 B2	3/2002	Hall et al.	2002/0155844 A1	10/2002	Rankin et al.
6,357,042 B2	3/2002	Srinivasan et al.	2002/0160766 A1	10/2002	Portman et al.
6,374,176 B1	4/2002	Schmier et al.	2002/0198003 A1	12/2002	Klapman
6,374,177 B1	4/2002	Lee et al.	2003/0004802 A1	1/2003	Callegari
6,404,388 B1	6/2002	Sollenberger et al.	2003/0007006 A1	1/2003	Baar et al.
6,424,840 B1	7/2002	Fitch et al.	2003/0037041 A1	2/2003	Hertz
6,442,529 B1	8/2002	Krishan et al.	2003/0040324 A1	2/2003	Eldering et al.
6,456,852 B2	9/2002	Bar et al.	2003/0125043 A1	7/2003	Silvester et al.
6,477,363 B1	11/2002	Ayoub et al.	2003/0126150 A1	7/2003	Chan et al.
6,496,857 B1	12/2002	Dustin et al.	2003/0130787 A1	7/2003	Clapper
6,519,463 B2	2/2003	Tendler	2003/0139190 A1	7/2003	Steelberg et al.
6,529,159 B1	3/2003	Fan et al.	2003/0216960 A1	11/2003	Postrel
6,552,682 B1	4/2003	Fan	2003/0220835 A1	11/2003	Barnes, Jr.
6,563,459 B2	5/2003	Takenaga	2004/0002359 A1	1/2004	Deas et al.
6,577,946 B2	6/2003	Myr	2004/0021567 A1	2/2004	Dunn
6,580,914 B1	6/2003	Smith	2004/0023666 A1	2/2004	Moon et al.
6,590,529 B2	7/2003	Schwoegler	2004/0039579 A1	2/2004	Chithambaram et al.
6,590,533 B2	7/2003	Sollenberger et al.	2004/0043773 A1	3/2004	Lee et al.
6,618,593 B1	9/2003	Drutman et al.	2004/0111332 A1	6/2004	Baar et al.
6,664,922 B1	12/2003	Fan	2004/0139330 A1	7/2004	Baar
6,690,322 B2	2/2004	Shamoto et al.	2004/0192339 A1	9/2004	Wilson et al.
6,714,797 B1	3/2004	Rautila	2004/0192349 A1	9/2004	Reilly
6,718,551 B1	4/2004	Swix et al.	2004/0203901 A1	10/2004	Wilson et al.
6,732,120 B1	5/2004	Du	2004/0203931 A1	10/2004	Karaoguz
6,741,188 B1	5/2004	Miller et al.	2005/0044032 A1	2/2005	Lee et al.
6,757,544 B2	6/2004	Rangarajan et al.	2005/0064852 A1	3/2005	Baldursson
6,807,479 B2	10/2004	Watanabe et al.	2005/0065916 A1	3/2005	Ge et al.
6,819,919 B1	11/2004	Tanaka	2005/0159883 A1 *	7/2005	Humphries et al. 701/207
7,082,365 B2	7/2006	Sheha et al.	2005/0250516 A1	11/2005	Shim
7,092,702 B2	8/2006	Cronin et al.	2005/0278749 A1	12/2005	Ewer et al.
7,130,622 B2	10/2006	Vänskäet al.	2006/0047825 A1	3/2006	Steenstra et al.
7,138,913 B2	11/2006	Mackenzie et al.	2006/0064346 A1	3/2006	Steenstra et al.
7,142,858 B2	11/2006	Aoki et al.	2006/0089792 A1	4/2006	Manber et al.
7,164,986 B2	1/2007	Humphries et al.	2006/0098028 A1	5/2006	Baar
7,196,639 B2	3/2007	Joyce et al.	2006/0099959 A1	5/2006	Staton et al.
7,197,719 B2	3/2007	Doyle et al.	2006/0145837 A1 *	7/2006	Horton et al. 340/539.13
7,199,815 B2	4/2007	Aoyama	2006/0148488 A1	7/2006	Syrbe
7,203,502 B2	4/2007	Wilson et al.	2006/0218114 A1	9/2006	Weare et al.
7,203,598 B1	4/2007	Whitsell	2006/0236257 A1	10/2006	Othmer et al.
7,213,214 B2	5/2007	Baar et al.	2006/0270421 A1	11/2006	Phillips et al.
7,216,109 B1	5/2007	Donner	2006/0271281 A1	11/2006	Ahn et al.
7,246,109 B1	7/2007	Ramaswamy	2007/0015517 A1	1/2007	Casey
			2007/0024469 A1	2/2007	Chou
			2007/0083437 A1	4/2007	Hamor
			2007/0118430 A1	5/2007	Wiseman et al.
			2007/0124229 A1	5/2007	Ku et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0165050	A1	7/2007	Baar	
2007/0202844	A1	8/2007	Wilson et al.	
2007/0244633	A1	10/2007	Phillips et al.	
2008/0035725	A1	2/2008	Jambunathan et al.	
2008/0040216	A1	2/2008	Dellovo	
2008/0046415	A1	2/2008	Henkin et al.	
2008/0070588	A1	3/2008	Morin	
2008/0102947	A1	5/2008	Hays et al.	
2008/0126251	A1	5/2008	Wassingbo	
2008/0126515	A1	5/2008	Chambers et al.	
2008/0177749	A1	7/2008	Overton	
2008/0248815	A1	10/2008	Busch	
2008/0290987	A1	11/2008	Li	
2008/0313078	A1	12/2008	Payne	
2009/0005077	A1	1/2009	Forstall et al.	
2009/0024476	A1	1/2009	Baar et al.	
2009/0037101	A1	2/2009	Koike et al.	
2009/0061884	A1	3/2009	Rajan et al.	
2009/0063229	A1	3/2009	Coladonato et al.	
2009/0076911	A1	3/2009	Vo et al.	
2009/0076925	A1	3/2009	Dewitt et al.	
2009/0100037	A1	4/2009	Scheibe	
2009/0132961	A1	5/2009	Baar	
2009/0156234	A1	6/2009	Sako et al.	
2009/0204672	A1	8/2009	Jetha et al.	
2011/0047075	A1	2/2011	Fourez	
2012/0129553	A1 *	5/2012	Phillips et al.	455/456.3
2012/0239483	A1	9/2012	Yankovich et al.	
2012/0239501	A1	9/2012	Yankovich et al.	
2013/0110624	A1	5/2013	Mitrovic	
2013/0150086	A1	6/2013	Caralis et al.	
2013/0173377	A1	7/2013	Keller et al.	
2013/0346233	A1	12/2013	Caralis et al.	

OTHER PUBLICATIONS

"U.S. Appl. No. 11/140,273, Final Office Action mailed Dec. 13, 2007", 11 pgs.
 "U.S. Appl. No. 11/140,273, Non Final Office Action mailed Feb. 26, 2010", 11 pgs.
 "U.S. Appl. No. 11/140,273, Non Final Office Action mailed May 31, 2007", 10 pgs.
 "U.S. Appl. No. 11/140,273, Non Final Office Action mailed Jul. 3, 2008", 11 pgs.
 "U.S. Appl. No. 11/140,273, Notice of Allowance mailed Aug. 3, 2010", 6 pgs.
 "U.S. Appl. No. 11/140,273, Preliminary Amendment mailed Aug. 30, 2005", 32 pgs.
 "U.S. Appl. No. 11/140,273, Response filed Mar. 20, 2007 to Restriction Requirement mailed Feb. 21, 2007", 10 pgs.
 "U.S. Appl. No. 11/140,273, Response filed Apr. 14, 2008 to Final Office Action mailed Dec. 13, 2007", 13 pgs.
 "U.S. Appl. No. 11/140,273, Response filed Apr. 21, 2009 to Restriction Requirement mailed Jan. 21, 2009", 10 pgs.
 "U.S. Appl. No. 11/140,273, Response filed May 26, 2010 to Non Final Office Action mailed Feb. 26, 2010", 13 pgs.
 "U.S. Appl. No. 11/140,273, Response filed May 27, 2007 to Final Office Action mailed Dec. 13, 2007", 18 pgs.
 "U.S. Appl. No. 11/140,273, Response filed Oct. 7, 2008 to Non Final Office Action mailed Jul. 3, 2008", 17 pgs.
 "U.S. Appl. No. 11/140,273, Response filed Nov. 16, 2009 to Non Final Office Action mailed Jul. 15, 2009", 19 pgs.
 "U.S. Appl. No. 11/140,273, Response filed Nov. 27, 2007 to Non Final Office Action mailed May 31, 2007", 12 pgs.
 "U.S. Appl. No. 11/140,273, Restriction Requirement mailed Jan. 21, 2009", 6 pgs.
 "U.S. Appl. No. 11/140,273, Restriction Requirement mailed Feb. 21, 2007", 5 pgs.
 "U.S. Appl. No. 11/593,047, Advisory Action mailed Jan. 29, 2010", 4 pgs.
 "U.S. Appl. No. 11/593,047, Applicant Summary of Examiner Interview mailed Mar. 15, 2010", 2 pgs.

"U.S. Appl. No. 11/593,047, Examiner Interview Summary mailed Mar. 12, 2010", 4 pgs.
 "U.S. Appl. No. 11/593,047, Final Office Action mailed Dec. 1, 2009", 19 pgs.
 "U.S. Appl. No. 11/593,047, Non Final Office Action mailed Feb. 2, 2009", 18 pgs.
 "U.S. Appl. No. 11/593,047, Non Final Office Action mailed Sep. 4, 2009", 13 pgs.
 "U.S. Appl. No. 11/593,047, Response filed Jan. 22, 2010 to Final Office Action mailed Dec. 1, 2009", 23 pgs.
 "U.S. Appl. No. 11/593,047, Response filed Apr. 20, 2009 to Non Final Office Action mailed Feb. 2, 2009", 33 pgs.
 "U.S. Appl. No. 11/593,047, Response filed Nov. 16, 2009 to Non Final Office Action mailed Sep. 4, 2009", 20 pgs.
 "U.S. Appl. No. 11/593,047, Supplemental Amendment filed Mar. 18, 2010 to Examiner Interview on Mar. 10, 2010", 12 pgs.
 "U.S. Appl. No. 11/690,720, Examiner Interview Summary mailed Feb. 22, 2012", 3 pgs.
 "U.S. Appl. No. 11/690,720, Final Office Action mailed Apr. 27, 2010", 10 pgs.
 "U.S. Appl. No. 11/690,720, Final Office Action mailed Nov. 9, 2011", 17 pgs.
 "U.S. Appl. No. 11/690,720, Non Final Office Action mailed Sep. 25, 2009", 20 pgs.
 "U.S. Appl. No. 11/690,720, Non-Final Office Action May 17, 2011", 11 pgs.
 "U.S. Appl. No. 11/690,720, Preliminary Amendment filed Mar. 23, 2007", 8 pgs.
 "U.S. Appl. No. 11/690,720, Response filed Jan. 28, 2010 to Non Final Office Action mailed Sep. 25, 2010", 11 pgs.
 "U.S. Appl. No. 11/690,720, Response filed Feb. 15, 2012 to Final Office Action mailed Nov. 9, 2011", 14 pgs.
 "U.S. Appl. No. 11/690,720, Response filed Aug. 17, 2011 to Non Final Office Action mailed May 17, 2011", 13 pgs.
 "U.S. Appl. No. 11/690,720, Response filed Aug. 25, 2010 to Final Office Action mailed Apr. 27, 2010", 11 pgs.
 "U.S. Appl. No. 12/175,512, Final Office Action mailed Dec. 7, 2011", 13 pgs.
 "U.S. Appl. No. 12/175,512, Non Final Office Action mailed Aug. 1, 2011", 12 pgs.
 "U.S. Appl. No. 12/175,512, Response filed Mar. 7, 2012 to Final Office Action mailed Dec. 7, 2011", 10 pgs.
 "U.S. Appl. No. 12/175,512, Response filed Nov. 28, 2011 to Non-Final Office Action Received Aug. 1, 2011", 12 pgs.
 "U.S. Appl. No. 12/268,693, Non Final Office Action mailed Aug. 8, 2011", 16 pgs.
 "U.S. Appl. No. 12/268,693, Response Filed Nov. 8, 2011 to Non-Final Office w/Restriction Requirement Received Aug. 8, 2011", 11 pgs.
 "U.S. Appl. No. 12/268,693, Response filed Nov. 8, 2011 to Non Final Office Action mailed Aug. 8, 2011", 11 pgs.
 "U.S. Appl. No. 12/369,068, Response filed Nov. 21, 2011 to Final Office Action mailed Aug. 19, 2011", 12 pgs.
 "U.S. Appl. No. 12/369,068, Final Office Action mailed Aug. 19, 2011", 17 pgs.
 "U.S. Appl. No. 12/369,068, Non Final Office Action mailed Dec. 8, 2010", 19 pgs.
 "U.S. Appl. No. 12/369,068, Response filed Jun. 8, 2011 to Non Final Office Action mailed Dec. 8, 2010", 19 pgs.
 "Halfbakery: Buddy Locator", [Online]. Retrieved from the Internet: <URL: http://www.halfbakery.com/idea/Buddy_20Locator#1055455737>, (Jun. 11, 2003), 2 pgs.
 "Halfbakery: Mobile phone utility", [Online]. Retrieved from the Internet: <URL: http://www.halfbakery.com/idea/mobile_20phone_20utility#1073585857>, (Jan. 8, 2004), 2 pgs.
 "Halfbakery: Mobile Proximity Line", [Online]. Retrieved from the Internet: <URL: http://www.halfbakery.com/idea/Mobile_20Proximity_20Link#1001923289>, (Sep. 30, 2001), 2 pgs.
 "Networks in Motion Named Semi-Finalist for Wireless LBS Challenge", [Online]. Retrieved from the Internet: <URL: <http://www.tmcnet.com/usubmiU2004/Mar/1025200.htm>>, (Mar. 18, 2004), 1 pg.

(56)

References Cited

OTHER PUBLICATIONS

"Proposal for free, open source cell phone location service", 90% Crud, [Online]. Retrieved from the Internet: <URL: http://george.hotelling.net/90percent/geekery/proposal_for_free_open_source_cell_phone_location_service.php>, (Mar. 6, 2004), 1 pg.

"SignalSoft Corporation awarded location-based services patent", [Online]. Retrieved from the Internet: <URL: <http://www.cellular.co.za/news/2001/04282001-signalsoft-patent.htm>>, (Apr. 27, 2001), 1 pg.

Carpendale, Marianne S.T., "A Framework for Elastic Presentation Space", Burnaby, British Columbia, Simon Fraser University, (1999), 296 pgs.

"U.S. Appl. No. 11/690,720, Examiners Interview Summary mailed Feb. 22, 2012", 3 pgs.

"U.S. Appl. No. 11/690,720, Notice of Allowance mailed May 15, 2012", 7 pgs.

"U.S. Appl. No. 12/268,693, Final Office Action mailed Dec. 2, 2011", 20 pgs.

"U.S. Appl. No. 12/268,693, Response filed Jun. 1, 2012 to Final Office Action mailed Dec. 2, 2011", 11 pgs.

"U.S. Appl. No. 13/339,235, Response filed Jun. 15, 2012 to Non Final Office Action mailed Mar. 16, 2012", 11 pgs.

"U.S. Appl. No. 13/339,235, Non Final Office Action mailed Mar. 16, 2012", 10 pgs.

"U.S. Appl. No. 13/361,196, Response filed Jun. 21, 2012 to Non Final Office Action mailed Mar. 29, 2012", 9 pgs.

"U.S. Appl. No. 13/361,196, Non Final Office Action mailed Mar. 29, 2012", 12 pgs.

"Targeted Incentive Actions Based on Location and Intent", U.S. Appl. No. 13/050,769, Application filed Mar. 17, 2011, 47 pgs.

"U.S. Appl. No. 11/690,720, Notice of Allowance mailed Aug. 2, 2012", 7 pgs.

"U.S. Appl. No. 13/313,681, Non Final Office Action mailed Aug. 21, 2012", 24 pgs.

"U.S. Appl. No. 13/339,235, Final Office Action mailed Aug. 29, 2012", 10 pgs.

"U.S. Appl. No. 13/361,196, Non Final Office Action mailed Aug. 23, 2012", 13 pgs.

"U.S. Appl. No. 12/369,068, Non Final Office Action mailed Oct. 8, 2013", 19 pgs.

"U.S. Appl. No. 13/050,769, Final Office Action mailed Jun. 17, 2013", 10 pgs.

"U.S. Appl. No. 13/050,769, Response filed Sep. 5, 2013 to Final Office Action Mailed Jun. 17, 2013", 14 pgs.

"U.S. Appl. No. 13/282,199, Final Office Action mailed Sep. 26, 2013", 25 pgs.

"U.S. Appl. No. 13/282,199, Non Final Office Action mailed Apr. 29, 2013", 20 pgs.

"U.S. Appl. No. 13/282,199, Response filed Aug. 28, 2013 to Non Final Office Action mailed Sep. 29, 2013", 16 pgs.

"U.S. Appl. No. 13/340,970, Final Office Action mailed Sep. 26, 2013", 18 pgs.

"U.S. Appl. No. 13/340,970, Non Final Office Action mailed Apr. 12, 2013", 18 pgs.

"U.S. Appl. No. 13/340,970, Response filed Jul. 12, 2013 to Non Final Office Action mailed Apr. 12, 2013", 10 pgs.

"U.S. Appl. No. 13/361,196, Examiner Interview Summary mailed Apr. 22, 2013", 3 pgs.

"U.S. Appl. No. 13/361,196, Response filed Apr. 18, 2013 to Final Office Action mailed Jan. 22, 2013", 10 pgs.

"Foursquare", Wikipedia, [Online]. Retrieved from the Internet: <<http://en.wikipedia.org/wiki/Foursquare>>, (Accessed Apr. 16, 2013), 12 pgs.

Keath, Jason, "21 Unique Location Examples from Foursquare", Gowalla, Whrrl, and MyTown, Socialfresh.com, (Jun. 1, 2010), 9 pgs.

Manninen, JP, "'Geofencing' enables new location-based apps, raises privacy concerns.", VentureBeat, [Online]. Retrieved from the Internet: <URL: <http://venturebeat.com/2010/04/23/geofencing-pushes-services-to-phones/>>, (Apr. 23, 2010), 4 pgs.

"U.S. Appl. No. 13/050,769, Non Final Office Action mailed Jan. 11, 2013", 10 pgs.

"U.S. Appl. No. 13/050,769, Response filed Apr. 9, 2013 to Non Final Office Action mailed Jan. 11, 2013", 15 pgs.

"U.S. Appl. No. 13/282,199, Response filed Apr. 4, 2013 to Restriction Requirement mailed Mar. 7, 2013", 10 pgs.

"U.S. Appl. No. 13/282,199, Restriction Requirement mailed Mar. 7, 2013", 8 pgs.

"U.S. Appl. No. 13/313,681, Notice of Allowance mailed Feb. 7, 2013", 13 pgs.

"U.S. Appl. No. 13/313,681, Response filed Jan. 21, 2013 to Non Final Office Action mailed Aug. 21, 2012", 10 pgs.

"U.S. Appl. No. 13/339,235, Response filed Nov. 29, 2012 to Final Office Action mailed Aug. 29, 2012", 11 pgs.

"U.S. Appl. No. 13/361,196, Final Office Action mailed Jan. 22, 2013", 15 pgs.

"U.S. Appl. No. 13/361,196, Response filed Nov. 21, 2012 to Non Final Office Action mailed Aug. 23, 2012", 13 pgs.

"U.S. Appl. No. 11/593,047, Non Final Office Action mailed Mar. 11, 2014", 18 pgs.

"U.S. Appl. No. 12/369,068, Response filed Feb. 10, 2014 to Non Final Office Action mailed Oct. 8, 2013", 14 pgs.

"U.S. Appl. No. 13/282,199, Non Final Office Action mailed Apr. 9, 2014", 28 pgs.

"U.S. Appl. No. 13/282,199; Response filed Jan. 27, 2014 to Non-Final Office Action mailed Sep. 26, 2013", 14 pgs.

"U.S. Appl. No. 13/339,235, Notice of Allowance mailed Apr. 25, 2014", 8 pgs.

"U.S. Appl. No. 13/340,970, Advisory Action mailed Feb. 13, 2014", 3 pgs.

"U.S. Appl. No. 13/340,970, Response filed Feb. 25, 2014 to Advisory Action mailed Feb. 13, 2014", 10 pgs.

"U.S. Appl. No. 13/340,970; Response filed Jan. 27, 2014 to Final Office Action mailed Sep. 26, 2013", 10 pgs.

"U.S. Appl. No. 13/361,196, Non Final Office Action mailed Jan. 3, 2014", 11 pgs.

"U.S. Appl. No. 13/361,196, Response filed Apr. 2, 2014 to Non Final Office Action mailed Jan. 3, 2014", 7 pgs.

"U.S. Appl. No. 13/913,768, Preliminary Amendment mailed Dec. 3, 2013", 8 pgs.

"U.S. Appl. No. 11/593,047, Examiner Interview Summary mailed Jul. 24, 2014", 2 pgs.

"U.S. Appl. No. 11/593,047, Response filed Jul. 28, 2014 to Non Final Office Action mailed Mar. 11, 2014", 10 pgs.

"U.S. Appl. No. 13/050,769, Notice of Allowance mailed Jun. 16, 2014", 8 pgs.

"U.S. Appl. No. 13/282,199, Examiner Interview Summary mailed Jul. 22, 2014", 3 pgs.

"U.S. Appl. No. 13/282,199, Response filed Jul. 17, 2014 to Non Final Office Action mailed Apr. 9, 2014", 16 pgs.

"U.S. Appl. No. 13/361,196, Notice of Allowance mailed Jun. 10, 2014", 8 pgs.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10

*FIG. 11*




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27A




FIG. 27B






FIG. 27C



2802

FIG. 28



2902

FIG. 29




FIG. 30

3102

uLocate : LAST KNOWN LOCATIONS FOR ALL UNITS

FILE

EDIT

VIEW

FAVORITES

TOOLS

HELP

uLocate

TODAYS

STOP REPORT

FOR

TRIMTRAC (GP VAN)

LOCATIONS

HELP

LOG OUT

TODAY

YESTERDAY

SELECT

REFRESH

STOP	TIME	DURATION	LOCATION	DIRECTION/ SPEED	DISTANCE (MILES)
3	11/03/04 - 1:19 PM - 1:23 PM 11/03/04 - 12:34 PM	0:03	uLOCATE OFFICE ROUTE 9, NATICK, MA	NW AT 0 MPH	3.84
2	11/03/04 - 8:50 AM - 8:58 AM 11/03/04 - 8:46 AM 11/03/04 - 8:35 AM 11/03/04 - 8:27 AM	0:03	uLOCATE OFFICE 154 COMMONWEALTH RD, WAYLAND, MA ROUTE 30, AUBUMDALE, MA HOMER ST, NEWTON CENTER, MA	N AT 0 MPH W AT 30 MPH N AT 0 MPH	11.69
1	11/03/04 - 7:54 AM - 8:09 AM	0:14	874, WALNUT ST, NEWTON CENTER, MA		0.00

(ALL TIMES EASTERN)

DOWNLOAD REPORT AS A COMMA SEPARATED VALUE (CSV) FILE

PRINTER-FRIENDLY VERSION

MINIMUM STOP DURATION (SECONDS)

120

SHOW ALL TRANSIT DETAIL:

ORDER REPORT CHRONOLOGICALLY:

SHOW DETAIL WITHIN GEOFENCES:

GO

DONE

INTERNET

FIG. 31




FIG. 32




FIG. 33

3402

LOCATION		ADDRESS BOOK	
ADDRESS BOOK > SAVE LOCATIONS > ALL			
LOCATION	ADDRESS		
GEOFF'S HOME	14 BUSWELL PARK NEWTON, MA 02458	EDIT	DELETE
HOME	16 BAY COLONY DR ASHLAND, MA 01721	EDIT	DELETE
uLOCATE'S OFFICE	148 SPEEN ST FRAMINGHAM, MA 01701	EDIT	DELETE
> <u>ADD LOCATION</u>		POWERED BY uLOCATE COMMUNICATIONS	

FIG. 34

3402

LOCATION ADDRESS BOOK

SAVE LOCATIONS > UPDATE LOCATIONS

ENTER LOCATION

NAME: GEOFF'S HOME


STREET: 100 MAIN STREET

CITY: NEWTON

STATE: MA

ZIP: 02458

COUNTRY: US



> BACK > NEXT > CANCEL

POWERED BY uLOCATE COMMUNICATIONS

FIG. 35

3602

uLocate

ALERT FOR ULOCATE TEST

LOCATION	PHONE	EVENT	ALERT CONTACTS	
uLOCATE OFFICE	ALAN	<=>	SMS: ALAN EMAIL: JEREMY EMAIL	EDIT DELETE
uLOCATE OFFICE	GEOFF	<=>	EMAIL: NINA	EDIT DELETE
uLOCATE OFFICE	ALAN	<=>	SMS: ALAN EMAIL: ALAN'S EMAIL EMAIL: FRANK'S EMAIL EMAIL: ALAN'S WORK EMAIL	EDIT DELETE
FRANK'S HOME	MAD	<=>	EMAIL: FRANK'S EMAIL	EDIT DELETE
FRANK'S HOME	FRANK	<=>	EMAIL: FRANK'S EMAIL	EDIT DELETE
uLOCATE OFFICE	STEFAN uWAM	<=>	SMS: STEFAN'S SMS EMAIL: ALAN'S EMAIL EMAIL: FRANK'S EMAIL	EDIT DELETE

[CREATE NEW ALERT](#)

FIG. 36



FIG. 37A




FIG. 37B




FIG. 37C




FIG. 38A




FIG. 38B




FIG. 38C




FIG. 39A




FIG. 39B




FIG. 39C




FIG. 39D




FIG. 40




FIG. 41




FIG. 42A




FIG. 42B

1

LOCATION-BASED SERVICES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation and claims the benefit of U.S. Non-Provisional application Ser. No. 11/690,720, filed Mar. 23, 2007, entitled LOCATION-BASED SERVICES, which is a divisional of and claims benefit of U.S. Non-Provisional No. 11/140,273, filed Mar. 27, 2005 entitled LOCATION-BASED SERVICES, now U.S. Pat. No. 7,848,765, issued Dec. 7, 2010, which applications are hereby incorporated by reference in their entirety.

BACKGROUND

1. Field of the Invention

This invention relates to the field of location-based services, and more particularly to the field of location-based services involving portable electronic facilities.

2. Description of the Related Art

Location systems have been developed for determining and tracking the locations of the users of mobile devices such as cellular phones, including global positioning systems (GPS), as well as various triangulation systems that use cellular telephone signals, broadcast television signals, or the like. Dead reckoning systems also exist for determining locations of devices based on movement in reference to a set of known coordinates. However, to date the uses of such systems have been limited. A need exists for improved systems for using location-based information for a variety of purposes.

SUMMARY

A variety of methods and systems are disclosed herein that include the capability of tracking mobile devices, such as cellular phones. In various embodiments, the present invention may provide an adaptable user interface, which may transmit a current location of a portable electronic facility, such as to another device or system and may receive an electronic storage file or other indication of the current location of the portable electronic facility. The file or message may contain code that enables a specific user interface capability for the portable electronic facility, so that it displays a version of the user interface based on the contents of the electronic storage file, message or other contents. The portable electronic facility may take various forms, such as, without limitation, a mobile phone, a GPS enabled mobile phone, a CDMA enabled mobile phone, a GPRS enabled mobile phone, a mobile phone with a camera, a mobile phone with browser capabilities, a GPS unit, a tracking unit, a portable electronic device with a compass, a laptop computer, a personal digital assistant, an MP3 player, a camera, a handheld device, a pager, and/or a portable gaming device. The portable electronic facility may be wearable.

The storage file may be transmitted from a remote location and may without limitation be in a format such as an XML document, a script, an HTML document, a program, a database, a table, a message, a folder, an application, an animation and/or a text file. The storage file may contain user interface information, such as specific menus that may be for a specific location and/or specific allocations that may be for a specific location. The storage file may be updatable, wherein the user may manually update the storage file with information or wherein the storage file may be automatically updated with information. The update may occur when a user stops at a

2

location. The user may modify the interface. The adaptable user interface may produce results, such as an answer to a user's query.

An adaptable user interface may provide for receiving location-based information associated with the portable electronic facility and outputting a version of such information through the portable electronic facility. The information may be received in response to a transmission of the location of the portable electronic facility. The output version of such information may without limitation be visual, audio, a facsimile, an email, voice, a light, a change in the intensity of a light, a change in the color of a light, via SMS, via an instant message, via a text message, and/or an application that may only be available at certain locations. In some embodiments, at least one menu item may be changed in response to the information.

The information may be defined in relation to an object and/or a location. The information may be a geocentric list. The information may be specific to a user and may without limitation alter the look and feel of the facility, alter the functionality of the facility, be in an XML format, be in a database format, and/or be in a text file format. An alert, which may relate to an item on a list, may be triggered in response to the information.

The present invention may provide for location tracking, wherein a location of a portable electronic facility may be transmitted, stored in a file, stored with other information in the portable electronic facility, and reported along with an indication of the movement of the portable electronic facility. The information itself may be displayed on a map and may comprise an indication of speed and/or direction.

The present invention may provide business information by storing the location of a plurality of portable electronic facilities, possibly in an electronic storage file or a location-containing file, which may be remote. The invention may provide access to the storage file, which may contain information pertaining to demographics, locations and motion of the portable electronic facilities. Access to the storage file or information may be password protected and the storage file or information may be encrypted. The storage file may be an XML document, a database, a table or a text file.

The invention may provide demographic information associated with the portable electronic facilities. Tracking information may constitute traffic patterns.

The present invention may provide methods and systems for effecting change on a portable electronic facility in response to location information. The method may involve receiving location information on the portable electronic facility and effecting a change on the portable electronic facility based on the location information. The change may involve activating the portable electronic device, powering off portable electronic device, placing the portable electronic device in standby mode, starting an application, stopping an application or the output of information. The output may involve audio, video, a picture related a location, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration, stimulation at least one of the five senses or an alert. The alert may involve fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or stimulation of at least one of the five senses.

The change may involve a reminder regarding an item on a list and the list may be a geocentric list. The change may involve a change to at least one item on a menu. The change may affect the availability of an application. The change may also involve enabling free calling when within a certain geofence, such as within a home or a user-defined geofence.

3

The location information may relate to the accuracy of the location information. The information may refresh continuously, in accordance with set preferences or in response to a request. The frequency of the requests may be varied in response to speed, location, specified preferences, proximity to a point of interest, or changes in a geofence. A user may make a request, such as a request for help, such as in response to pressing a panic button or activating a panic mode on a portable electronic facility.

The present invention may provide for methods and systems of triggering the output of location-based information involving receiving information via a portable electronic facility and outputting location-based information based on the received information. The information may be received via a sensor, which may measure the parameters of a device, facility or vehicle.

The present invention may provide methods and systems for location determination involving capturing characteristics of a location using a portable electronic facility, transmitting those characteristics and receiving location based information. The characteristics may be captured as a picture, a photograph, verbally or using at least one sensor. The characteristics may be transmitted via SMS, fax, email, instant message, text message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet, text or as a file.

The present invention may provide methods and systems of varying transmissions for a portable electronic facility involving varying information transmissions to a portable electronic facility and varying information transmissions from a portable electronic facility. The length or frequency of the transmissions may be varied. The variation may be in response to velocity, direction, location, a point of interest, an object, preferences, a location with respect to a geofence or changes in a geofence. The variation may result in increased battery life for the portable electronic facility. The data may be stored and transmitted all at one or it may be transmitted as it is updated.

The present invention may provide methods and systems of increasing the quality of location based information for a portable electronic facility, involving varying information transmissions to a portable electronic facility and varying information transmissions from a portable electronic facility. The length or frequency of the transmissions may be varied. The variation may be in response to velocity, direction, location, a point of interest, an object, preferences, a location with respect to a geofence or changes in a geofence.

In an embodiment the information transmissions may be from multiple sources. The multiple sources may be different networks or different means of communication. The means of communication may be SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. The information may be transmitted in a costless manner, a cost reduced manner or in the form of a DNS lookup.

The present invention may provide methods and systems of increasing the quality of location based information for a portable electronic facility involving obtaining multiple data points for a given item of information or a location. The multiple data points may be analyzed and outliers dropped. The analysis may be performed using an algorithm. The item of information may relate to location, velocity or direction.

The present invention may provide methods and systems of defining a geofence on a portable electronic facility involving inputting the geofence using the portable electronic facility. The center and a radius of a geofence may be entered on the portable electronic facility. The geofence may be defined using a cursor on the display of the portable electronic facility.

4

The geofence may be defined using a touch screen on the portable electronic facility. The geofence may be defined by the location of the portable electronic facility. The geofence may be defined by placing the portable electronic facility at certain points comprising the geofence. The geofence may be defined in real time by placing the portable electronic facility at certain points comprising the geofence. The geofence may be manipulated using the portable electronic facility. The geofence may be moved using the display of the portable electronic facility. The geofence may be moved using the portable electronic facility. The geofence may be a circle, a sphere, in the shape of any closed polygon, a closed volume, in two dimensions, in three dimensions or may travel with a person.

The present invention may provide methods and systems of defining a geofence on a computer screen involving inputting the geofence through a user interface. The geofence may be defined or moved about the interface using a pointing device such as a mouse or stylus. The radius, shape or dimensions of the geofence may also be defined or changed using a pointing device such as a mouse or stylus.

The present invention may provide methods and systems of sending location-based alerts involving determining the location of a portable electronic facility and sending an alert based on the location of the portable electronic facility. The alert may be in response to the location of a portable electronic facility with respect to a geofence. The alert may be via audio, video, fax, email, instant message, text message, SIMS, internet protocol, voice, voicemail, vibration or may stimulate at least one of the five senses. The alert may be communicated via one of the following means of communication: SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text.

The present invention may provide methods and systems of analyzing information related to at least one portable electronic facility involving transmitting information from the at least one portable electronic facility and analyzing such information using an analysis engine. The information from one or more portable electronic facilities may be stored or aggregated. The analysis engine may provide the ability to view location history or analyze location history. The analysis engine may also request additional information or send alerts. The analysis engine may perform analytics on location information such as demographic analysis, predictive analysis and descriptive analysis. The information provided by the analysis engine may include purchasing information, personal preferences, demographics or consumer purchasing data relating to individual consumers or classes of consumers.

Access to the analysis engine, the system and information may be granted at different access levels. A user may be granted partial or restricted access via a guest login. It may be that whether a user is permitted to know the location of another user is determined based on the access levels of the users.

Methods and systems disclosed herein may include methods and systems for verifying a transaction using a portable electronic facility. Methods and systems disclosed herein may include methods and systems for tailoring information to the behavior of a user, such as observing the behavior of a user and communicating information to the user by a portable electronic facility, such as information based on the observed behavior of a user. Methods and systems disclosed herein may include methods and systems for providing information to a portable electronic facility based on information received from the portable electronic facility, including location information. A network of portable electronic facilities may be provided, allowing communication among portable elec-

5

tronic facilities, including information based on the tracked locations of the portable electronic facilities. In embodiments information is communicated directly among the portable electronic facilities, without use of a central server. Information may be communicated by SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet and/or text.

Several possible graphical user interfaces may be presented on a portable electronic facility. The interface may display a map or a menu or provide an overview of the locations of all the users in a defined group or of the location history of a particular user. The view may involve the use of tiled maps. The graphical user interface may present a stop report. A geofence may be created using a graphical user interface and an icon may be assigned to a geofence. A graphical user interface may also display an address book or be used to define alerts. Graphical user interfaces may also be used to present of points of interest on a portable electronic facility. A graphical user interface that may allow a user to vary the frequency with which a portable electronic device obtains location information.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a block diagram of components of a location services facility.

FIG. 2 is a block diagram of additional components of the location services facility.

FIG. 3 is a block diagram of an aspect of a peer-to-peer configuration of the location services facility.

FIG. 4 is a block diagram of one aspect of the location services facility in operation.

FIG. 5 is a schematic diagram of an embodiment of part of the location services facility.

FIG. 6 is a block diagram of a portable electronic facility.

FIG. 7 is a block diagram of a GPS state machine.

FIG. 8 is a block diagram of the major components of the location services facility of the present invention.

FIG. 9 is a map overlaid with a geofence and a geographic location.

FIG. 10 is a block diagram of an adaptable user interface.

FIG. 11 is a block diagram of an adaptable user interface.

FIG. 12 is a schematic diagram of location tracking.

FIG. 13 is a schematic diagram relating to the provision of business information.

FIG. 14 is a block diagram relating to effecting change on a portable electronic facility.

FIG. 15 is a schematic diagram relating to outputting location-based information on a portable electronic facility.

FIG. 16 is a schematic diagram relating to location determination.

FIG. 17 is a schematic diagram relating to varying transmissions to and from a portable electronic facility.

FIG. 18 is a schematic diagram relating to increasing the quality of location based information on a portable electronic facility.

FIG. 19 is a block diagram related to defining a geofence on a portable electronic facility.

FIG. 20 is a block diagram related to defining a geofence on a computer.

FIG. 21 is a schematic diagram relating to sending location-based alerts.

FIG. 22 is a schematic diagram relating to analyzing information related to at least one portable electronic facility.

FIG. 23 is a schematic diagram relating to verifying a transaction using a portable electronic facility.

6

FIG. 24 is a schematic diagram relating to tailoring information to the behavior of a user.

FIG. 25 is a schematic diagram relating to providing information to a portable electronic facility based on information received from the portable electronic facility.

FIG. 26 is a block diagram presenting a network of portable electronic facilities.

FIGS. 27A-27C present several graphical user interfaces that may be presented on a portable electronic facility.

FIG. 28 depicts a graphical user interface providing an overview of the locations of all the users in a defined group.

FIG. 29 provides a view of the locations of the users in a defined group.

FIG. 30 presents a detailed display of the location information for one particular user.

FIG. 31 presents a stop report.

FIG. 32 shows a geofence.

FIG. 33 shows several icons that may be assigned to a geofence.

FIG. 34 depicts an address book.

FIG. 35 presents a more detailed view an address book

FIG. 36 depicts a graphical user interface that may be used to define alerts using the system.

FIGS. 37A-37C depict location details as both lists and maps.

FIGS. 38A-38C depicts several menus related to storing location-based information.

FIGS. 39A-39D depict several graphical user interfaces related to the presentation of points of interest on a portable electronic facility.

FIG. 40 presents a graphical user interface that may allow a user to send location information via email or voice.

FIG. 41 presents a graphical user interface that may allow a user to input a zip code.

FIGS. 42A-42B presents a graphical user interface that may allow a user to vary the frequency with which a portable electronic device obtains location information.

DETAILED DESCRIPTION

Referring to FIG. 1 and FIG. 8, the present invention comprises a location services facility that may provide services or data products associated with a geolocation datum 104 associated with a portable electronic facility 300. The location services facility may comprise a database 100 containing aggregate data 102, an application server 108, and a Web server 110. The location services facility may provide the aggregate data 102, in raw or processed forms, to a third-party service provider 200. In some embodiments, the present invention may comprise a network 304, which in some embodiments may be a peer-to-peer (P2P) network, comprising a plurality of facilities wherein each of the plurality of facilities may be a portable electronic facility 300 across which may be distributed the database 100, or its equivalent or constituent components 302, containing, in whole or in part, the aggregate data 102. An expanded view of one aspect of the P2P network is shown in FIG. 3. These embodiments are discussed in detail below and other embodiments will be apparent from the following discussion.

Referring to FIG. 4, the disclosed invention may gather a datum 104 from a portable electronic facility 300. The datum 104 may be stored in the database 100. In particular, the datum 104 may be representative of a position and/or velocity associated with the portable electronic facility 300. Alternatively or additionally, the datum may be representative of an output value from a sensor associated with the portable electronic facility 300. In most cases, an additional datum 104

from the portable electronic facility **300** or another portable electronic facility **300** may also be stored in the database. The aggregate of a plurality of datum **104** from one or more portable electronic facilities **300** may comprise aggregate data **102**, which may be stored within the database **100**.

Referring again to FIG. **1**, the aggregate data **102** may flow from the database **100** to the application server **108**. The application server **108**, in turn, may provide an application based service, a number of which are described below and the general provision of which further comprise the disclosed invention. The application based service may be provided to a user of the portable electronic facility via a Web interface such as a Web browser. In this case, embodiments may comprise the Web server **110** for delivering the service.

Referring to FIG. **2**, the aggregate data **102**, in whole or in part, may be provided to a third-party service provider **200** in a predetermined format, which may be specified by an XML schema. As provided, the data may be formatted or modified according to various needs, including without limitation a need of a first end user **202** who may be a data consumer (such as, revealing consumer behavior); a need of a second end user **204** who may be a user of the portable electronic facility (such as, obeying a privacy agreement associated with the data); and/or a need of the third-party service provider **200** (such as, receiving data in a file that is formatted to facilitate automated processing). When formatted, the data may comprise a report, which may be a computer generated report.

The third-party service provider **200** may in turn provide a service to the first end user **202** or the second end user **204**, wherein the service may be associated with the data. In some cases, the first end user **202** may be a marketing organization. Other cases will be apparent due to the following description.

In one embodiment, the aggregate data **102** may be disaggregated and provided to the third-party service provider as a single data point. This may be useful in many applications including, but not limited to, a service that provides to the end user a map showing the location of the user and the user's immediate surroundings; a service that provides to the end user a map showing the location of a point of interest in the vicinity of the user; a service that provides to the end user a map showing the location of another user; a service that provides to the end user a map showing the location of a pet associated with the user, wherein the pet may be fitted with a collar containing a portable electronic facility; the establishment of a geofence (described below in detail) and the monitoring of the portable electronic facility with respect to its crossing the geofence; and so forth.

In another embodiment, the aggregate data **102** may be scrubbed and provided to the third-party service provider **200** as a generalized dataset. This may be useful in many applications including, but not limited to, a service that may provide to a marketing company demographic information that may be representative of the generalized dataset, which may be representative of a plurality of users in a given geographical area; a service that may provide the user with highway traffic information that may be based upon aggregate traffic flows, which may comprise the generalized dataset; and so forth. For example and without limitation, in one application, the generalized dataset, which may comprise demographic information, may be representative of users' gender and spending habits, wherein the spending habits comprise the means and routes utilized by the users to arrive at a shopping destination. The generalized dataset may further comprise a unique identifier associated with each user represented, wherein the unique identifier may obscure the identity of each

user while also allowing the third-party service provider **200** to discriminate between users, especially during an analysis of the generalized dataset.

In yet another embodiment, the aggregate data **102** may be provided in its entirety to the third-party service provider **200** as a comprehensive dataset. This may be useful in many applications including, but not limited to, a service that may provide to a logistics company detailed tracking information pertaining to a fleet of delivery vehicles, wherein each vehicle is located and tracked through time; a service that shows to a head of a household a plurality of locations representative of each of the members of the household; and so forth. For example and without limitation, a company providing cleaning services may utilize the aggregate data **102** to track how long its employees dwell at each customer location and which routes the employees take to travel to each customer location. This information may be useful in monitoring the efficiency of its employees and in optimizing assignments given to employees, for example and without limitation, by grouping jobs given to a particular employee into a smaller geographical area.

In still yet another embodiment, the aggregate data **102** may be processed to provide a service to a plurality of users. One example is a social networking application. For example, without limitation, a dating service may allow the plurality of users to enter individual preference information associated with a desired characteristic of a mate. Processing of the aggregate data **102** may allow the service to recognize when pairs of mutually desirable mates are in close proximity of each other. Data associated with this recognition may be transmitted to one or both users in the pair, allowing the users in the pair to meet each other. This transmission of data may be in the form of an alert, such as a text message, e-mail, automated telephone call, and so forth. For another example, an interested-based social network application may allow the plurality of users to enter individual preference information associated with a favorite pastime, such as wine tasting. Processing of the aggregate data **102** may allow the service to recognize when events associated with the favorite pastime are being held in proximity to the users. Relevant users may be notified and additional information, which may encourage social interaction between the users, may be provided to users on the basis of the contents of the aggregate data **102**. For example, a subset of users may, based upon observed travel patterns in the aggregate data **102**, be likely carpool candidates to a local wine tasting event.

Generally, in embodiments, the aggregate data **102** may be disaggregated, scrubbed, reformatted, transmitted as-is, stored, processed, and/or formatted in any practicable manner that is useful to any particular third-party application. Moreover, in embodiments, an alert may be transmitted to a user, wherein the alert comprises data that is associated with a recognition that is associated with some form or component of the aggregate data.

Referring now to FIG. **5**, in one aspect, a system according to the present invention may comprise a database server **500**, which may comprise the database **100**; a Web/Application server **502**, which may comprise the application server **108** and the Web server **110**; and a storage device **504**, which may store the database **100**. It should be clear to one of ordinary skill in the art that these servers may exist as one computer, as independent computers, as a network of workstations, as a cluster computer, as a part of a three-tier configuration such as a Web client connected via the Internet to a plurality of Web servers and application servers connected to one or more database servers, and so forth.

In one embodiment, a dual Internet connection **508** may arrive at a Cisco 6509 CIS load balancer/firewall/switch **510**. Additionally connected to the Cisco 6509 **510** may be an a-side **512** and a b-side **514** network, which may have independent main power sources. A Dell 1855 10-blade server **502** may bridge the two networks and may run a Web server and two application servers, namely a mapping server and a routing server. There may be, in each of the a-side **512** and b-side **514** networks, a Dell 2850 database server **500** which may be connected to a RAID 5 storage facility **504**.

The database server **500**, as is mentioned above, may store data representative of positions and/or velocities, which may be the aggregate data **102** and which may be associated with a plurality of portable electronic facilities **300**.

The database server **500** may also store information pertaining to the user's privacy or security. The user may be provided an option to choose if the location and/or velocity of the portable electronic facility associated with the user is recorded in the database **100**. This enables privacy by allowing the user to determine the persistence of data associated with the user. The user may also be asked to provide a personal identification number (PIN), which may be entered into a handset that may be the portable electronic facility **300**. This PIN, perhaps in conjunction with the handset's phone number, comprises an authentication code needed to access a service enabled by the present invention, for example and without limitation, a Web site that provides a map showing the location of the user.

The database server **500** may also store information pertaining to the user's level of access to a service enabled by the present invention. This access level may be used to determine a user's privileges. In one instance, a parent may want to allow a child to have access to the location of other family members, but not allow the child to establish a geofence (described below) or an alert. In another instance, a plurality of handsets may be configured as peers in the network **304** when the network **304** is embodied as a P2P network. In this embodiment of the network **304**, a first peer may exchange location and/or velocity data with a second peer provided that the second peer has an appropriate level of access to such information from the first peer. In yet another instance, the exchange of information from the first peer to the second peer may be conditioned on the second peer having both the appropriate level of access and the user of the second peer providing a PIN and/or authentication code that corresponds to a code stored in the database **100**.

In other embodiments, some or all of the information pertaining to the user's level of access to a service is stored in the distributed database component **302** associated with the portable electronic facility **300**.

Referring again to FIG. 1, the application server **100** may host a geospatial application. The geospatial application may provide geo-coding, mapping, or routing functionality. Mapping functionality may comprise overlaying onto a map a current location and a plurality of stored, past locations of the portable electronic facility. Routing functionality may comprise overlaying onto the map the current location of the portable electronic facility **300** along with a calculated path from the current location to a specified destination. The calculated path may be a straight line, a route that follows geographic features such as a road or a river, a path between navigational aids such as very high frequency omnidirectional range (commonly known as a VOR), a great circle path, and so forth. Both the routing and mapping functionality may be provided by a commercial, off-the-shelf (COTS) application, such as the MapQuest Enterprise Server.

The application server **100** may host an alert application. The alert application may transmit the alert to a user in response to the occurrence of an event designated by the user as an alert-generating event. The alert may be sent via e-mail, short message service (SMS), interactive voice response (IVR), voice, instant message (TM), or any other practicable method.

The application server **100** may host a geofencing application, which monitors the location of one or more portable electronic facilities with respect to a geofence.

The Web server **110** may provide a front-end interface to the user. The pages served by the Web server **110** may include geo-coding, mapping, routing, geofencing, or any other functionality supported by the application server **108** or the database **100**.

The portable electronic facility **300** may take a number of portable forms, including but not limited to a cell phone; a PDA; an electronic watch; a handheld GPS; a laptop computer; a portable music player such as an Apple iPod; an electronic keychain; a camera; or any other portable electronic facility.

Referring now to FIG. 6, in addition to including technology providing for the ascertainment of the location of itself, the portable electronic facility **300** may comprise additional capabilities and facilities, such as a random access memory facility **600**; a display facility **602**, which may comprise a color display, a backlight, a liquid crystal display (LCD), a light-emitting diode (LED) screen, an organic light-emitting diode (OLED) screen, a flexible organic light-emitting diode (POLED) screen, or a projection display; a power facility **604**, which may comprise a battery, a power port, a photovoltaic facility such as a solar cell, or a fuel cell; an input facility **608**, which may comprise a touch pad, a key pad, a stylus-based input facility, a speakerphone, or a microphone; a data communication facility **610**, which may comprise a telescoping antenna, a fixed external antenna, an internal antenna, a serial data port, a parallel data port, a WiFi facility, a Bluetooth facility, or a ZigBee facility; a central processing unit **612**; an operating system **614**; a software application **618** such as but not limited to a game, a relationship management application, an expense tracker, a to-do list, a calendar, a notepad, a Web browser, an e-mail client, an audio file player, a photo viewer, a video viewer, a text editor, a time tracker, a day planner, a clock, a calculator, a dictionary, a file viewer, a synchronization manager, a virtual private network (VPN) client; and so forth.

The portable electronic facility **300** may provide functionality complementary to and, in some embodiments, enhancing the location based service. Such functionality may include Web browsing, Web searching, wireless communication, software application execution, software application interpretation, entertaining lighting effects, a moving map display, a static map display, a map display with zoom capability, a color map, a grayscale map, a black-and-white map, and so on.

In various embodiments, the portable electronic facility **300** could be used in a vehicle, while camping, during the exploration of terrain, mounted on an animal such as but not limited to a dog collar, during a game, while walking through a city, and so forth.

The portable electronic facility **300** may communicate with the other elements of the location services facility, for example and without limitation the application server **108**, the Web server **110**, the database **100**, the third-party service provider **200**, the first end user **202**, the second end user **204**, another portable electronic facility **300**, the distributed database component **302**, the peer-to-peer network **304**, the data-

11

base server **500**, the Web/application server **502**, the storage device **504**, the dual internet connection **508**, the Cisco 6509 **510**, the A-side network **512**, and/or the B-side network **514**. This communication may comprise two-way communication or one-way communication. In embodiments, the portable electronic facility **300** may comprise a radio frequency (RE) transmitter/receiver providing the capability of sending and/or receiving data from a cellular telephone network. The portable electronic facility may also or alternatively comprise an RE transmitter/receiver for sending and/or receiving data from a local area network, such as and without limitation an 802.11 b “Wifi” network. The data communication facility **610** may further comprise a physical connector, such as a docking port, which may allow for the synchronization of data to and/or from the portable electronic facility **300** and a host computer, such as a personal computer.

One consideration in the design of the portable electronic facility **300** may be battery life. There are a number of factors that may affect battery life. One factor may be the power density of the battery. Another factor may be the volume of the battery. Yet another factor may be the power consumption of the portable electronic facility **300** connected to the battery. In the portable electronic facility **300**, it is typical for the power consumption to be dominated by RE transmission electronics that may be integral to the facility **300** and of which the data communication facility **610** may be comprised. This is due to theoretical and practical limitations of the physics of RF transmission. The battery life of the portable electronic facility **300**, then, may be improved by limiting the amount of time that the portable electronic facility **300** is transmitting data: the transmission electronics may be powered down the rest of the time. Likewise, it is known that the power consumption of RF receive electronics, of which the data communication facility **610** may also be comprised, may have a considerable impact on the battery life of the portable electronic facility **300**. It follows that methods for limiting the amount of time that the portable electronic facility **300** is sending and/or receiving data may be present in some embodiments of the location services facility. These methods may comprise varying the length and/or frequency of transmissions to and/or from the portable electronic facility **300**.

Another consideration in the design of the portable electronic facility **300** may be a speed with which the facility provides the user with data and/or the accuracy of the data. In embodiments, the portable electronic facility **300** and/or the location services facility at large may be designed to vary the length and/or frequency of data transmissions to and/or from the electronic facility **300** to improve the speed with which the facility **300** provides a user with data and/or the accuracy of the data.

One aspect of the location services facility is to provide location information to the user. Location information may comprise latitude; longitude; altitude; depth; pitch; roll; yaw; time; velocity; or orientation and/or distance to or from a waypoint, an origin, a destination, magnetic north, or true north. The location may be presented to a user in a number of embodiments including, without limitation, a map, a moving map, an interactive map, a textual description, a spoken description, a color code, an aural code, an e-mail, a text message, a pager message, a printout, and so forth.

The location information provided by the location services facility to the user may originate from the use of various methods incorporating data from a sensor facility such as, without limitation, a global positioning system (GPS), a radio frequency identification (RFID), a plurality of cell phone towers (for example, for time and/or triangulation), an altimeter,

12

a depth gauge, a gyroscope (including “gyroscopes” that use a vibrating structure, a laser, or a MEMS device), an inertial sensor, a compass, an accelerometer, a speedometer, a seismometer, a magnetometer, a thermometer, a photon detector (including, but not limited to, a visible camera, an infrared (IR) detector, an ultraviolet (UV) detector, an X-ray detector, a gamma-ray detector, a Geiger counter), a hygrometer, a heart rate monitor, a blood glucose meter, a blood oxygen meter, an electrical sensor, an electrical interference sensor, a current sensor, a resistance sensor, a thermistor, an electrostatic sensor, a frequency sensor, a temperature sensor, a heat sensor, a thermostat, a differential light sensor, an opacity sensor, a scattering sensor, a diffraction sensor, a refraction sensor, a reflection sensor, a polarization sensor, a phase sensor, a fluorescence sensor, a phosphorescence sensor, an optical activity sensor, an optical sensory array, an imaging sensor, a calibrated micro mirror array, a calibrated pixel array, a micro mirror array, a pixel array, an angular momentum sensor, a rotation sensor, a rotation speed sensor, a rotation direction sensor, a velocity sensor, an inclinometer, a momentum sensor, a smoke detector, a fire sensor, a heat detector, a combined heat and smoke detector, a vapor sensor, a gas sensor, a signal sensor, a wireless signal sensor, a cellular signal sensor, a Wi-Fi signal sensor, an Internet signal sensor, a touch sensor, a contact sensor, a viscosity sensor, a position sensor, a height sensor, a ray detector, a microwave sensor, a proximity sensor, a distance sensor, a motion sensor, a range sensor, a mote, a marker, a powered marked, a signal emitter, a signal receiver, a powered signal emitter, a powered signal receiver, a chemical sensor, a fire sensor, a hazardous material sensor, a hazardous vapor sensor, a biohazard sensor, a bacteria sensor, a virus sensor, an anthrax detector, a nerve gas sensor, a poisonous gas sensor, a carbon monoxide detector, an energy sensor, or an aerosol sensor. RFID tracking may, without limitation, comprise a portable electronic facility further comprising a RFID transponder that is interrogated by electronic equipment that is installed along a roadway, along a sidewalk, at the entrance of a building, at the egress of a building, or in a building. Once created, the location information may be compiled, accessed, processed, searched, sorted, or in any other way manipulated for the benefit of the first end user **202**, the second end user **204**, or any other entity that values the user’s location information. In embodiments a location may be obtained from a database, such as based on the location of a wireless access facility, such as a Wi-Fi or 802.xx access point, switch, or similar device.

In embodiments, an individual location information sample, which may be a datum **104**, may be subject to errors, which may be due to physical or practical limitations of the location services facility. For example, cell phone triangulation systems are limited by RF multipath effects due to large metal structures such as building or water towers. One method of compensating for these errors may comprise processing multiple location samples to determine, via statistics or heuristics, to what extent the individual location information sample may be reliable. Another method of compensating for these errors may comprise processing multiple location samples to determine an aggregate location information sample that may include information such as mean location and standard deviation, which may provide a more accurate determination of location than the individual location information sample.

Referring now to FIG. 7, the portable electronic facility **300** may comprise a state machine **702** heuristic approach to obtaining a GPS fix **700**. The state machine **702** may comprise a plurality of states, **704**, **708**, **710**, **712**, **714**, and **718**. The state machine **702** may comprise a fix delay, which may

13

be a string that may be processed by the central processing unit **612**, the operating system **614**, the software application **618**, the geolocation facility **620**, or any other facility associated with the geolocation facility **620**. In the plurality of states, “mposition:delay=tow” may indicate a fix delay that may take no greater than 32 seconds to provide a limited degree of computation for determining a low-accuracy velocity of the portable electronic facility **300**. “mposition:delay=high” may indicate a fix delay that will take no greater than 3 minutes and 32 seconds to provide a substantial degree of computation for determining a high-accuracy velocity of the portable electronic facility **300**.

The Inside State **704** may reflect that the facility **300** may be receiving the GPS fix **700** from a tower. In this state, the facility **300** may sleep for 90 seconds and then may attempt to receive a fix, at first, using mposition:delay=low and then for every fix thereafter using mposition:delay=high. Should the facility **300** receive five fix attempts in the Inside State **704**, the facility **300** may go into the Sleep State **704**.

The Stopped State **710** may reflect that the facility **300** may be receiving the UPS fix **700** from a satellite and that the facility **300** may be associated with a speed, according to the fix’s National Marine Electronics Association’s (NMEA) string **720**, of approximately 0 kilometers per hour (KPH). In this state, the facility **300** may sleep for approximately 90 seconds and then may attempt to receive a fix using mposition:delay=high. Should the facility **300** receive five sequential GPS fixes **700** in the Stopped State **710**, the device may go into the Sleep State **704**. In the Stopped State **710**, the facility **300** may send every UPS fix **700**, of which a datum **104** may be comprised, to a datum receiving facility, which may, without limitation, comprise the database **100**, the application server **108**, the Web server **110**, another portable electronic facility **300** such as via the P2P network **304**, or any other facility associated with the database **100** or the distributed database component **302**.

The Moving_Slow State **712** may reflect that the facility **300** may be receiving the UPS fix **700** from a satellite and may be associated with a speed, according to the fix’s NMEA string **720**, of greater than approximately 0 KPH and less than approximately 17 KPH. In this state, the facility **300** may sleep for 60 seconds and then may attempt to receive the UPS fix **700** using a mposition:delay=high and every UPS fix may be sent to the datum receiving facility.

The Moving_Med State **714** may reflect—that the facility **300** may be receiving the UPS fix **700** from a satellite and may be associated with a speed, according to the fix’s NMEA string **720**, of greater than approximately 17 KPH and less than approximately 106 KPH. In this state, the facility **300** may sleep for 30 seconds and then may attempt to receive the UPS fix **700** using mposition:delay=high and every UPS fix **700** may be sent to the datum receiving facility.

The Moving Fast state **718** may reflect that the facility **300** may be receiving the UPS fix **700** from a satellite and may be associated with a speed, according to the fix’s NMEA string **720**, of greater than approximately 105 KPH. In this state, the facility **300** may sleep for 10 seconds and then may attempt to receive a GPS fix **700** using mposition:delay=thigh and every UPS fix may be sent to the datum receiving facility.

The Sleep State **704**, as is mentioned above, may reflect that the facility **300** may have received five UPS fixes in a row in the Stopped State **710** or may have received five GPS fixes in a row in the Inside State **708**. In this state, the device may sleep for approximately two minutes and then attempt to receive a UPS fix **700** alternating with the use of mposition:delay=high and mposition:delay=low.

14

The state machine may also note a significant position change wherein a new UPS fix may generate a measured change in distance of greater than 10 kilometers. A check for the significant position change may be taken on every UPS fix **700** in the Sleep State **704** or Inside State **708**.

When the portable electronic facility **300** is switched into an operational mode, the facility **300** may make an attempt to retrieve a UPS fix using an mposition:delay=low. If the facility **300** cannot receive a satellite UPS fix **700** on a first fix attempt, the facility **300** may immediately or soon thereafter make another attempt to receive a UPS fix **700** using mposition:delay=high. In either case, the facility **300** may consequently be considered to be initialized.

The facility **300** may, based upon its current state, make attempts to receive the UPS fix **700** at a rate, which may be periodic. In the event that the UPS fix **700** cannot be obtained or is invalid, the facility **300** may alert a user of the facility **300**. In the event that a valid UPS fix **700** cannot be obtained during five consecutive attempts, the facility **300** may discontinue attempts to get the UPS fix **700**, which may necessitate a manual restart of the facility **300** to renew attempts to obtain the GPS fix **700**.

Once obtained or calculated, the location information, which may comprise the GPS fix **700**, may be used in an application service including, but not limited to, an entertainment application service such as location-aware games, a commerce application service such as location-based transactions, an information application service such as mapping a route from an origin to a destination, or any other application service specified, mentioned, implied, or made apparent by this discussion.

Referring now to FIG. 9, as mentioned above, the location services facility may support a geofencing application that involves the geofence **900**. In one case, the geofence **900** is the circumference of a circle that is defined by a user who specifies a geographic location **902** for its center and a radius. In general, the geofence **900** may be defined as any arbitrary boundary between one geographic area and another, wherein the boundary may be stationary or may move, wherein said movement either may be correlated to the movement of a physical object such as the portable electronic facility **300** or may be determined arbitrarily. In any case, the geofencing application may be the alert application and, therefore, may generate the alert when the portable electronic facility **300** crosses the geofence **900**. This alert may be transmitted to the user who specified the crossing of the geofence **900** as an alert-generating event. Alternatively or additionally, this alert may be transmitted to a second user who either opted to receive the alert or who was designated to receive the alert. Optionally, the alert may pertain to a facility in the vicinity of the geofence **900**, such as and without limitation an advertisement for a nearby restaurant.

In embodiments, the user may define and/or manipulate a geofence **900** via the Web browser of the three-tier architecture. Alternatively, the user may define and/or manipulate a geofence **900** via the portable electronic facility **300**, for example and without limitation via the input facility **608** of the portable electronic facility **300**.

The location services facility may support a number of end uses. One end use may comprise a location based adaptable user interface. For example, in an embodiment, the portable electronic facility **300** may be a cell phone. A screen integral to the cell phone may display information to the user of the cell phone. Under usual circumstances, the screen may display a small menu of options, such as show location and get directions. However, when the cell phone is within proximity of a restaurant, the screen may display an additional menu

15

option make dinner reservation. This adaptation to the menu of options is an example of a location based adaptable user interface.

Another end use may comprise the tracking of the location of the portable electronic facility **300**, which has been described above.

Yet another end use may comprise providing business information associated with the portable electronic facility. For example, a comprehensive stop report provided by the location services facility may comprise a plurality of entries comprising a stop identification, a time, a duration, and a location. The stop identification may comprise a unique identifier comprising a number associated with a stop made by a delivery truck. The time may be associated with a time at which the delivery truck stopped. The duration may be associated with the time that the delivery truck dwelled at the stop. The location may be associated with the geographic location of the stop. In total, the comprehensive stop report may provide information useful to an operator of a business in monitoring the performance of a fleet of delivery trucks.

Still yet another end use may comprise remotely affecting the portable electronic facility **300**. In one embodiment, the location services facility may start, stop, or change an application on the facility **300**. The application may comprise, without limitation, un/up, a route, a to-do list, a calendar, a calculator, an expense report, a mileage tracker, a phone book, and so forth.

Another end use may comprise outputting location information on the portable electronic facility **300**. As is mentioned above, the portable electronic facility **300** may provide to the user location information associated with the portable electronic facility **300**, for example and without limitation, information in the form of a map. The portable electronic facility **300** may augment the information provided by the location services facility with information from the sensor. For example, the location services facility may provide mapping information to the portable electronic facility **300** according to the location data provided by the facility **300** to the location services facility. Upon this map, the facility **300** may overlay an artificial horizon, which provides pitch and roll information to the user. This pitch and roll information may be provided to the portable electronic facility **300** by the sensor.

Yet another end use may comprise outputting location information on the portable electronic facility **300**, wherein the location information itself depends upon the output sensor. For example, in an embodiment wherein the sensor is a visible camera, images of surrounding terrain may be captured by the camera and may be transmitted to the location services facility. The location services facility may analyze these images and transmit location information associated with the images back to the portable electronic facility **300**. This location information may then be output by the portable electronic facility **300** for presentation to the user.

More generally, a plurality of end uses may comprise presenting location based information to the user in response to the characteristics of a location. In one embodiment, as described above, the characteristics of a location may be the terrain in the vicinity of the location. In other embodiments, the characteristics of a location may, without limitation, comprise the barometric pressure, humidity, temperature, radio-activity, depth, infrared lighting, visible lighting, ultraviolet lighting, and so forth.

Another end use may comprise providing location information associated with a transaction. In one embodiment, a person may present a credit card associated with the user to a merchant at a point of sale. The merchant or merchant's bank

16

may query the location services facility to determine the location of the portable electronic facility **300** associated with the user. If the portable electronic facility **300** is located at the merchant then the user may be presumed to be located at the merchant and the person may be presumed to be the user. Therefore, the transaction may be authorized. Conversely, if the portable electronic facility **300** is located at a location other than at the merchant then the location of the user may be deemed to be in question and the person is may not be deemed to be the user. As a result, the transaction may be denied or the merchant may be required to further verify the identity of the user.

Yet another end use may comprise tailoring information to the behavior of a user. In one embodiment, the location services facility may recognize that the route a user usually takes to and from work is suboptimal. In response to this behavior of the user, the location services facility may provide to the user a custom tailored, daily-commute route map.

More generally speaking, end uses of the location services facility may provide information to the portable electronic facility **300** based on information received from the portable electronic facility **300**, including but not limited to information associated with the user's behavior.

Referring now to FIG. **10**, the present invention may provide an adaptable user interface **1000**, which may transmit a current location **1002** of a portable electronic facility **300**, such as to another device or system and may receive an electronic storage file **1004** or other indication of the current location of the portable electronic facility **300**. The file or message may contain code that enables a specific user interface capability for the portable electronic facility **300**, no that it displays a version of the user interface **1000** based on the contents of the electronic storage file **1004**, message or other contents. The portable electronic facility **300** may take various forms, such as, without limitation, a mobile phone, a GPS enabled mobile phone, a CDMA enabled mobile phone, a GPRS enabled mobile phone, a mobile phone with a camera, a mobile phone with browser capabilities, a UPS unit, a tracking unit, a portable electronic device with a compass, a laptop computer, a personal digital assistant, an MP3 player, a camera, a handheld device, a pager, and/or a portable gaming device. The portable electronic facility **300** may be wearable.

The storage file **1004** may be transmitted from a remote location and may without limitation be in a format such as an XML document, a script, an HTML document, a program, a database, a table, a message, a folder, an application, an animation and/or a text file. The storage file **1004** may contain user interface information, such as specific menus that may be for a specific location and/or specific allocations that may be for a specific location. The storage file **1004** may be updatable, wherein the user may manually update the storage file **1004** with information or wherein the storage file **1004** may be automatically updated with information. The update may occur when a user stops at a location.

In embodiments, the storage file **1004** may be stored locally and/or remotely. The storage file **1004** may contain similar locations, such as without limitation points of interest, which may be displayed based upon factors such as speed, location, and/or user preference. The user preference may be maintained in a user-preference file, which may be stored locally, and/or remotely, and which in certain embodiments may comprise the storage file **1004**.

In embodiments one feature of the adaptable user interface **1000** is that the user may modify the interface **1000**. For example, a menu selection may be modified, automatically and/or manually. Selections from the menu may be added,

17

such as from a list of menu options. Another feature of the adaptable user interface **1000** is that an application selection may be modified, automatically and/or manually, wherein the modification may be the addition and/or removal of an application, which may be selected from an available list. Yet another feature of the adaptable user interface **1000** is that it may maintain location specific information, wherein the information may be available near the location, wherein user orders may be created. The user orders may be based without limitation on a user list; the proximity of a store; an order sent by text; an order sent by voice; or another order that may be transmitted. The locations in the storage file **1004** may be based on a coordinate system, such as and without limitation the Cartesian coordinate system; the polar coordinate system; latitude and longitude; and/or latitude, longitude and altitude.

The adaptable user interface **1000** may produce results, such as an answer to a user's query. The results may be based on the location of the portable electronic facility **300**, wherein the results may be sorted based on the speed and/or direction, preferences, and/or accessibility of locations of the portable electronic facility **300**. Web search results may be based upon the location of the portable electronic facility **300** and may be sorted based on portable electronic facility **300** speed, portable electronic facility **300** direction, preferences, and/or accessibility of locations. A localized search may be conducted based on the location of the portable electronic facility **300**, wherein the search results may be sorted based on portable electronic facility **300** speed, portable electronic facility **300** direction, preferences, and/or accessibility of locations.

Referring now to FIG. **11**, an adaptable user interface **1000** may provide for receiving location-based information **1100** associated with the portable electronic facility **300** and outputting a version **1102** of such information **1100** through the portable electronic facility **300**. The information **1100** may be received in response to a transmission of the location of the portable electronic facility **300**. The output version **1100** of such information **1102** may without limitation be visual, audio, a facsimile, an email, voice, a light, a change in the intensity of a light, a change in the color of a light, via SMS, via an instant message, via a text message, and/or an application that may only be available at certain locations. In some embodiments, at least one menu item may be changed in response to the information **1100**. Moreover, the user may modify the interface **1000**.

The information **1100** may be defined in relation to an object and/or a location. Multiple networks may supply the information **1100**, which may be altered such as created, updated, supplemented, augmented, reduced, encoded, decoded, encrypted, decrypted, and/or deleted. Alterations may be at a frequency that may be based on the velocity of the portable electronic facility **300** and/or the location of the portable electronic facility **300**. The information **1100** may be a geocentric list.

The information **1100** may be specific to a user and may without limitation alter the look and feel of the facility **300**, alter the functionality of the facility **300**, be in an XML format, be in a database format, and/or be in a text file format.

An alert, which may relate to an item on a list, may be triggered in response to the information **1100**.

Referring now to FIG. **12**, the present invention may provide for location tracking **1200**, wherein a location **1202** of a portable electronic facility **300** may be transmitted, stored in a file **1204** (which, in embodiments, may comprise the electronic storage file **1004**), stored with other information (such as and/or associated with aggregate data **102**, datum **104**, geographic location **902**, and so forth) in the portable electronic facility **300**, and reported along with an indication of

18

the movement **1208** of the portable electronic facility **300**. The file **1204** may be stored remotely (such as and without limitation in database **100**, in a distributed database component **302**, in a database server **500**, and/or in a storage device **504**). The file **1204** may maintain an archive **1210** of a plurality of locations **1202** associated with the portable electronic facility **300**, which may be displayed and in which an indication of movement **1208** may be reported.

The information itself may be displayed on a map **1212** and may comprise an indication of speed and/or direction **1214**. The location **1202** may be masked, wherein the masking may involve substituting a different location for the actual location **1202**.

In applications, the location tracking facility **1200** may be used by families to track members of the family, such as children or elderly members of the family. For example, in tracking the location of a child, the tracking may identify a position, within a yard, upon the activation of certain triggers, such as upon request by another family member, if the child is lost, and/or only at specified times such as a day of the week and/or time of day. For example, in tracking the location of elderly, the tracking **1200** may be in a home, in a hospital, and/or in a care facility.

In other applications, the location tracking **1200** may be used to track driving and/or vehicle location. This tracking **1200** may comprise tracking location **1202**, speed, and/or a set path. An alarm, which may be an alert, may be sent when the driving is classified as speeding. An alert may also be sent if the vehicle position is outside a boundary, wherein the boundary is associated with shipping a hazardous material. In some applications, the location tracking may encompass the vehicle location of every vehicle in a fleet.

In general applications, the tracking **1200** may be remotely set, permanently enabled, and/or disabled only from a remote location. Thus, the portable electronic facility **300** may be controlled remotely, which may include the remote control of an application (such as and without limitation software application **618**) within the portable electronic facility **300**.

In yet another application, the tracking **1200** may be used for computer gaming, wherein one or more features of the game may be based on the real-world location **1202** of the portable electronic facility **300**. In embodiments the real-world location **1202** of the portable electronic facility **300** may be used to trigger other actions or events within the game. In such embodiments, the real-world location may be led to a program or system that generates game conditions based on the location, such as from a table, database, or other facility, or based on real-world information associated with the location, such as weather information, stored views of the location, maps of the location, or the like. For example, the current weather conditions in the environment surrounding the portable electronic facility **300** may be retrieved from a server that obtains weather information, and a game operating on the portable electronic facility **300** may present similar conditions to the user of the portable electronic facility **300**, such as in a role-playing game, a driving game, first person shooting game, or other simulation game. Similarly, a map for area surrounding a user may be used to generate a simulated environment in the game that resembles the user's real world environment. For example, locations of buildings and roads can be used to create a "track" in a driving game, or to create obstacles or locations in a role-playing game. In embodiments locations of other portable electronic facilities **300**, such as those used by friends or family members of a user, can be used to generate game elements, such as to allow users to "race", "battle", or otherwise interact in a multi-player game that draws elements such as weather, roads, or buildings from

the real-world environments of the users of the portable electronic facilities **300**. Thus, in a variety of embodiments, a game on a portable electronic facility **300** may be location-based.

In still another application, the location tracking **1200** may be used as a basis for selecting entertainment such as determining available shows, movies, and/or food facilities. For example, a menu of video or movie clips may be made available based on the location of the portable electronic facility **300**, such as showing movies that contain scenes that depict areas that are in proximity to the current location of the facility **300**, showing tourist information for the area near the facility **300**, or the like.

In still yet another application, the tracking **1200** may be associated with a police activity, such as, without limitation, tracking shoplifters, tracking criminals, placing a portable electronic facility **300** in a money bag, and/or placing a portable electronic facility **300** in a bank teller drawer.

In another application, the tracking **1200** may be associated with a security activity, such as and without limitation tracking people within a facility, wherein the tracking may comprise tracking direction and/or speed; tracking personnel such as sales people, social workers, home health care workers; tracking dangerous substances; and/or tracking dangerous shipments. For example, a geofence may be established around a particular location, so that an alert is sent if a person exits the area of the geofence, such as if a home health care worker leaves a scene, a worker enters a hazardous area, a shipment departs from a planned route, a social worker fails to appear at a designated location for an appointment, a maintenance worker fails to appear at a designated location, or the like.

In still another application, the tracking **1200** may be associated with a pet, such as and without limitation tracking the pet within a yard and/or if lost. A geofence may be established around the pet, so that an alert is sent if the pet departs the region of the geofence.

In yet still another application, the tracking **1200** may be associated with a school, such as and without limitation tracking students and/or employees at all times and/or only if they leave school property. A geofence around the school can allow a teacher, administrator or parent know when a child arrives at the school, leaves the school, or the like. Thus, portable electronic facilities **300** can be used to check attendance against the rolls of the school, and to determine the locations of absent students who possess such portable electronic facilities **300**.

In an embodiment, the tracking **1200** may be associated with health care, such as and without limitation tracking patients, doctors, and/or nurses. In this application, the tracking **1200** may be within a health care facility, outside a health care facility, and/or may comprise finding the closest doctor and/or nurse in an emergency. A geofence may be established, for example, indicating when a patient has left a hospital, or indicating when a doctor arrives or departs the proximity of the facility, such as to generate an alert if there are not enough staff available to handle an emergency.

In another application, the tracking **1200** may be associated with real estate, such as, without limitation, tracking a location of a house for sale, which may be associated with a picture, directions, and/or tracking visitors to the real estate. For example, a portable electronic facility **300** may be associated with a digital camera, and the location of a picture or recording, as determined by the tracking facility **1200**, may be embedded in the picture or recording for future retrieval of the location of the picture. Such a picture or recording location capability may be used to know the location of a real estate

location, the location of an accident, the location where a photo was taken during a vacation, the location of a crime, or the location of another event that is recorded on the digital camera.

The capability to record the location of a picture or a recording may support transport logistics, the adjustment of traffic signals, the documentation of potholes, the documentation of defects in infrastructure, and/or an insurance purpose. The insurance purpose may comprise documenting the location of accident; capturing a picture or recording of an accident such as for the purpose of adjusting claims; storing driving habits on file such as for the purpose of determining safe driving, which may be associated with changes in insurance prices based on driving speed. The picture or recording location tracking may support bounty hunters, private investigators, police, detectives, or other in, for example, tracking people. For example, tracking **1200** may support tracking a stalker, for example, in determining a distance in relation to another person where, in some embodiments, an alert that may be sent to police is sent if the stalker is too close to a person.

In embodiments, the tracking **1200** may support a maid service in, for example, tracking the time that a maid spends at a location and, perhaps, comparing the actual billed charges to the tracked time.

In embodiments the tracking **1200** may support flea management in, for example, tracking the dwell time of a vehicle in the fleet on a location and, perhaps, comparing an actual billed charge to the tracked dwell time at a location, which may be a tracked location **1202**. This tracking **1200** may serve a purpose in project accounting.

The tracking **1200** may support armored cars in, for example, tracking locations of the armored cars and, perhaps, tracking deviation from a set path. The tracking **1200** may support parole tracking such as the tracking of a person, perhaps with respect to an allowable zone, wherein if the person being tracked is outside an allowable zone (such as and without limitation a geofence **900**) an alert may be sent. The tracking **1200** may support emergency dispatching, which may be associated with a known location of a person and which may provide directions to the known location. The tracking **1200** may support roadside assistance dispatching, which may be associated with the known location of a person and which may provide directions to the known location. The tracking **1200** may support an alert, which may be an alert where the alert may be without limitation audio, visual, associated with a location that may be user determined, in response to a vehicle, via fax, via email, via instant message, via a text message, via SMS, via an Internet protocol, via voice, via voicemail, in the form of a vibration.

In embodiments, the tracking **1200** may be associated with the location of a lobster trap, wherein the tracking may be further associated with an indication of whether the lobster trap has been previously checked.

In embodiments the tracking **1200** may be associated with social networking, such as, without limitation, introducing certain people to each other; introducing certain groups of people; communicating with at least one individual; and/or communicating with a group of individuals, such as informing them of an event at a location (which may be the location **1202**).

Referring now to FIG. **13**, the present invention may provide business information by storing the location of a plurality of portable electronic facilities **300**, possibly in an electronic storage file **1004** or a location-containing file **1204**, which may be remote. The invention may provide access to the storage file **1004** or **1204**, which may contain information

21

pertaining to demographics, locations and motion of the portable electronic facilities. Access to the storage file **1004** or **1204** or information may be password protected and the storage file **1004** or **1204** or information may be encrypted. The storage file **1004** or **1204** may be an XML document, a database, a table or a text file.

The invention may provide demographic information associated with the portable electronic facilities **300**, such as the number and types of facilities **300** with particular demographic or other characteristics in a certain area or the speed and location of the facilities **300**. For example, location information may be associated with demographic information or information about past behavior of users of portable electronic facilities **300**, to determine the characteristics of users in an area. For example, if many users within a geofence **900** that is associated with a large retail store are shown to have high income and to be interested in electronics, then the store can make an announcement about a high-end electronics item that is for sale. Similarly, if many users within the area of a restaurant have a preference for a particular food (based on past purchases), then the restaurant can prepare to serve that food, such as by ordering and offering that food. Thus, a system may include a geofence for establishing a proximity of a location and may track or take actions based on the characteristics of users within that geofence, such as determined by past actions of those users, such as purchases, browsing, or other behavior performed by the users using their portable electronic **300**.

In embodiments, tracking information may constitute traffic patterns, and such traffic patterns may be compared to historical traffic patterns for infrastructure design.

Referring now to FIG. **14**, the present invention may provide methods and systems for effecting change on a portable electronic facility **300** in response to location information **1100**. The method may involve receiving location information **1100** on the portable electronic facility **300** and effecting a change on the portable electronic facility based on the location information **1100**. The change may involve activating the portable electronic device, powering off portable electronic device, placing the portable electronic device in standby mode, starting an application, stopping an application or the output of information. The output may involve audio, video, a picture related a location, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration, stimulation at least one of the five senses or an alert. The alert may involve fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or stimulation of at least one of the five senses.

In another embodiment the change may involve a reminder regarding an item on a list and the list may be a geocentric list. For example, the reminder may be to purchase an item at a location in close proximity to the portable electronic facility **300**. For example, a user's grocery list may be presented in response to the user entering a geofence **900** that is defined around a grocery store. In another example, the reminder may be to perform a task at a location in close proximity to the portable electronic facility **300**. For example, in arriving within a geofence **900** that is defined around a friend's home, a user may be reminded to drop off an item at the friend's house. Thus, the methods and systems described herein include location-based reminders, to do lists, and task lists, and in embodiments the location-based reminders are triggered by the proximity of a portable electronic facility **300** to a geofence **900** that is defined by a user of the portable electronic facility **300**.

In another embodiment the change may involve a change to at least one item on a menu. For example, the change may be

22

the removal or addition of a class of point of interest from or to a menu. For example, the class of point of interest may be a hotel, store or tourist location. For example, when a user is far from home, nearby locations of stores, tourist locations and hotels may be presented to a user in the user interface, but such locations may be removed from the menu when the user is close to home, on the assumption that a user is familiar with stores near the user's home and that the user will not need hotel or tourist information near home. In embodiments a portable electronic facility **300** may allow a user to modify preferences for what items are presented when a user is near a particular location or far from that location.

In another embodiment the change may affect the availability of an application. The change may also involve enabling free calling when within a certain geofence, such as within a home or a user defined geofence. Thus, a telecommunications system may track user locations through their portable electronic facilities **300**, and may determine the presence of a user within a geofence **900** associated, for example, with a home, business, school, or other location of the user. The telecommunications system may vary the rate charged to the user based on proximity to the geofence **900**.

In embodiments location information **1100** may relate to the accuracy of the location information or be stored in relation to a particular location, coordinate (such as Cartesian or polar coordinates), latitude, longitude or altitude. The information may refresh continuously, in accordance with set preferences or in response to a request. The frequency of the requests may be varied in response to speed, location, specified preferences, proximity to a point of interest, or changes in a geofence **900**. The frequency of the requests may also be varied in such a manner as to have the effect of extending the battery life of the portable electronic facility **300**. Thus, a power management application may manage the use of a location-based application based on the location of a user to preserve battery life in a portable electronic facility **300**.

In embodiments, a user may make a request, such as a request for help, such as in response to pressing a panic button or activating a panic mode on a portable electronic facility **300**. The request for help may include location information **1100**, information relevant to the emergency or other information. The request may include a picture or recording taken by a camera of the portable electronic facility **300**, and the picture or recording may have embedded in it location information.

In embodiments the location information **1100** may be received via SMS, fax, email, instant message, text message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, interact, text or as a file.

Referring now to FIG. **15**, the present invention may provide for methods and systems of triggering the output of location-based information **1100** involving receiving information via a portable electronic facility **300** and outputting location-based information **1100** based on the received information.

The information **1100** may be received via a sensor **1502**, which may measure the parameters of a device, facility **300** or vehicle. The sensor may provide information relating to the fuel-level of a vehicle. The fuel may be gasoline, diesel, propane, hydrogen, alcohol-based or ethanol. The sensor may transmit the information via Bluetooth or by other means. In embodiments the location-based information **1100** may consist of a list of fueling stations in the area, fuel prices and hours of operation. The sensor may also enable monitoring and the location-based information **1100** may be relevant to the monitoring.

23

Referring to FIG. 16, the present invention may provide methods and systems for location determination involving capturing characteristics of a location 1202 using a portable electronic facility 300, transmitting those characteristics and receiving location based information 1100. The characteristics may be captured as a picture, a photograph, verbally or using at least one sensor. The picture may be entered by a user. The photograph may be taken with a camera on the portable electronic facility 300. The sensor may be a temperature sensor, a velocity sensor, a direction sensor, an altitude sensor, a pressure sensor, a fluid level sensor or a power level sensor. The characteristics may be transmitted via SMS, fax, email, instant message, text message, interact protocol, voice, voice-mail, GPRS, CDMA, WAP protocol, internet, text or as a file.

Referring to FIG. 17, the present invention may provide methods and systems of varying transmissions 1702 for a portable electronic facility 300 involving varying information transmissions 1702 to a portable electronic facility 300 and varying information transmissions 1702 from a portable electronic facility 300. The length or frequency of the transmissions 1702 may be varied. The variation may be in response to velocity, direction, location, a point of interest, an object, preferences, a location with respect to a geofence or changes in a geofence. The variation may result in increased battery life for the portable electronic facility 300. The data may be stored and transmitted all at one or it may be transmitted as it is updated. The data may be location information 1100.

In an embodiment the information transmissions may be from multiple sources. The multiple sources may be different networks or different means of communication. The means of communication may be SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. The information may be transmitted in a costless manner, a cost reduced manner or in the form of a DNS lookup.

Referring again to FIG. 17, the present invention may provide methods and systems of increasing the quality of location based information 1100 for a portable electronic facility 300, involving varying information transmissions 1702 to a portable electronic facility 300 and varying information transmissions 1702 from a portable electronic facility 300. The length or frequency of the transmissions 1702 may be varied. The variation may be in response to velocity, direction, location, a point of interest, an object, preferences, a location with respect to a geofence or changes in a geofence. The variation may result in increased battery life for the portable electronic facility 300. The data may be stored and transmitted all at one or it may be transmitted as it is updated. The data may be location information 1100.

In an embodiment the information transmissions may be from multiple sources. The multiple sources may be different networks or different means of communication. The means of communication may be SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. The information may be transmitted in a costless manner, a cost reduced manner or in the form of a DNS lookup.

Referring to FIG. 18, the present invention may provide methods and systems of increasing the quality of location based information 1100 for a portable electronic facility 300 involving obtaining multiple data points for a given item of information or a location 1202. The multiple data points may be analyzed and outliers dropped. The analysis may be performed using an algorithm. The item of information may relate to location, velocity or direction.

Referring to FIG. 19, the present invention may provide methods and systems of defining a geofence 900 on a portable

24

electronic facility 300 involving inputting the geofence 900 using the portable electronic facility 300. The center and a radius of a geofence 900 may be entered on the portable electronic facility 300. The geofence 900 may be defined using a cursor on the display of the portable electronic facility 300. The geofence 900 may be defined using a touch screen on the portable electronic facility 300. The geofence 900 may be defined by the location of the portable electronic facility 300. The geofence 900 may be defined by placing the portable electronic facility 300 at certain points comprising the geofence 900. The geofence 900 may be defined in real time by placing the portable electronic facility 300 at certain points comprising the geofence 900. The geofence 900 may be manipulated using the portable electronic facility 300. The geofence 900 may be moved using the display of the portable electronic facility 300. The geofence 900 may be moved using the portable electronic facility 300. The geofence 900 may be a circle, a sphere, in the shape of any closed polygon, a closed volume, in two dimensions, in three dimensions or may travel with a person.

In certain embodiments the location of the portable electronic facility 300 with respect to the geofence 900 may result in the transmission of information 1702 to the portable electronic facility 300. The information may relate to a coupon, the weather or traffic conditions. In other embodiments the information and geofence 900 may be used for social networking. For example, all or certain of the portable electronic facilities 300 within a geofence 900 may receive information or all or certain of the portable electronic facilities 300 outside a geofence 900 may receive information.

In another embodiment, services may be linked to a geofence 900. For example, all or certain portable electronic facilities 300 located within a geofence 900 may receive or be eligible to receive certain services or all or certain of the portable electronic facilities 300 located outside a geofence 900 may receive or be eligible to receive certain services. The service may be a game, application or coupon. The price for a service may be varied with the location of a portable electronic facility 300 in relation to a geofence 900. For example, a cell phone may be allowed to place calls at no additional cost if located within a certain geofence 900, for example a geofence 900 corresponding to the home of the cell phone owner. In another example a portable electronic facility 300 may be able to receive and transmit information at no additional cost when located within a certain geofence, such as the home area of the portable electronic facility 300.

Referring to FIG. 20, the present invention may provide methods and systems of defining a geofence 900 on a computer screen or similar graphical user interface 2002 involving inputting the geofence 900 through a user interface. The geofence 900 may be defined or moved about the interface using a pointing device such as a mouse or stylus. The radius, shape or dimensions of the geofence 900 may also be defined or changed using a pointing device such as a mouse or stylus. The user interface may be web-based and the geofence 900 may be defined on a server. The geofence 900 may be a circle, a sphere, in the shape of any closed polygon, a closed volume, in two dimensions, in three dimensions or may travel with a person.

Referring to FIG. 21, the present invention may provide methods and systems of sending location-based alerts 2102 involving determining the location 1202 of a portable electronic facility 300 and sending an alert 2102 based on the location 1202 of the portable electronic facility 300. The alert 2102 may be in response to the location of a portable electronic facility 300 with respect to a geofence 900. The alert 2102 may be sent if the portable electronic facility 300 is

25

within or outside a geofence 900 or within or outside a geofence 900 for a certain period of time. The alert 2102 may be sent if a portable electronic facility 300 enters or exits a geofence 900 or enters or exits a geofence 900 for a certain period of time. An alert 2102 may be contingent on the location of other portable electronic facilities 300 or the location of other portable electronic facilities 300 with respect to a geofence 900. The alert 2102 may be affected by the location of other portable electronic facilities 300 or the location of other portable electronic facilities 300 with respect to a geofence 900.

In one embodiment, the geofence 900 may define a place of business. The alert 2102 may be in response to a certain employee or employer arriving or not arriving at work. The alert 2102 may also be in response to a certain employee or employer arriving or not arriving at work by a specified time.

In another embodiment, the geofence 900 may define a home. The alert 2102 may be in response to a certain child, teenager or vehicle arriving or not arriving at home. The alert 2102 may also be in response to a certain child, teenager or vehicle arriving or not arriving at home by a specified time.

In another embodiment, the geofence 900 may define an airport. The alert 2102 may be in response to a passenger arriving or departing. The geofence 900 may also define a city. The alert 2102 may be in response to a passenger or a shipment arriving or departing.

The alert 2102 may be via audio, video, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or may stimulate at least one of the five senses. The alert 2102 may be communicated via one of the following means of communication: SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text.

Referring to FIG. 22, the present invention may provide methods and systems of analyzing information related to at least one portable electronic facility 300 involving transmitting information from the at least one portable electronic facility 300 and analyzing such information using an analysis engine 2202. The information from one or more portable electronic facilities 300 may be stored or aggregated. The analysis engine 2202 may provide the ability to view location history or analyze location history. The analysis engine 2202 may also request additional information or send alerts 2102.

The analysis engine 2202 may perform analytics on location information such as demographic analysis, predictive analysis and descriptive analysis. The analysis may be for retail purposes, marketing purposes or security purposes. The analysis engine 2202 may determine the types of portable electronic facilities 300 or people at a given location. The analysis engine 2202 may determine the class of people at a given location. The class of people may be specified based on the following characteristics: income level, profession, race, ethnicity, gender, sex, sexual orientation, address, age, disposable income level, number of children, education level or health factors. The analysis engine 2202 may determine the route by which a person arrived at a location. The analysis engine 2202 may also determine the routes by which a class of people arrived at a location. The analysis engine 2202 may also determine the locations of a type of portable electronic facility 300. The information provided by the analysis engine 2202 may include purchasing information, personal preferences, demographics or consumer purchasing data relating to individual consumers or classes of consumers.

Access to the analysis engine 2202, the system and information may be granted at different access levels. A user may be granted partial or restricted access via a guest login. It may

26

be that whether a user is permitted to know the location of another user is determined based on the access levels of the users.

Referring to FIG. 23, methods and systems disclosed herein may include methods and systems for verifying a transaction using a portable electronic facility 300. In such embodiments, the location of a portable electronic facility 300 may be linked to a location of a transaction 2302, such as to verify the presence of a user in proximity to the use of the user's credit card, debit card, portable electronic transaction device, or other device. In embodiments the transaction is made using the Internet from a user's home computer, and the tracking information confirms the presence of the user at home by locating the user inside a home geofence 900.

Referring to FIG. 24, methods and systems disclosed herein may include methods and systems for tailoring information to the behavior of a user 2402, such as observing the behavior of a user 2402 and communicating information 2404 to the user by a portable electronic facility 300, such as information 2404 based on the observed behavior of a user 2402. The observed behavior 2402 may include behavior that is tied to locations, such as shopping behavior, purchasing behavior, or the like. In embodiments information may be presented to the user about alternate locations for shopping or purchasing for alternative, similar or complementary goods and services to those being shopped by the user at the tracked location. In embodiments the tracked behavior may indicate personal preferences, may constitute marketing information, or may be observed or inferred behavior based on past actions of the user.

Referring to FIG. 25, methods and systems disclosed herein may include methods and systems for providing information 2404 to a portable electronic facility 300 based on information 2404 received from the portable electronic facility 300, including location information 1100. In embodiments the portable electronic facility 300 may have instant messaging capabilities, and an instant message may embed the location of the user such as a real-world location or an indication of location, such as proximity to a geofence 900, such as designed as "home," "work," or the like.

Referring to FIG. 26, a network of portable electronic facilities 300 may be provided, allowing communication among portable electronic facilities 300, including information based on the tracked locations of the portable electronic facilities 300. In embodiments information is communicated directly among the portable electronic facilities 300, without use of a central server. In embodiments information may be communicated by SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet and/or text. In embodiments the portable electronic facilities 300 may share information that includes or is based upon location information, such as a file, a music file, a movie, a game, an application, a ringtone, a text file, a document, or an email.

FIGS. 27A-C present several examples of the possible graphical user interfaces 2702 that may be presented on a portable electronic facility 300, such as a mobile phone. The interface may display a map or a menu. FIG. 28 depicts a graphical user interface 2802 providing an overview of the locations of all the users in a defined group. The users may be individual drivers in a fleet of delivery trucks. FIG. 29 provides another view 2902 of the locations of the users in FIG. 29. The view may involve the use of tiled maps. FIG. 30 depicts a detailed display 3002 of the location information for one particular user. The "today" and "yesterday" buttons 3004, 3008 may allow for the rapid toggling between data for

27

different dates. FIG. 31 depicts a stop report 3102, as described above, for a particular user.

FIG. 32 depicts the definition of a geofence 900 using a map 3202. FIG. 33 shows several icons 3302 that may be assigned to various geofences 900, such as to distinguish different geofences 900 that are created or used for different purposes. For example, a geofence may be designated with a star to signify its importance, or with an icon representing a house to indicate that it is a geofence 900 for a home. FIG. 34 depicts an address book 3402 that may be provided for a user. FIG. 35 presents a more detailed view of one of the entries 3502 in the address book 3402. FIG. 36 depicts a graphical user interface 3602 that may be used to define alerts using the system. FIG. 37A-37C depict location details as both lists 3702 and maps 3704. FIG. 38A-38C depict several menus 3802 related to storing location-based information 1100, including a menu 3804 for finding saved locations, such as by zip code or other data, a menu 3808 displaying detailed locations, and a menu 3810 for displaying options related to a location, such as an option to see a map, to send directions to the location from a particular location, and an option to send the location information to another user. FIG. 39A-39D depict several graphical user interfaces 3902 related to the presentation of points of interest on a portable electronic facility 300, such as an interface 3904 for finding particular types of location, such as hotels, restaurants, automated teller machines, or gas stations, an interface 3908 for showing details of a particular type of location, an interface 3910 for offering options related to a particular type of location, such as the option to see a map, get directions, or call the location, and an interface 3912 for displaying the results, such as showing a map of the location. FIG. 40 presents a graphical user interface 4002 that may allow a user to send location information, such as via email or voice. FIG. 41 presents a graphical user interface 4102 that may allow a user to input a zip code while traveling. FIGS. 42A-42B present a graphical user interface with a setting menu 4202 that may allow a user to vary the settings of the portable electronic facility 300, such as allowing a user to vary the frequency with which a portable electronic device obtains location information using an interface 4204.

While the invention has been disclosed in connection with certain preferred embodiments, other embodiments will be recognized by those of ordinary skill in the art and are encompassed herein. All documents referenced herein are hereby incorporated by reference.

The invention claimed is:

1. A method comprising:
 - receiving a task on a mobile device;
 - associating, using the mobile device, the task with a physical location;
 - generating, automatically on the mobile device, a geofence around the physical location associated with the task;
 - tracking a current location of the mobile device relative to the geofence; and
 - generating an alert associated with the task when the current location is within the geofence.
2. The method of claim 1, wherein the associating the task with the physical location includes receiving an address representative of the physical location on the mobile device.
3. The method of claim 1, wherein the associating the task with the physical location includes receiving a selection, from a map displayed on the mobile device, of a point representative of the physical location.
4. The method of claim 1, wherein the generating the geofence includes generating a circle with a pre-defined radius around the physical location.

28

5. The method of claim 1, wherein the generating the alert includes sending a message from the mobile device.

6. The method of claim 1, wherein the tracking the current location includes periodically transmitting, from the mobile device, data representative of the current location of the mobile device to a service provider.

7. The method of claim 6, wherein the generating the alert includes sending, from the service provider, a message to the mobile device.

8. The method of claim 6, wherein the generating the alert includes sending, from the service provider, a message to a second mobile device.

9. A non-transitory machine-readable storage medium including instructions that, when executed on a machine, cause the machine to:

- receive data defining a task;
- associate the task with a physical location;
- generate, automatically, a geofence around the physical location associated with the task;
- track a current location of a mobile device relative to the geofence; and
- generate an alert associated with the task when the current location is within the geofence.

10. The machine-readable storage medium of claim 9, wherein the associating the task with the physical location includes receiving an address representative of the physical location on the mobile device.

11. The machine-readable storage medium of claim 9, wherein the associating the task with the physical location includes receiving a selection, from a map displayed on the mobile device, of a point representative of the physical location.

12. The machine-readable storage medium of claim 9, wherein the generating the geofence includes generating a circle with a pre-defined radius around the physical location.

13. The machine-readable storage medium of claim 9, wherein the generating the alert includes sending a message from the mobile device.

14. The machine-readable storage medium of claim 9, wherein the tracking the current location includes periodically transmitting, from the mobile device, data representative of the current location of the mobile device to a service provider.

15. The machine-readable storage medium of claim 14, wherein the generating the alert includes sending, from the service provider, a message to the mobile device.

16. The machine-readable storage medium of claim 14, wherein the generating the alert includes sending, from the service provider, a message to a second mobile device.

17. A mobile device comprising:

- an input facility to receive a task;
- a geolocation facility to track a current location associated with the mobile device; and a central processing unit to:
 - associate the task with a physical location;
 - generate, automatically, a geofence around the physical location associated with the task;
 - generate an alert associated with the task when the current location is within the geofence.

18. The mobile device of claim 17, wherein the input facility is also to receive an address representative of the physical location associated with the task.

19. The mobile device of claim 17, wherein the input facility is also to:

- display a map on the mobile device; and
- receive a selection from the displayed map of a point representative of the physical location associated with the task.

20. The mobile device of claim 17, wherein the mobile device further includes a data communication facility; wherein the geolocation facility communicates the current location to the data communication facility; and wherein the data communication facility periodically transmits the current location to a service provider.

* * * * *