

US009654923B2

# (12) United States Patent

## Phillips et al.

#### (54) LOCATION-BASED SERVICES

- (71) Applicant: PayPal, Inc., San Jose, CA (US)
- Inventors: Alan Phillips, Hopkinton, MA (US);
  Frank Schroth, Milton, MA (US);
  Geoffrey M. Palmer, Newton, MA (US); Stefan G. Zielinski, Watertown, MA (US); Allen P. Smith, Milton, MA (US); Colin M. Cunningham, III, Cambridge, MA (US)
- (73) Assignee: PayPal, Inc., San Jose, CA (US)
- (\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: 14/534,797
- (22) Filed: Nov. 6, 2014

#### (65) **Prior Publication Data**

US 2015/0065177 A1 Mar. 5, 2015

#### **Related U.S. Application Data**

- (63) Continuation of application No. 13/361,113, filed on Jan. 30, 2012, now Pat. No. 8,909,248, which is a continuation of application No. 11/140,273, filed on May 27, 2005, now Pat. No. 7,848,765.
- (51) Int. Cl.

H04W 24/00	(2009.01)
H04W 4/02	(2009.01)
G08B 21/02	(2006.01)
H04W 4/12	(2009.01)
H04W 4/14	(2009.01)
H04W 8/10	(2009.01)
H04W 8/14	(2009.01)
H04W 92/08	(2009.01)

### (10) Patent No.: US 9,654,923 B2

### (45) **Date of Patent:** May 16, 2017

- (52) **U.S. Cl.** 
  - CPC ....... H04W 4/021 (2013.01); G08B 21/0236 (2013.01); G08B 21/0261 (2013.01); G08B 21/0269 (2013.01); G08B 21/0272 (2013.01); H04W 4/12 (2013.01); H04W 4/14 (2013.01); H04W 8/10 (2013.01); H04W 8/14 (2013.01); H04W 92/08 (2013.01)
- (58) **Field of Classification Search** CPC .... H04W 4/02; H04W 64/00; H04L 29/08657 USPC ...... 455/456.3, 414.1, 414.2, 404.2 See application file for complete search history.

#### (56) **References Cited**

#### U.S. PATENT DOCUMENTS

5,559,707 A	9/1996 Delorme et al.	
5,649,114 A	7/1997 Deaton et al.	
5,724,521 A	3/1998 Dedrick	
	(Continued)	

#### OTHER PUBLICATIONS

"U.S. Appl. No. 12/268,693, Response filed Jul. 6, 2015 to Final Office Action mailed Apr. 15, 2015", 11 pgs. (Continued)


Primary Examiner — Nghi H Ly

(74) Attorney, Agent, or Firm -- Maschoff Brennan

#### (57) **ABSTRACT**

Provided herein are methods and systems relating to location-based services such as providing a geofencing, outputting location-based information on a mobile device, varying transmissions to and from a mobile device, and providing location-based alerts. More specifically, a method can include receiving data defining a geofence, monitoring a current location, comparing the current location with the geofence, determining that the current location is within the geofence, and in response altering the state of an application on the mobile device.

#### 20 Claims, 28 Drawing Sheets



#### (56) **References** Cited

### U.S. PATENT DOCUMENTS

5,724,660 A	3/1998	Kauser et al.
5,732,354 A	3/1998	Macdonald
5,848,373 A	12/1998	DeLorme et al.
5,890,068 A	3/1999	Fattouche et al.
5,905,246 A	5/1999	Fajkowski Duggali at el
5,938,721 A 5,946,687 A	8/1999 8/1999	Dussell et al. Gehani et al.
5,948,040 A	9/1999	DeLorme et al.
6,014,090 A	1/2000	Rosen et al.
6,069,570 A	5/2000	Herring et al.
6,091,956 A	7/2000	Hollenberg
6,097,958 A	8/2000	Bergen
6,122,520 A	9/2000	Want et al.
6,154,172 A	11/2000	Piccionelli et al.
6,157,841 A 6,167,274 A	12/2000 12/2000	Bolduc et al.
6,198,927 B1	3/2001	Smith Wright et al.
6,204,812 B1	3/2001	Fattouche
6,208,297 B1	3/2001	Fattouche et al.
6,208,857 B1	3/2001	Agre et al.
6,243,588 B1	6/2001	Koorapaty et al.
6,246,861 B1	6/2001	Messier et al.
6,246,882 B1	6/2001	Lachance
6,259,381 B1	7/2001	Small
6,259,923 B1	7/2001	Lim et al.
6,266,014 B1 6,269,361 B1	7/2001 7/2001	Fattouche et al. Davis et al.
6,314,365 B1	11/2001	Smith
6,317,684 B1	11/2001	Roeseler et al.
6,321,158 B1	11/2001	Delorme et al.
6,330,452 B1	12/2001	Fattouche et al.
6,341,255 B1	1/2002	Lapidot
6,347,230 B2	2/2002	Koshima et al.
6,356,543 B2	3/2002	Hall et al.
6,357,042 B2	3/2002 4/2002	Srinivasan et al. Schmier et al.
6,374,176 B1 6,374,177 B1	4/2002	Lee et al.
6,404,388 B1	6/2002	Sollenberger et al.
6,424,840 B1	7/2002	Fitch et al.
6,442,529 B1	8/2002	Krishan et al.
6,456,852 B2	9/2002	Bar et al.
6,477,363 B1	11/2002	Ayoub et al.
6,496,857 B1	12/2002	Dustin et al.
6,519,463 B2	2/2003	Tendler For at al
6,529,159 B1 6,552,682 B1	3/2003 4/2003	Fan et al. Fan
6,563,459 B2	5/2003	Takenaga
6,577,946 B2	6/2003	Myr
6,580,914 B1	6/2003	Smith
6,590,529 B2	7/2003	Schwoegler
6,590,533 B2	7/2003	Sollenberger et al.
6,618,593 B1	9/2003	Drutman et al.
6,625,457 B1*	9/2003	Raith H04M 1/72572
6 664 022 D1	12/2002	340/991 Fan
6,664,922 B1 6,690,322 B2	12/2003 2/2004	Fan Shamoto et al.
6,714,797 B1	3/2004	Rautila
6,718,551 B1	4/2004	Swix et al.
6,732,080 B1*	5/2004	Blants G06Q 10/109
		705/7.18
6,732,120 B1	5/2004	Du
6,741,188 B1	5/2004	Miller et al.
6,757,544 B2	6/2004 10/2004	Rangarajan et al.
6,807,479 B2 6,819,919 B1	11/2004	Watanabe et al. Tanaka
7,082,365 B2	7/2004	Sheha et al.
7,092,702 B2	8/2006	Cronin et al.
7,119,828 B1	10/2006	Kizhnerman et al.
7,130,622 B2	10/2006	Vänskä et al.
7,138,913 B2	11/2006	Mackenzie et al.
7,142,858 B2	11/2006	Aoki et al.
7,164,986 B2	1/2007	Humphries et al.
7,196,639 B2 7,197,719 B2	3/2007 3/2007	Joyce et al. Doyle et al.
7,199,815 B2	4/2007	Aoyama
,,199,019 DZ	1/2007	2 so julia

7,203,502 B2	4/2007	Wilson et al.
7,203,598 B1	4/2007	Whitsell
7,213,214 B2	5/2007	Baar et al
7,216,109 B1	5/2007	Donner
7,228,287 B1	6/2007	Samson et al.
7,233,913 B2	6/2007	Scroggie et al.
7,246,109 B1	7/2007	Ramaswamy
7,254,388 B2	8/2007	Nam et al.
7,273,172 B2	9/2007	Olsen, III et al.
7,385,499 B2	6/2008	Horton et al.
7,389,919 B2	6/2008	Walker et al.
7,502,133 B2	3/2008	Fukunaga et al.
7,532,899 B2	5/2009	
		Wilson et al.
7,593,871 B1	9/2009	Mesaros
7,657,436 B2	2/2010	Elmore et al.
7,668,931 B2	2/2010	Parupudi et al.
7,669,759 B1	3/2010	Zettner
7,706,740 B2	4/2010	Collins et al.
7,715,981 B2	5/2010	Bradley et al.
7,720,436 B2	5/2010	Hamynen et al.
7,720,844 B2	5/2010	Chu et al.
7,747,259 B2	6/2010	Pande et al.
7,751,971 B2	7/2010	Chang et al.
7,848,765 B2	12/2010	Phillips et al.
7,909,326 B2	3/2011	Walker et al.
8,041,604 B1	10/2011	Glaser
8,099,109 B2	1/2012	Altman et al.
8.249.884 B2	8/2012	Turner et al.
8.326.315 B2	12/2012	Phillips et al.
8,355,948 B2	1/2013	Mason
8,371,502 B1	2/2013	Galit et al.
8,463,295 B1	6/2013	Caralis et al.
8,549,028 B1	10/2013	Alon et al.
8,566,197 B2	10/2013	Satyavolu et al.
8,732,019 B2	5/2014	Brown et al.
8,862,150 B2	10/2014	Phillips et al.
8,909,248 B2	12/2014	Phillips et al.
2001/0055976 A1	12/2001	Couch et al.
2002/0046259 A1	4/2002	Glorikian
2002/0065689 A1	5/2002	Bingham et al.
2002/0078444 A1	6/2002	Krewin et al.
2002/0082941 A1	6/2002	Bird
2002/0111154 A1	8/2002	Eldering et al.
2002/0115453 A1	8/2002	Poulin et al.
2002/0143930 A1	10/2002	Babu et al.
2002/0145984 A1	10/2002	Babu et al.
2002/0155844 A1	10/2002	Rankin et al.
2002/0160766 A1	10/2002	Portman et al.
2002/0198003 A1	12/2002	Klapman
2003/0004802 A1	1/2003	Callegari
2003/0007006 A1	1/2003	Baar et al.
2003/0037041 A1	2/2003	Hertz
2003/0040324 A1	2/2003	Eldering et al.
2003/0125043 A1	7/2003	Silvester et al.
2003/0126150 A1	7/2003	Chan et al.
2003/0120130 A1 2003/0130787 A1	7/2003	Clapper
2003/0130130 A1	7/2003	Steelberg et al.
2003/0139190 A1*	11/2003	Mault G06F 19/3475
2005/0208409 AT	11/2003	
2002/0216060 +1	11/2002	705/15
2003/0216960 A1	11/2003	Postrel
2003/0220835 A1	11/2003	Barnes, Jr.
2004/0002359 A1	1/2004	Deas et al.
2004/0021567 A1	2/2004	Dunn
2004/0023666 A1	2/2004	Moon et al.
2004/0030598 A1	2/2004	Boal
2004/0039579 A1	2/2004	Chithambaram et al.
2004/0043773 A1		
2001/0111222	3/2004	Lee et al.
2004/0111332 A1	3/2004 6/2004	Lee et al. Baar et al.
2004/0111332 A1 2004/0139330 A1		
	6/2004	Baar et al.
2004/0139330 A1 2004/0142750 A1	6/2004 7/2004 7/2004	Baar et al. Baar Glisson et al.
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1	6/2004 7/2004 7/2004 9/2004	Baar et al. Baar Glisson et al. Wilson et al.
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1	6/2004 7/2004 7/2004 9/2004 9/2004	Baar et al. Baar Glisson et al. Wilson et al. Reilly
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1	6/2004 7/2004 7/2004 9/2004 9/2004 10/2004	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al.
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1 2004/0203931 A1	6/2004 7/2004 9/2004 9/2004 10/2004 10/2004	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al. Karaoguz
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1 2004/0203901 A1 2005/0044032 A1	6/2004 7/2004 7/2004 9/2004 9/2004 10/2004 10/2004 2/2005	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al. Karaoguz Lee et al.
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1 2004/0203931 A1 2005/0044032 A1 2005/0064852 A1	6/2004 7/2004 9/2004 9/2004 10/2004 10/2004 2/2005 3/2005	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al. Karaoguz Lee et al. Baldursson
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1 2004/0203931 A1 2005/0044032 A1 2005/0064852 A1 2005/0065916 A1	6/2004 7/2004 7/2004 9/2004 9/2004 10/2004 10/2004 2/2005 3/2005 3/2005	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al. Karaoguz Lee et al. Baldursson Ge et al.
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1 2004/0203931 A1 2005/0044032 A1 2005/0064852 A1	6/2004 7/2004 9/2004 9/2004 10/2004 10/2004 2/2005 3/2005	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al. Karaoguz Lee et al. Baldursson Ge et al. Humphries
2004/0139330 A1 2004/0142750 A1 2004/0192339 A1 2004/0192349 A1 2004/0203901 A1 2004/0203931 A1 2005/0044032 A1 2005/0064852 A1 2005/0065916 A1	6/2004 7/2004 7/2004 9/2004 9/2004 10/2004 10/2004 2/2005 3/2005 3/2005	Baar et al. Baar Glisson et al. Wilson et al. Reilly Wilson et al. Karaoguz Lee et al. Baldursson Ge et al.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

2005/0250516 A1	11/2005	Shim
2005/0278749 A1	12/2005	Ewert et al.
2006/0047825 A1	3/2006	Steenstra et al.
2006/0064346 A1	3/2006	Steenstra et al.
2006/0089792 A1	4/2006	Manber et al.
2006/0089792 A1 2006/0098028 A1	5/2006	Baar
2006/0099959 A1	5/2006	Staton et al.
2006/0145837 A1*	7/2006	Horton G06Q 10/08
		340/539.13
2006/0148488 A1	7/2006	Syrbe
2006/0211453 A1*	9/2006	Schick H04M 1/274566
		455/564
2006/0218114 A1	9/2006	Weare et al.
2006/0224583 A1	10/2006	Fikes et al.
2006/0236257 A1	10/2006	Othmer et al.
2006/0230237 A1 2006/0270421 A1	11/2006	Phillips et al.
2006/0270421 A1 2006/0271281 A1	11/2006	Ahn et al.
		Mazzella et al.
2006/0271501 A1	11/2006	
2006/0277564 A1	12/2006	Jarman
2007/0015517 A1	1/2007	Casey
2007/0024469 A1	2/2007	Chou
2007/0083437 A1	4/2007	Hamor
2007/0100802 A1	5/2007	Celik
2007/0118430 A1	5/2007	Wiseman et al.
2007/0124229 A1	5/2007	Ku et al.
2007/0165050 A1	7/2007	Baar
2007/0202844 A1	8/2007	Wilson et al.
2007/0244633 A1	10/2007	Phillips et al.
2008/0035725 A1	2/2008	Jambunathan et al.
2008/0040216 A1	2/2008	Dellovo
2008/0046415 A1	2/2008	Henkin et al.
2008/0070588 A1	3/2008	Morin
2008/0102947 A1	5/2008	Hays et al.
2008/0102547 A1 2008/0104542 A1	5/2008	Cohen et al.
2008/0126251 A1	5/2008	Wassingbo
2008/0126515 A1	5/2008	Chambers et al.
2008/0177749 A1	7/2008	Overton
2008/0248815 A1	10/2008	Busch
2008/0251580 A1	10/2008	Van De Velde et al.
2008/0290987 A1	11/2008	Li
2008/0313078 A1	12/2008	Payne
2009/0005077 A1	1/2009	Forstall et al.
2009/0024476 A1	1/2009	Baar et al.
2009/0033633 A1	2/2009	Newman et al.
2009/0037101 A1	2/2009	Koike et al.
2009/0061884 A1	3/2009	Rajan et al.
2009/0063229 A1	3/2009	Coladonato et al.
2009/0076911 A1	3/2009	Vo et al.
2009/0076925 A1	3/2009	Dewitt et al.
2009/0100037 A1	4/2009	Scheibe
2009/0132961 A1	5/2009	Baar
2009/0156182 A1	6/2009	Jenkins et al.
2009/0156234 A1	6/2009	Sako et al.
2009/0204672 A1	8/2009	Jetha et al.
2009/0239552 A1	9/2009	Churchill et al.
2009/02555552 AI	11/2009	Otto et al.
2009/02/0306886 A1	12/2009	Mueller
2009/0300880 A1 2010/0114683 A1	5/2010	Wessels et al.
2011/0047075 A1	2/2011	Fourez
2011/0106605 A1	5/2011	Malik et al.
2011/0212717 A1	9/2011	Rhoads et al.
2012/0036015 A1	2/2012	Sheikh
2012/0126974 A1	5/2012	Phillips et al.
2012/0129553 A1	5/2012	Phillips et al.
2012/0239483 A1	9/2012	Yankovich et al.
2012/0239501 A1	9/2012	Yankovich et al.
2013/0080239 A1	3/2013	Okerlund
2013/0110624 A1	5/2013	Mitrovic
2013/0150086 A1	6/2013	Caralis et al.
2013/0173377 A1	7/2013	Keller et al.
2013/0346233 A1	12/2013	Caralis et al.
2015/0006291 A1	1/2015	Yankovich et al.
2015/0032531 A1	1/2015	Yankovich et al.
2015/0148078 A1		
_010/01/10//0 /11	5/2015	Phillips et al.
2015/0163632 11	5/2015	Phillips et al. Phillips et al
2015/0163632 A1	5/2015 6/2015	Phillips et al. Phillips et al.

#### OTHER PUBLICATIONS

"U.S. Appl. No. 12/369,068, Response filed Oct. 12, 2015 to Final Office Action mailed Jul. 16, 2015", 12 pgs.

"U.S. Appl. No. 12/369,068, Final Office Action mailed Jul. 16, 2015", 18 pgs.

"U.S. Appl. No. 12/369,068, Non Final Office Action mailed Dec. 4, 2015", 15 pgs.

"U.S. Appl. No. 13/282,199, Non Final Office Action mailed Sep. 18, 2015", 26 pgs.

"U.S. Appl. No. 13/339,235, Non Final Office Action mailed Sep. 18, 2015", 14 pgs.

"U.S. Appl. No. 13/340,970, Non Final Office Action mailed Sep. 16, 2015", 25 pgs.

"U.S. Appl. No. 13/913,768, Notice of Allowance mailed Sep. 28, 2015", 17 pgs.

"U.S. Appl. No. 13/913,768, Supplemental Preliminary Amendment filed Sep. 16, 2015", 7 pgs.

"U.S. Appl. No. 14/486,518, Final Office Action mailed Dec. 8, 2015", 7 pgs.

"U.S. Appl. No. 14/486,518, Response filed Aug. 21, 2015 to Non Final Office Action mailed May 21, 2015", 17 pgs.

"U.S. Appl. No. 14/512,350, Final Office Action mailed Nov. 30, 2015", 7 pgs.

"U.S. Appl. No. 14/512,350, Response filed Aug. 24, 2015 to Non Final Office Actio mailed May 22, 2015", 20 pgs.

"U.S. Appl. No. 11/593,047, Response filed Feb. 19, 2015 to Final Office Action mailed Aug. 19, 2014", 12 pgs.

"U.S. Appl. No. 12/175,512, Examiner Interview Summary mailed Dec. 11, 2014", 3 pgs.

"U.S. Appl. No. 12/175,512, Final Office Action mailed Jan. 22, 2015", 20 pgs.

"U.S. Appl. No. 12/175,512, Response filed May 22, 2015 to Final Office Action mailed Jan. 22, 2015", 23 pgs.

"U.S. Appl. No. 12/175,512, Response filed Dec. 12, 2014 to Non Final Office Action mailed Sep. 12, 2014", 15 pgs.

"U.S. Appl. No. 12/268,693, Examiner Interview Summary mailed Jan. 12, 2015", 3 pgs.

"U.S. Appl. No. 12/268,693, Final Office Action mailed Apr. 6, 2015", 32 pgs.

"U.S. Appl. No. 12/268,693, Response filed Mar. 25, 2015 to Non Final Office Action mailed Nov. 25, 2014", 14 pgs.

"U.S. Appl. No. 12/369,068, Examiner Interview Summary mailed Jan. 9, 2015", 5 pgs.

"U.S. Appl. No. 12/369,068, Response filed Apr. 20, 2015 to Non Final Office Action mailed Nov. 21, 2014", 14 pgs.

"U.S. Appl. No. 13/282,199, Examiner Interview Summary mailed Mar. 12, 2015", 3 pgs.

"U.S. Appl. No. 13/282,199, Final Office Action mailed Jan. 16, 2015", 27 pgs.

"U.S. Appl. No. 13/282,199, Response filed May 18, 2015 to Final Office Action mailed Jan. 16, 2015", 30 pgs.

"U.S. Appl. No. 13/339,235, Non Final Office Action mailed Feb. 12, 2015", 4 pgs.

"U.S. Appl. No. 13/339,235, Response filed Feb. 2, 2015 to Final Office Action mailed Dec. 2, 2014", 12 pgs.

"U.S. Appl. No. 13/339,235, Response filed May 12, 2015 to Non Final Office Action mailed Feb. 12, 2015", 33 pgs.

"U.S. Appl. No. 13/340,970, Final Office Action mailed Feb. 24, 2015", 19 pgs.

"U.S. Appl. No. 13/340,970, Response filed Jun. 24, 2015 to Final Office Action mailed Feb. 24, 2015", 22 pgs.

"U.S. Appl. No. 14/486,518, Non Final Office Action mailed May 21, 2015", 9 pgs.

"U.S. Appl. No. 14/512,350, Non Final Office Action mailed May 22, 2015", 10 pgs.

"U.S. Appl. No. 14/611,210, Preliminary Amendment filed Feb. 4, 2015", 8 pgs.

"U.S. Appl. No. 14/624,083, Preliminary Amendment filed Mar. 6, 2015", 9 pgs.

"U.S. Appl. No. 11/140,273, Final Office Action mailed Jul. 15, 2009", 11 pgs.

#### (56) **References Cited**

#### OTHER PUBLICATIONS

"U.S. Appl. No. 11/140,273, Final Office Action mailed Dec. 13, 2007", 11 pgs.

"U.S. Appl. No. 11/140,273, Non Final Office Action mailed Feb. 26, 2010", 11 pgs.

"U.S. Appl. No. 11/140,273, Non Final Office Action mailed May 31, 2007", 10 pgs.

"U.S. Appl. No. 11/140,273, Non Final Office Action mailed Jul. 3, 2008", 11 pgs.

"U.S. Appl. No. 11/140,273, Notice of Allowance mailed Aug. 3, 2010", 6 pgs.

"U.S. Appl. No. 11/140,273, Preliminary Amendment mailed Aug. 30, 2005", 32 pgs.

"U.S. Appl. No. 11/140,273, Response filed Mar. 20, 2007 to Restriction Requirement mailed Feb. 21, 2007", 10 pgs.

"U.S. Appl. No. 11/140,273, Response filed Apr. 14, 2008 to Final Office Action mailed Dec. 13, 2007", 13 pgs.

"U.S. Appl. No. 11/140,273, Response filed Apr. 21, 2009 to Restriction Requirement mailed Jan. 21, 2009", 10 pgs.

"U.S. Appl. No. 11/140,273, Response filed May 26, 2010 to Non Final Office Action mailed Feb. 26, 2010", 13 pgs.

"U.S. Appl. No. 11/140,273, Response filed May 27, 2007 to Final Office Action mailed Dec. 13, 2007", 18 pgs.

"U.S. Appl. No. 11/140,273, Response filed Oct. 7, 2008 to Non Final Office Action mailed Jul. 3, 2008", 17 pgs.

"U.S. Appl. No. 11/140,273, Response filed Nov. 16, 2009 to Non Final Office Action mailed Jul. 15, 2009", 19 pgs.

"U.S. Appl. No. 11/140,273, Response filed Nov. 27, 2007 to Non Final Office Action mailed May 31, 2007", 12 pgs.

"U.S. Appl. No. 11/140,273, Restriction Requirement mailed Jan. 21, 2009", 6 pgs.

"U.S. Appl. No. 11/140,273, Restriction Requirement mailed Feb. 21, 2007", 5 pgs.

"U.S. Appl. No. 11/593,047, Supplemental Amendment filed Mar. 18, 2010", 12 pgs.

"U.S. Appl. No. 11/593,047, Advisory Action mailed Jan. 29, 2010", 4 pgs.

"U.S. Appl. No. 11/593,047, Applicant, Summary of Examiner Interview filed Mar. 15, 2010", 2 pgs.

"U.S. Appl. No. 11/593,047, Examiner Interview Summary mailed Mar. 12, 2010", 4 pgs.

"U.S. Appl. No. 11/593,047, Examiner Interview Summary mailed Jul. 24, 2014", 2 pgs.

"U.S. Appl. No. 11/593,047, Final Office Action mailed Dec. 1, 2009", 19 pgs.

"U.S. Appl. No. 11/593,047, Non Final Office Action mailed Feb. 2, 2009", 18 pgs.

"U.S. Appl. No. 11/593,047, Non Final Office Action mailed Mar. 11, 2014", 18 pgs.

"U.S. Appl. No. 11/593,047, Non Final Office Action mailed Sep. 4, 2009", 13 pgs.

"U.S. Appl. No. 11/593,047, Response filed Jan. 22, 2010 to Final Office Action mailed Dec. 1, 2009", 23 pgs.

"U.S. Appl. No. 11/593,047, Response filed Apr. 20, 2009 to Non Final Office Action mailed Feb. 2, 2009", 33 pgs.

"U.S. Appl. No. 11/593,047, Response filed Jul. 28, 2014 to Non Final Office Action mailed Mar. 11, 2014", 10 pgs.

"U.S. Appl. No. 11/593,047, Response filed Nov. 16, 2009 to Non Final Office Action mailed Sep. 4, 2009", 20 pgs.

"U.S. Appl. No. 11/690,720, Examiner Interview Summary mailed Feb. 22, 2012", 3 pgs.

"U.S. Appl. No. 11/690,720, Final Office Action mailed Apr. 27, 2010", 10 pgs.

"U.S. Appl. No. 11/690,720, Final Office Action mailed Nov. 9, 2011", 17 pgs.

"U.S. Appl. No. 11/690,720, Non Final Office Action mailed Sep. 25, 2009", 20 pgs.

"U.S. Appl. No. 11/690,720, Non-Final Office Action May 17, 2011", 11 pgs.

"U.S. Appl. No. 11/690,720, Notice of Allowance mailed May 15, 2012", 7 pgs.

"U.S. Appl. No. 11/690,720, Notice of Allowance mailed Aug. 2, 2012", 7 pgs.

"U.S. Appl. No. 11/690,720, Preliminary Amendment filed Mar. 23, 2007", 8 pgs.

"U.S. Appl. No. 11/690,720, Response filed Jan. 28, 2010 to Non Final Office Action mailed Sep. 25, 2010", 11 pgs.

"U.S. Appl. No. 11/690,720, Response filed Feb. 15, 2012 to Final Office Action mailed Nov. 9, 2011", 14 pgs.

"U.S. Appl. No. 11/690,720, Response filed Aug. 17, 2011 to Non Final Office Action mailed May 17, 2011", 13 pgs.

"U.S. Appl. No. 11/690,720, Response filed Aug. 25, 2010 to Final Office Action mailed Apr. 27, 2010", 11 pgs.

"U.S. Appl. No. 12/175,512, Final Office Action mailed Dec. 7, 2011", 13 pgs.

"U.S. Appl. No. 12/175,512, Non Final Office Action mailed Jul. 26, 2011", 12 pgs.

"U.S. Appl. No. 12/175,512, Response filed Mar. 7, 2012 to Final Office Action mailed Dec. 7, 2011", 10 pgs.

"U.S. Appl. No. 12/175,512, Response filed Nov. 28, 2011 to Non-Final Office Action mailed Aug. 1, 2011", 12 pgs.

"U.S. Appl. No. 12/268,693, Final Office Action mailed Dec. 2, 2011", 20 pgs.

"U.S. Appl. No. 12/268,693, Non Final Office Action mailed Aug. 8, 2011", 16 pgs.

"U.S. Appl. No. 12/268,693, Non Final Office Action mailed Nov. 25, 2014", 24 pgs.

"U.S. Appl. No. 12/268,693, Response filed Jun. 1, 2012 to Final Office Action mailed Dec. 2, 2011", 11 pgs.

"U.S. Appl. No. 12/268,693, Response filed Nov. 8, 2011 to Restriction Requirement mailed Aug. 8, 2011", 11 pgs.

"U.S. Appl. No. 12/268,693, Response filed Nov. 8, 2011 to Non Final Office Action mailed Aug. 8, 2011", 11 pgs.

"U.S. Appl. No. 12/369,068, Response filed Nov. 21, 2011 to Final Office Action mailed Aug. 19, 2011", 12 pgs.

"U.S. Appl. No. 12/369,068, Final Office Action mailed Aug. 19, 2011", 17 pgs.

"U.S. Appl. No. 12/369,068, Non Final Office Action mailed Oct. 8, 2013", 19 pgs.

"U.S. Appl. No. 12/369,068, Non Final Office Action mailed Nov. 21, 2014", 16 pgs.

"U.S. Appl. No. 12/369,068, Non Final Office Action mailed Dec. 8, 2010", 19 pgs.

"U.S. Appl. No. 12/369,068, Response filed Feb. 10, 2014 to Non Final Office Action mailed Oct. 8, 2013", 14 pgs.

"U.S. Appl. No. 12/369,068, Response filed Jun. 8, 2011 to Non Final Office Action mailed Dec. 8, 2010", 19 pgs.

"U.S. Appl. No. 13/050,769, Final Office Action mailed Jun. 17, 2013", 10 pgs.

"U.S. Appl. No. 13/050,769, Non Final Office Action mailed Jan. 11, 2013", 10 pgs.

"U.S. Appl. No. 13/050,769, Notice of Allowance mailed Jun. 16, 2014", 8 pgs.

"U.S. Appl. No. 13/050,769, Response filed Apr. 9, 2013 to Non Final Office Action mailed Jan. 11, 2013", 15 pgs.

"U.S. Appl. No. 13/050,769, Response filed Sep. 5, 2013 to Final Office Action Mailed Jun. 17, 2013", 14 pgs.

"U.S. Appl. No. 13/282,199, Examiner Interview Summary mailed Jul. 22, 2014", 3 pgs.

"U.S. Appl. No. 13/282,199, Final Office Action mailed Sep. 26, 2013", 25 pgs.

"U.S. Appl. No. 13/282,199, Non Final Office Action mailed Apr. 9, 2014", 28 pgs.

"U.S. Appl. No. 13/282,199, Non Final Office Action mailed Apr. 29, 2013", 20 pgs.

"U.S. Appl. No. 13/282,199, Response filed Jan. 27, 2014 to Non-Final Office Action mailed Sep. 26, 2013", 14 pgs.

"U.S. Appl. No. 13/282,199, Response filed Apr. 4, 2013 to Restriction Requirement mailed Mar. 7, 2013", 10 pgs.

"U.S. Appl. No. 13/282,199, Response filed Jul. 17, 2014 to Non Final Office Action mailed Apr. 9, 2014", 16 pgs.

#### (56) **References Cited**

#### OTHER PUBLICATIONS

"U.S. Appl. No. 13/282,199, Response filed Aug. 28, 2013 to Non Final Office Action mailed Apr. 29, 2013", 16 pgs.

"U.S. Appl. No. 13/282,199, Restriction Requirement mailed Mar. 7, 2013", 8 pgs.

"U.S. Appl. No. 13/313,681, Non Final Office Action mailed Aug. 21, 2012", 23 pgs.

"U.S. Appl. No. 13/313,681, Notice of Allowance mailed Feb. 7, 2013", 13 pgs.

"U.S. Appl. No. 13/313,681, Response filed Jan. 21, 2013 to Non Final Office Action mailed Aug. 21, 2012", 10 pgs.

"U.S. Appl. No. 13/339,235, Final Office Action mailed Aug. 29, 2012", 11 pgs.

"U.S. Appl. No. 13/339,235, Final Office Action mailed Dec. 2, 2014", 7 pgs.

"U.S. Appl. No. 13/339,235, Non Final Office Action mailed Mar. 16, 2012", 10 pgs.

"U.S. Appl. No. 13/339,235, Notice of Allowance mailed Apr. 25, 2014", 8 pgs.

"U.S. Appl. No. 13/339,235, Response filed Jun. 15, 2012 to Non Final Office Action mailed Mar. 16, 2012", 11 pgs.

"U.S. Appl. No. 13/339,235, Response filed Nov. 29, 2012 to Final Office Action mailed Aug. 29, 2012", 11 pgs.

"U.S. Appl. No. 13/340,970, Advisory Action mailed Feb. 13, 2014", 3 pgs.

"U.S. Appl. No. 13/340,970, Final Office Action mailed Sep. 26, 2013", 18 pgs.

"U.S. Appl. No. 13/340,970, Non Final Office Action mailed Apr. 12, 2013", 17 pgs.

"U.S. Appl. No. 13/340,970, Response filed Feb. 25, 2014 to Advisory Action mailed Feb. 13, 2014", 10 pgs.

"U.S. Appl. No. 13/340,970, Response filed Jul. 12, 2013 to Non Final Office Action mailed Apr. 12, 2013", 10 pgs.

"U.S. Appl. No. 13/340,970, Response filed Dec. 1, 2014 to Non Final Office Action mailed Aug. 29, 2014", 14 pgs.

"U.S. Appl. No. 13/340,970; Response filed Jan. 27, 2014 to Final Office Action mailed Sep. 26, 2013", 10 pgs.

"U.S. Appl. No. 13/361,113, 312 Amendment filed Oct. 29, 2014", 6 pgs.

"U.S. Appl. No. 13/361,113, Non Final Office Action mailed Feb. 13, 2014", 13 pgs.

"U.S. Appl. No. 13/361,113, Notice of Allowance mailed Aug. 1, 2014", 8 pgs.

"U.S. Appl. No. 13/361,113, PTO Response to Rule 312 Communication mailed Nov. 6, 2014", 2 pgs.

"U.S. Appl. No. 13/361,113, Response filed May 13, 2014 to Non Final Office Action mailed Feb. 13, 2014", 13 pgs.

"U.S. Appl. No. 13/361,113, Supplemental Notice of Allowability mailed Sep. 17, 2014", 2 pgs.

"U.S. Appl. No. 13/361,196, Examiner Interview Summary mailed Apr. 22, 2013", 3 pgs.

"U.S. Appl. No. 13/361,196, Final Office Action mailed Jan. 22, 2013", 15 pgs.

"U.S. Appl. No. 13/361,196, Non Final Office Action mailed Jan. 3, 2014", 11 pgs.

"U.S. Appl. No. 13/361,196, Non Final Office Action mailed Mar. 29, 2012", 12 pgs.

"U.S. Appl. No. 13/361,196, Non Final Office Action mailed Aug. 23, 2012", 13 pgs.

"U.S. Appl. No. 13/361,196, Notice of Allowance mailed Jun. 10, 2014", 8 pgs.

"U.S. Appl. No. 13/361,196, Response filed Apr. 2, 2014 to Non Final Office Action mailed Jan. 3, 2014", 7 pgs.

"U.S. Appl. No. 13/361,196, Response filed Apr. 18, 2013 to Final Office Action mailed Jan. 22, 2013", 10 pgs.

"U.S. Appl. No. 13/361,196, Response filed Jun. 21, 2012 to Non Final Office Action mailed Mar. 29, 2012", 9 pgs.

"U.S. Appl. No. 13/361,196, Response filed Nov. 21, 2012 to Non Final Office Action mailed Aug. 23, 2012", 13 pgs.

"U.S. Appl. No. 13/913,768, Preliminary Amendment mailed Dec. 3, 2013", 8 pgs.

"U.S. Appl. No. 14/512,350, Preliminary Amendment mailed Nov. 26, 2014", 10 pgs.

"Foursquare", Wikipedia, [Online]. Retrieved from the Internet: <http://en.wikipedia.org/wiki/Foursquare>, (Accessed Apr. 16, 2013), 12 pgs.

"Halfbakery: Buddy Locator", [Online]. Retrieved from the Internet: <URL: http://www.halfbakery.com/idea/Buddy\_20Locator#1055455737>, (Jun. 11, 2003), 2 pgs.

"Halfbakery: Mobile phone utility", [Online]. Retrieved from the Internet: <URL: http://www.halfbakery.com/idea/mobile\_ 20phone\_20utility#1073585857>, (Jan. 8, 2004), 2 pgs.

"Halfbakery: Mobile Proximity Link", [Online]. Retrieved from the Internet: <URL: http://www.halfbakery.com/idea/Mobile\_20Proximity\_20Link#1001923289>, (Sep. 30, 2001), 2 pgs.

"Networks in Motion Named Semi-Finalist for Wireless LBS Challenge", [Online]. Retrieved from the Internet: <URL: http://www.tmcnet.com/usubmiU2004/Mar/1025200.htm>, (Mar. 18, 2004), 1 pg.

"Proposal for free, open source cell phone location service", 90% Crud, [Online]. Retrieved from the Internet: <URL: http://george. hotelling.net/90percent/geekery/proposal\_for\_free\_open\_

source\_cell\_phone\_location\_service.php>, (Mar. 6, 2004), 1 pg. "SignalSoft Corporation awarded location-based services patent", [Online]. Retrieved from the Internet: <URL: http://www.cellular. co.za/news 2001/04282001-signalsoft-patent.htm>, (Apr. 27, 2001), 1 pg.


Carpendale, Marianne S.T, "A Framework for Elastic Presentation Space", Burnaby, British Columbia, Simon Fraser University, (1999), 296 pgs.


Keath, Jason, "21 Unique Location Examples from Foursquare", Gowalla, Whrrl, and MyTown, Socialfresh.com, (Jun. 1, 2010), 9 pgs.


Manninen, JP, ""Geofencing" enables new location-based apps, raises privacy concerns.", VentureBeat, [Online]. Retrieved from the Internet: <URL: http://venturebeat.com/20 10/04/23/geofencing -pushes-services-to-phones/ >, (Apr. 23, 2010), 4 pgs.


Yankovich, Steve, et al., "Targeted Incentive Actions Based on Location and Intent", U.S. Appl. No. 13/050,769, Application filed Mar. 17, 2011, 47 pgs.


\* cited by examiner

































FIG. 12











FIG. 15


FIG. 16












*FIG. 20* 






FIG. 23








FIG. 24













**U.S.** Patent



(uLoco	nte	TODAYS STOP	REPORT 🖂 FOR TRINTRAC (GP VAN) 🖂		HELP J LOG OUT
	DDAY (YESTERDAY) (SELECT)	REFRESH			
STOP	TIME	DURATION	LOCATION	DIRECTION/ SPEED	DISTANCE (MILES)
3	11/03/04 – 1:19 PM – 1:23 PM 11/03/04 – 12:34 PM	0:03	ULOCATE OFFICE Route 9, Natick, Ma	NW AT 0 MPH	3.84
2	11/03/04 – 8:50 AM – 8:58 AM 11/03/04 – 8:46 AM 11/03/04 – 8:35 AM 11/03/04 – 8:37 AM	0:03	ulocate office 154 commonwealth RD, wayland, wa Route 30, aubundale, wa Homer ST, newton center, wa	N AT O MPH W AT 30 MPH N AT 0 MPH	11.69
1	11/03/04 - 7:54 AM - 8:09 AM	0:14	874, WALNUT ST, NEWTON CENTER, MA		0.00
(ALL 1	rimes eastern)				
DOWN	load report as a comma separated	VALUE (CSV) FILI	e printei	R-FRIENDLY VERSION	

**U.S.** Patent







FIG. 33


(LOCATION) ADDRESS	BOOK 3402		
ADDRESS BOOK > SAVE LOCA			
LOCATION	ADDRESS		
geoff's home	14 BUSWELL PARK NEWTON, MA 02458	EDIT	DELETE
HOME	16 BAY COLONY DR Ashland, Ma 01721	edit	DELETE
ulocate's office	148 speen st Framingham, ma 01701	edit	DELETE
> <u>ADD LOCATION</u>			POWERED BY ULOCATE COMMUNICATIONS


FIG. 34



		2006		
uLocate	ALE	rt for ulo	cate test	
LOCATION	PHONE	event	ALERT CONTACTS	
ulocate office	ALAN	<=>	SMS: ALAN Email: Jeremy Email	edit   delete
ulocate office	GEOFF	<=>	email: Nina	edit   delete
ulocate office	ALAN	<=>	SMS: ALAN Email: Alan's Email Email: Frank's Email Email: Alan's Work Email	edit   delete
Frank's home	MAD	<=>	email: frank's email	edit   delete
Frank's home	FRANK	<=>	email: frank's email	EDIT   DELETE
ulocate office	stefan uwam	<=>	SMS: STEFAN'S SMS EMAIL: ALAN'S EMAIL EMAIL: FRANK'S EMAIL	EDIT   DELETE
<u>CREATE NEW ALERT</u>				

3602








FIG. 39A









FIG. 39B














### LOCATION-BASED SERVICES

#### CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation and claims the benefit of U.S. Non-Provisional application Ser. No. 13/361,113, filed Jan. 30, 2012, which is a continuation of and claims benefit of application Ser. No. 11/690,720, filed Mar. 23, 2007, entitled LOCATION-BASED SERVICES, which is a divi-<sup>10</sup> sional of and claims benefit of U.S. Non-Provisional No. 11/140,273, filed May 27, 2005 entitled LOCATION-BASED SERVICES, now U.S. Pat. No. 7,848,765, issued Dec. 7, 2010, which applications are hereby incorporated by reference in their entirety.<sup>15</sup>

#### BACKGROUND

Field of the Invention

This invention relates to the field of location-based ser-<sup>20</sup> vices, and more particularly to the field of location-based services involving portable electronic facilities.

Description of the Related Art

Location systems have been developed for determining and tracking the locations of the users of mobile devices <sup>25</sup> such as cellular phones, including global positioning systems (GPS), as well as various triangulation systems that use cellular telephone signals, broadcast television signals, or the like. Dead reckoning systems also exist for determining locations of devices based on movement in reference to a set <sup>30</sup> of known coordinates. However, to date the uses of such systems have been limited. A need exists for improved systems for using location-based information for a variety of purposes.

#### SUMMARY

A variety of methods and systems are disclosed herein that include the capability of tracking mobile devices, such as cellular phones. In various embodiments, the present 40 invention may provide an adaptable user interface, which may transmit a current location of a portable electronic facility, such as to another device or system and may receive an electronic storage file or other indication of the current location of the portable electronic facility. The file or mes- 45 sage may contain code the enables a specific user interface capability for the portable electronic facility, so that it displays a version of the user interface based on the contents of the electronic storage file, message or other contents. The portable electronic facility may take various forms, such as, 50 without limitation, a mobile phone, a GPS enabled mobile phone, a CDMA enabled mobile phone, a GPRS enabled mobile phone, a mobile phone with a camera, a mobile phone with browser capabilities, a GPS unit, a tracking unit, a portable electronic device with a compass, a laptop com- 55 puter, a personal digital assistant, an MP3 player, a camera, a handheld device, a pager, and/or a portable gaming device. The portable electronic facility may be wearable.

The storage file may be transmitted from a remote location and may without limitation be in a format such as an 60 XML document, a script, an HTML document, a program, a database, a table, a message, a folder, an application, an animation and/or a text file. The storage file may contain user interface information, such as specific menus that may be for a specific location and/or specific allocations that may 65 be for a specific location. The storage file may be updatable, wherein the user may manually update the storage file with

information or wherein the storage file may be automatically updated with information. The update may occur when a user stops at a location. The user may modify the interface. The adaptable user interface may produce results, such as an answer to a user's query.

An adaptable user interface may provide for receiving location-based information associated with the portable electronic facility and outputting a version of such information through the portable electronic facility. The information may be received in response to a transmission of the location of the portable electronic facility. The output version of such information may without limitation be visual, audio, a facsimile, an email, voice, a light, a change in the intensity of a light, a change in the color of a light, via SMS, via an instant message, via a text message, and/or an application that may only be available at certain locations. In some embodiments, at least one menu item may be changed in response to the information.

The information may be defined in relation to an object and/or a location. The information may be a geocentric list. The information may be specific to a user and may without limitation alter the look and feel of the facility, alter the functionality of the facility, be in an XML format, be in a database format, and/or be in a text file format. An alert, which may relate to an item on a list, may be triggered in response to the information.

The present invention may provide for location tracking, wherein a location of a portable electronic facility may be transmitted, stored in a file, stored with other information in the portable electronic facility, and reported along with an indication of the movement of the portable electronic facility. The information itself may be displayed on a map and may comprise an indication of speed and/or direction.

The present invention may provide business information 55 by storing the location of a plurality of portable electronic facilities, possibly in an electronic storage file or a locationcontaining file, which may be remote. The invention may provide access to the storage file, which may contain information pertaining to demographics, locations and motion of 40 the portable electronic facilities. Access to the storage file or information may be password protected and the storage file or information may be encrypted. The storage file may be an XML document, a database, a table or a text file.

The invention may provide demographic information associated with the portable electronic facilities. Tracking information may constitute traffic patterns.

The present invention may provide methods and systems for effecting change on a portable electronic facility in response to location information. The method may involve receiving location information on the portable electronic facility and effecting a change on the portable electronic facility based on the location information. The change may involve activating the portable electronic device, powering off portable electronic device, placing the portable electronic device in standby mode, starting an application, stopping an application or the output of information. The output may involve audio, video, a picture related a location, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration, stimulation at least one of the five senses or an alert. The alert may involve fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or stimulation of at least one of the five senses.

The change may involve a reminder regarding an item on a list and the list may be a geocentric list. The change may involve a change to at least one item on a menu. The change may affect the availability of an application. The change may also involve enabling free calling when within a certain geofence, such as within a home or a user-defined geofence.

The location information may relate to the accuracy of the location information. The information may refresh continuously, in accordance with set preferences or in response to 5 a request. The frequency of the requests may be varied in response to speed, location, specified preferences, proximity to a point of interest, or changes in a geofence. A user may make a request, such as a request for help, such as in response to pressing a panic button or activating a panic 10 mode on a portable electronic facility.

The present invention may provide for methods and systems of triggering the output of location-based information involving receiving information via a portable electronic facility and outputting location-based information 15 based on the received information. The information may be received via a sensor, which may measure the parameters of a device, facility or vehicle.

The present invention may provide methods and systems for location determination involving capturing characteris- 20 tics of a location using a portable electronic facility, transmitting those characteristics and receiving location based information. The characteristics may be captured as a picture, a photograph, verbally or using at least one sensor. The characteristics may be transmitted via SMS, fax, email, 25 instant message, text message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet, text or as a file.

The present invention may provide methods and systems of varying transmissions for a portable electronic facility 30 involving varying information transmissions to a portable electronic facility and varying information transmissions from a portable electronic facility. The length or frequency of the transmissions may be varied. The variation may be in response to velocity, direction, location, a point of interest, 35 an object, preferences, a location with respect to a geofence or changes in a geofence. The variation may result in increased battery life for the portable electronic facility. The data may be stored and transmitted all at one or it may be transmitted as it is updated.

The present invention may provide methods and systems of increasing the quality of location based information for a portable electronic facility, involving varying information transmissions to a portable electronic facility and varying information transmissions from a portable electronic facility. 45 The length or frequency of the transmissions may be varied. The variation may be in response to velocity, direction, location, a point of interest, an object, preferences, a location with respect to a geofence or changes in a geofence.

In an embodiment the information transmissions may be 50 from multiple sources. The multiple sources may be different networks or different means of communication. The means of communication may be SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. The information 55 may be granted at different access levels. A user may be may be transmitted in a costless manner, a cost reduced manner or in the form of a DNS lookup.

The present invention may provide methods and systems of increasing the quality of location based information for a portable electronic facility involving obtaining multiple data 60 points for a given item of information or a location. The multiple data points may be analyzed and outliers dropped. The analysis may be performed using an algorithm. The item of information may relate to location, velocity or direction.

The present invention may provide methods and systems 65 of defining a geofence on a portable electronic facility involving inputting the geofence using the portable elec4

tronic facility. The center and a radius of a geofence may be entered on the portable electronic facility. The geofence may be defined using a cursor on the display of the portable electronic facility. The geofence may be defined using a touch screen on the portable electronic facility. The geofence may be defined by the location of the portable electronic facility. The geofence may be defined by placing the portable electronic facility at certain points comprising the geofence. The geofence may be defined in real time by placing the portable electronic facility at certain points comprising the geofence. The geofence may be manipulated using the portable electronic facility. The geofence may be moved using the display of the portable electronic facility. The geofence may be moved using the portable electronic facility. The geofence may be a circle, a sphere, in the shape of any closed polygon, a closed volume, in two dimensions, in three dimensions or may travel with a person.

The present invention may provide methods and systems of defining a geofence on a computer screen involving inputting the geofence through a user interface. The geofence may be defined or moved about the interface using a pointing device such as a mouse or stylus. The radius, shape or dimensions of the geofence may also be defined or changed using a pointing device such as a mouse or stylus.

The present invention may provide methods and systems of sending location-based alerts involving determining the location of a portable electronic facility and sending an alert based on the location of the portable electronic facility. The alert may be in response to the location of a portable electronic facility with respect to a geofence. The alert may be via audio, video, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or may stimulate at least one of the five senses. The alert may be communicated via one of the following means of communication: SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text.

The present invention may provide methods and systems of analyzing information related to at least one portable 40 electronic facility involving transmitting information from the at least one portable electronic facility and analyzing such information using an analysis engine. The information from one or more portable electronic facilities may be stored or aggregated. The analysis engine may provide the ability to view location history or analyze location history. The analysis engine may also request additional information or send alerts. The analysis engine may perform analytics on location information such as demographic analysis, predictive analysis and descriptive analysis. The information provided by the analysis engine may include purchasing information, personal preferences, demographics or consumer purchasing data relating to individual consumers or classes of consumers.

Access to the analysis engine, the system and information granted partial or restricted access via a guest login. It may be that whether a user is permitted to know the location of another user is determined based on the access levels of the users

Methods and systems disclosed herein may include methods and systems for verifying a transaction using a portable electronic facility. Methods and systems disclosed herein may include methods and systems for tailoring information to the behavior of a user, such as observing the behavior of a user and communicating information to the user by a portable electronic facility, such as information based on the observed behavior of a user. Methods and systems disclosed

45

50

65

herein may include methods and systems for providing information to a portable electronic facility based on information received from the portable electronic facility, including location information. A network of portable electronic facilities may be provided, allowing communication among portable electronic facilities, including information based on the tracked locations of the portable electronic facilities. In embodiments information is communicated directly among the portable electronic facilities, without use of a central server. Information may be communicated by SMS, fax, 10 email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet and/or text.

Several possible graphical user interfaces may be presented on a portable electronic facility. The interface may display a map or a menu or provide an overview of the 15 locations of all the users in a defined group or of the location history of a particular user. The view may involve the use of tiled maps. The graphical user interface may present a stop report. A geofence may be created using a graphical user interface and an icon may be assigned to a geofence. A 20 mation for one particular user. graphical user interface may also display an address book or be used to define alerts. Graphical user interfaces may also be used to present of points of interest on a portable electronic facility. A graphical user interface that may allow a user to vary the frequency with which a portable electronic 25 device obtains location information.

#### BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 is a block diagram of components of a location 30 services facility.

FIG. 2 is a block diagram of additional components of the location services facility.

FIG. 3 is a block diagram of an aspect of a peer-to-peer configuration of the location services facility.

FIG. 4 is a block diagram of one aspect of the location services facility in operation.

FIG. 5 is a schematic diagram of an embodiment of part of the location services facility.

FIG. 6 is a block diagram of a portable electronic facility. 40

FIG. 7 is a block diagram of a GPS state machine.

FIG. 8 is a block diagram of the major components of the location services facility of the present invention.

FIG. 9 is a map overlaid with a geofence and a geographic location

FIG. 10 is a block diagram of an adaptable user interface.

FIG. 11 is a block diagram of an adaptable user interface.

FIG. 12 is a schematic diagram of location tracking.

FIG. 13 is a schematic diagram relating to the provision of business information.

FIG. 14 is a block diagram relating to effecting change on a portable electronic facility.

FIG. 15 is a schematic diagram relating to outputting location-based information on a portable electronic facility.

FIG. 16 is a schematic diagram relating to location 55 determination.

FIG. 17 is a schematic diagram relating to varying transmissions to and from a portable electronic facility.

FIG. 18 is a schematic diagram relating to increasing the quality of location based information on a portable elec- 60 tronic facility.

FIG. 19 is a block diagram related to defining a geofence on a portable electronic facility.

FIG. 20 is a block diagram related to defining a geofence on a computer.

FIG. 21 is a schematic diagram relating to sending location-based alerts.

6

FIG. 22 is a schematic diagram relating to analyzing information related to at least one portable electronic facility.

FIG. 23 is a schematic diagram relating to verifying a transaction using a portable electronic facility.

FIG. 24 is a schematic diagram relating to tailoring information to the behavior of a user.

FIG. 25 is a schematic diagram relating to providing information to a portable electronic facility based on information received from the portable electronic facility.

FIG. 26 is a block diagram presenting a network of portable electronic facilities.

FIGS. 27A-27C present several graphical user interfaces that may be presented on a portable electronic facility.

FIG. 28 depicts a graphical user interface providing an overview of the locations of all the users in a defined group.

FIG. 29 provides a view of the locations of the users in a defined group.

FIG. 30 presents a detailed display of the location infor-

FIG. 31 presents a stop report.

FIG. 32 shows a geofence.

FIG. 33 shows several icons that may be assigned to a geofence.

FIG. 34 depicts an address book.

FIG. 35 presents a more detailed view an address book

FIG. 36 depicts a graphical user interface that may be used to define alerts using the system.

FIGS. 37A-37C depict location details as both lists and maps.

FIGS. 38A-38C depicts several menus related to storing location-based information.

FIGS. 39A-39D depict several graphical user interfaces related to the presentation of points of interest on a portable 35 electronic facility.

FIG. 40 presents a graphical user interface that may allow a user to send location information via email or voice.

FIG. 41 presents a graphical user interface that may allow a user to input a zip code.

FIGS. 42A-42B presents a graphical user interface that may allow a user to vary the frequency with which a portable electronic device obtains location information.

#### DETAILED DESCRIPTION

Referring to FIG. 1 and FIG. 8, the present invention comprises a location services facility that may provide services or data products associated with a geolocation datum 104 associated with a portable electronic facility 300. The location services facility may comprise a database 100 containing aggregate data 102, an application server 108, and a Web server 110. The location services facility may provide the aggregate data 102, in raw or processed forms, to a third-party service provider **200**. In some embodiments, the present invention may comprise a network 304, which in some embodiments may be a peer-to-peer (P2P) network, comprising a plurality of facilities wherein each of the plurality of facilities may be a portable electronic facility 300 across which may be distributed the database 100, or its equivalent or constituent components 302, containing, in whole or in part, the aggregate data 102. An expanded view of one aspect of the P2P network is shown in FIG. 3. These embodiments are discussed in detail below and other embodiments will be apparent from the following discussion.

Referring to FIG. 4, the disclosed invention may gather a datum 104 from a portable electronic facility 300. The datum 104 may be stored in the database 100. In particular, the datum 104 may be representative of a position and/or velocity associated with the portable electronic facility 300. Alternatively or additionally, the datum may be representative of an output value from a sensor associated with the 5 portable electronic facility 300. In most cases, an additional datum 104 from the portable electronic facility 300 or another portable electronic facility 300 may also be stored in the database. The aggregate of a plurality of datum 104 from one or more portable electronic facilities 300 may comprise 10 aggregate data 102, which may be stored within the database 100.

Referring again to FIG. 1, the aggregate data 102 may flow from the database 100 to the application server 108. The application server 108, in turn, may provide an appli-15 cation based service, a number of which are described below and the general provision of which further comprise the disclosed invention. The application based service may be provided to a user of the portable electronic facility via a Web interface such as a Web browser. In this case, embodi-20 ments may comprise the Web server 110 for delivering the service.

Referring to FIG. 2, the aggregate data 102, in whole or in part, may be provided to a third-party service provider 200 in a predetermined format, which may be specified by 25 an XML schema. As provided, the data may be formatted or modified according to various needs, including without limitation a need of a first end user 202 who may be a data consumer (such as, revealing consumer behavior); a need of a second end user 204 who may be a user of the portable 30 electronic facility (such as, obeying a privacy agreement associated with the data); and/or a need of the third-party service provider 200 (such as, receiving data in a file that is formatted to facilitate automated processing). When formatted, the data may comprise a report, which may be a 35 computer generated report.

The third-party service provider **200** may in turn provide a service to the first end user **202** or the second end user **204**, wherein the service may be associated with the data. In some cases, the first end user **202** may be a marketing organization. Other cases will be apparent due to the following description.

In one embodiment, the aggregate data 102 may be disaggregated and provided to the third-party service provider as a single data point. This may be useful in many 45 applications including, but not limited to, a service that provides to the end user a map showing the location of the user and the user's immediate surroundings; a service that provides to the end user a map showing the location of a point of interest in the vicinity of the user; a service that 50 provides to the end user a map showing the location of another user; a service that provides to the end user a map showing the location of a pet associated with the user, wherein the pet may be fitted with a collar containing a portable electronic facility; the establishment of a geofence 55 (described below in detail) and the monitoring of the portable electronic facility with respect to its crossing the geofence; and so forth.

In another embodiment, the aggregate data **102** may be scrubbed and provided to the third-party service provider <sup>60</sup> **200** as a generalized dataset. This may be useful in many applications including, but not limited to, a service that may provide to a marketing company demographic information that may be representative of the generalized dataset, which may be representative of a plurality of users in a given <sup>65</sup> geographical area; a service that may provide the user with highway traffic information that may be based upon aggre8

gate traffic flows, which may comprise the generalized dataset; and so forth. For example and without limitation, in one application, the generalized dataset, which may comprise demographic information, may be representative of users' gender and spending habits, wherein the spending habits comprise the means and routes utilized by the users to arrive at a shopping destination. The generalized dataset may further comprise a unique identifier associated with each user represented, wherein the unique identifier may obscure the identity of each user while also allowing the third-party service provider **200** to discriminate between users, especially during an analysis of the generalized dataset.

In yet another embodiment, the aggregate data 102 may be provided in its entirety to the third-party service provider 200 as a comprehensive dataset. This may by useful in many applications including, but not limited to, a service that may provide to a logistics company detailed tracking information pertaining to a fleet of delivery vehicles, wherein each vehicle is located and tracked through time; a service that shows to a head of a household a plurality of locations representative of each of the members of the household; and so forth. For example and without limitation, a company providing cleaning services may utilize the aggregate data 102 to track how long its employees dwell at each customer location and which routes the employees take to travel to each customer location. This information may be useful in monitoring the efficiency of its employees and in optimizing assignments given to employees, for example and without limitation, by grouping jobs given to a particular employee into a smaller geographical area.

In still yet another embodiment, the aggregate data 102 may be processed to provide a service to a plurality of users. One example is a social networking application. For example, without limitation, a dating service may allow the plurality of users to enter individual preference information associated with a desired characteristic of a mate. Processing of the aggregate data 102 may allow the service to recognize when pairs of mutually desirable mates are in close proximity of each other. Data associated with this recognition may be transmitted to one or both users in the pair, allowing the users in the pair to meet each other. This transmission of data may be in the form of an alert, such as a text message, e-mail, automated telephone call, and so forth. For another example, an interested-based social network application may allow the plurality of users to enter individual preference information associated with a favorite pastime, such wine tasting. Processing of the aggregate data 102 may allow the service to recognize when events associated with the favorite pastime are being held in proximity to the users. Relevant users may be notified and additional information, which may encourage social interaction between the users, may be provided to users on the basis of the contents of the aggregate data 102. For example, a subset of users may, based upon observed travel patterns in the aggregate data 102, be likely carpool candidates to a local wine tasting

Generally, in embodiments, the aggregate data **102** may be disaggregated, scrubbed, reformatted, transmitted as-is, stored, processed, and/or formatted in any practicable manner that is useful to any particular third-party application. Moreover, in embodiments, an alert may be transmitted to a user, wherein the alert comprises data that is associated with a recognition that is associated with some form or component of the aggregate data.

Referring now to FIG. **5**, in one aspect, a system according to the present invention may comprise a database server

25

500, which may comprise the database 100; a Web/Application server 502, which may comprise the application server 108 and the Web server 110; and a storage device 504, which may store the database 100. It should be clear to one of ordinary skill in the art that these servers may exist as one 5 computer, as independent computers, as a network of workstations, as a cluster computer, as a part of a three-tier configuration such as a Web client connected via the Internet to a plurality of Web servers and application servers connected to one or more database servers, and so forth.

In one embodiment, a dual Internet connection 508 may arrive at a Cisco 6509 CIS load balancer/firewall/switch 510. Additionally connected to the Cisco 6509 510 may be an a-side 512 and a b-side 514 network, which may have independent main power sources. A Dell 1855 10-blade 15 server 502 may bridge the two networks and may run a Web server and two application servers, namely a mapping server and a routing server. There may be, in each of the a-side 512 and b-side 514 networks, a Dell 2850 database server 500

The database server 500, as is mentioned above, may store data representative of positions and/or velocities, which may be the aggregate data 102 and which may be associated with a plurality of portable electronic facilities 300.

The database server 500 may also store information pertaining to the user's privacy or security. The user may be provided an option to choose if the location and/or velocity of the portable electronic facility associated with the user is recorded in the database 100. This enables privacy by 30 allowing the user to determine the persistence of data associated with the user. The user may also be asked to provide a personal identification number (PIN), which may be entered into a handset that may be the portable electronic facility 300. This PIN, perhaps in conjunction with the 35 handset's phone number, comprises an authentication code needed to access a service enabled by the present invention, for example and without limitation, a Web site that provides a map showing the location of the user.

The database server 500 may also store information 40 pertaining to the user's level of access to a service enabled by the present invention. This access level may be used to determine a user's privileges. In one instance, a parent may want to allow a child to have access to the location of other family members, but not allow the child to establish a 45 geofence (described below) or an alert. In another instance, a plurality of handsets may be configured as peers in the network 304 when the network 304 is embodied as a P2P network. In this embodiment of the network 304, a first peer may exchange location and/or velocity data with a second 50 peer provided that the second peer has an appropriate level of access to such information from the first peer. In yet another instance, the exchange of information from the first peer to the second peer may be conditioned on the second peer having both the appropriate level of access and the user 55 of the second peer providing a PIN and/or authentication code that corresponds to a code stored in the database 100.

In other embodiments, some or all of the information pertaining to the user's level of access to a service is stored in the distributed database component 302 associated with 60 the portable electronic facility 300.

Referring again to FIG. 1, the application server 100 may host a geospatial application. The geospatial application may provide geo-coding, mapping, or routing functionality. Mapping functionality may comprise overlaying onto a map 65 a current location and a plurality of stored, past locations of the portable electronic facility. Routing functionality may

comprise overlaying onto the map the current location of the portable electronic facility 300 along with a calculated path from the current location to a specified destination. The calculated path may be a straight line, a route that follows geographic features such as a road or a river, a path between navigational aids such as very high frequency omnidirectional range (commonly known as a VOR), a great circle path, and so forth. Both the routing and mapping functionality may be provided by a commercial, off-the-shelf (COTS) application, such as the MapQuest Enterprise Server.

The application server 100 may host an alert application. The alert application may transmit the alert to a user in response to the occurrence of an event designated by the user as an alert-generating event. The alert may be sent via e-mail, short message service (SMS), interactive voice response (IVR), voice, instant message (IM), or any other practicable method.

The application server 100 may host a geofencing appliwhich may be connected to a RAID 5 storage facility 504. 20 cation, which monitors the location of one or more portable electronic facilities with respect to a geofence.

> The Web server 110 may provide a front-end interface to the user. The pages served by the Web server 110 may include geo-coding, mapping, routing, geofencing, or any other functionality supported by the application server 108 or the database 100.

> The portable electronic facility 300 may take a number of portable forms, including but not limited to a cell phone; a PDA; an electronic watch; a handheld GPS; a laptop computer; a portable music player such as an Apple iPod; an electronic keychain; a camera; or any other portable electronic facility.

> Referring now to FIG. 6, in addition to including technology providing for the ascertainment of the location of itself, the portable electronic facility 300 may comprise additional capabilities and facilities, such as a random access memory facility 600; a display facility 602, which may comprise a color display, a backlight, a liquid crystal display (LCD), a light-emitting diode (LED) screen, an organic light-emitting diode (OLED) screen, a flexible organic lightemitting diode (FOLED) screen, or a projection display; a power facility 604, which may comprise a battery, a power port, a photovoltaic facility such as a solar cell, or a fuel cell; an input facility 608, which may comprise a touch pad, a key pad, a stylus-based input facility, a speakerphone, or a microphone; a data communication facility 610, which may comprise a telescoping antenna, a fixed external antenna, an internal antenna, a serial data port, a parallel data port, a WiFi facility, a Bluetooth facility, or a ZigBee facility; a central processing unit 612; an operating system 614; a software application 618 such as but not limited to a game, a relationship management application, an expense tracker, a to-do list, a calendar, a notepad, a Web browser, an e-mail client, an audio file player, a photo viewer, a video viewer, a text editor, a time tracker, a day planner, a clock, a calculator, a dictionary, a file viewer, a synchronization manager, a virtual private network (VPN) client; and so forth.

> The portable electronic facility 300 may provide functionality complementary to and, in some embodiments, enhancing the location based service. Such functionality may include Web browsing, Web searching, wireless communication, software application execution, software application interpretation, entertaining lighting effects, a moving map display, a static map display, a map display with zoom capability, a color map, a grayscale map, a black-and-white map, and so on.

In various embodiments, the portable electronic facility **300** could be used in a vehicle, while camping, during the exploration of terrain, mounted on an animal such as but not limited to a dog collar, during a game, while walking through a city, and so forth.

The portable electronic facility 300 may communicate with the other elements of the location services facility, for example and without limitation the application server 108, the Web server 110, the database 100, the third-party service provider 200, the first end user 202, the second end user 204, 10 another portable electronic facility 300, the distributed database component 302, the peer-to-peer network 304, the database server 500, the Web/application server 502, the storage device 504, the dual internet connection 508, the Cisco 6509 510, the A-side network 512, and/or the B-side 15 network 514. This communication may comprise two-way communication or one-way communication. In embodiments, the portable electronic facility 300 may comprise a radio frequency (RF) transmitter/receiver providing the capability of sending and/or receiving data from a cellular 20 telephone network. The portable electronic facility may also or alternatively comprise an RF transmitter/receiver for sending and/or receiving data from a local area network, such as and without limitation an 802.11b "WiFi" network. The data communication facility 610 may further comprise 25 a physical connector, such as a docking port, which may allow for the synchronization of data to and/or from the portable electronic facility 300 and a host computer, such as a personal computer.

One consideration in the design of the portable electronic 30 facility 300 may be battery life. There are a number of factors that may affect battery life. One factor may be the power density of the battery. Another factor may be the volume of the battery. Yet another factor may be the power consumption of the portable electronic facility 300 con- 35 nected to the battery. In the portable electronic facility 300, it is typical for the power consumption to be dominated by RF transmission electronics that may be integral to the facility 300 and of which the data communication facility 610 may be comprised. This is due to theoretical and 40 practical limitations of the physics of RF transmission. The battery life of the portable electronic facility 300, then, may be improved by limiting the amount of time that the portable electronic facility 300 is transmitting data: the transmission electronics may be powered down the rest of the time. 45 Likewise, it is known that the power consumption of RF receive electronics, of which the data communication facility 610 may also be comprised, may have a considerable impact on the battery life of the portable electronic facility 300. It follows that methods for limiting the amount of time 50 that the portable electronic facility 300 is sending and/or receiving data may be present in some embodiments of the location services facility. These methods may comprise varying the length and/or frequency of transmissions to and/or from the portable electronic facility 300.

Another consideration in the design of the portable electronic facility **300** may be a speed with which the facility provides the user with data and/or the accuracy of the data. In embodiments, the portable electronic facility **300** and/or the location services facility at large may be designed to vary <sup>60</sup> the length and/or frequency of data transmissions to and/or from the electronic facility **300** to improve the speed with which the facility **300** provides a user with data and/or the accuracy of the data.

One aspect of the location services facility is to provide 65 location information to the user. Location information may comprise latitude; longitude; altitude; depth; pitch; roll;

yaw; time; velocity; or orientation and/or distance to or from a waypoint, an origin, a destination, magnetic north, or true north. The location may be presented to a user in a number of embodiments including, without limitation, a map, a moving map, an interactive map, a textual description, a spoken description, a color code, an aural code, an e-mail, a text message, a pager message, a printout, and so forth.

The location information provided by the location services facility to the user may originate from the use of various methods incorporating data from a sensor facility such as, without limitation, a global positioning system (GPS), a radio frequency identification (RFID), a plurality of cell phone towers (for example, for time and/or triangulation), an altimeter, a depth gauge, a gyroscope (including "gyroscopes" that use a vibrating structure, a laser, or a MEMS device), an inertial sensor, a compass, an accelerometer, a speedometer, a seismometer, a magnetometer, a thermometer, a photon detector (including, but not limited to, a visible camera, an infrared (IR) detector, an ultraviolet (UV) detector, an X-ray detector, a gamma-ray detector, a Geiger counter), a hygrometer, a heart rate monitor, a blood glucose meter, a blood oxygen meter, an electrical sensor, an electrical interference sensor, a current sensor, a resistance sensor, a thermistor, an electrostatic sensor, a frequency sensor, a temperature sensor, a heat sensor, a thermostat, a differential light sensor, an opacity sensor, a scattering sensor, a diffraction sensor, a refraction sensor, a reflection sensor, a polarization sensor, a phase sensor, a florescence sensor, a phosphorescence sensor, an optical activity sensor, an optical sensory array, an imaging sensor, a calibrated micro mirror array, a calibrated pixel array, a micro mirror array, a pixel array, an angular momentum sensor, a rotation sensor, a rotation speed sensor, a rotation direction sensor, a velocity sensor, an inclinometer, a momentum sensor, a smoke detector, a fire sensor, a heat detector, a combined heat and smoke detector, a vapor sensor, a gas sensor, a signal sensor, a wireless signal sensor, a cellular signal sensor, a Wi-Fi signal sensor, an Internet signal sensor, a touch sensor, a contact sensor, a viscosity sensor, a position sensor, a height sensor, a ray detector, a microwave sensor, a proximity sensor, a distance sensor, a motion sensor, a range sensor, a mote, a marker, a powered marked, a signal emitter, a signal receiver, a powered signal emitter, a powered signal receiver, a chemical sensor, a fire sensor, a hazardous material sensor, a hazardous vapor sensor, a biohazard sensor, a bacteria sensor, a virus sensor, an anthrax detector, a nerve gas sensor, a poisonous gas sensor, a carbon monoxide detector, an energy sensor, or an aerosol sensor. RFID tracking may, without limitation, comprise a portable electronic facility further comprising a RFID transponder that is interrogated by electronic equipment that is installed along a roadway, along a sidewalk, at the entrance of a building, at the egress of a building, or in a building. Once created, the location information may be compiled, 55 accessed, processed, searched, sorted, or in any other way manipulated for the benefit of the first end user 202, the second end user 204, or any other entity that values the user's location information. In embodiments a location may be obtained from a database, such as based on the location of a wireless access facility, such as a Wi-Fi or 802.xx access point, switch, or similar device.

In embodiments, an individual location information sample, which may be a datum **104**, may be subject to errors, which may be due to physical or practical limitations of the location services facility. For example, cell phone triangulation systems are limited by RF multipath effects due to large metal structures such as building or water towers. One method of compensating for these errors may comprise processing multiple location samples to determine, via statistics or heuristics, to what extent the individual location information sample may be reliable. Another method of compensating for these errors may comprise processing multiple location samples to determine an aggregate location information sample that may include information such as mean location and standard deviation, which may provide a more accurate determination of location than the individual location information sample.

Referring now to FIG. 7, the portable electronic facility 300 may comprise a state machine 702 heuristic approach to obtaining a GPS fix 700. The state machine 702 may comprise a plurality of states, **704**, **708**, **710**, **712**, **714**, and 718. The state machine 702 may comprise a fix delay, which may be a string that may be processed by the central processing unit 612, the operating system 614, the software application 618, the geolocation facility 620, or any other facility associated with the geolocation facility 620. In the  $_{20}$ plurality of states, "mposition:delay=low" may indicate a fix delay that may take no greater than 32 seconds to provide a limited degree of computation for determining a low-accuracy velocity of the portable electronic facility 300. "mposition:delay=high" may indicate a fix delay that will take no 25 an operational mode, the facility 300 may make an attempt greater than 3 minutes and 32 seconds to provide a substantial degree of computation for determining a high-accuracy velocity of the portable electronic facility 300.

The Inside State 704 may reflect that the facility 300 may be receiving the GPS fix 700 from a tower. In this state, the facility 300 may sleep for 90 seconds and then may attempt to receive a fix, at first, using mposition:delay=low and then for every fix thereafter using mposition:delay=high. Should the facility 300 receive five fix attempts in the Inside State 35 704, the facility 300 may go into the Sleep State 704.

The Stopped State 710 may reflect that the facility 300 may be receiving the GPS fix 700 from a satellite and that the facility 300 may be associated with a speed, according to the fix's National Marine Electronics Association's 40 (NMEA) string 720, of approximately 0 kilometers per hour (KPH). In this state, the facility 300 may sleep for approximately 90 seconds and then may attempt to receive a fix using mposition:delay=high. Should the facility 300 receive five sequential GPS fixes 700 in the Stopped State 710, the 45 device may go into the Sleep State 704. In the Stopped State 710, the facility 300 may send every GPS fix 700, of which a datum 104 may be comprised, to a datum receiving facility, which may, without limitation, comprise the database 100, the application server 108, the Web server 110, another 50 portable electronic facility 300 such as via the P2P network 304, or any other facility associated with the database 100 or the distributed database component 302.

The Moving\_Slow State 712 may reflect that the facility 300 may be receiving the GPS fix 700 from a satellite and 55 may be associated with a speed, according to the fix's NMEA string 720, of greater than approximately 0 KPH and less than approximately 17 KPH. In this state, the facility 300 may sleep for 60 seconds and then may attempt to receive the GPS fix 700 using a mposition:delay=high and 60 every GPS fix may be sent to the datum receiving facility.

The Moving\_Med State 714 may reflect—that the facility 300 may be receiving the GPS fix 700 from a satellite and may be associated with a speed, according to the fix's NMEA string 720, of greater than approximately 17 KPH 65 and less than approximately 106 KPH. In this state, the facility 300 may sleep for 30 seconds and then may attempt

to receive the GPS fix 700 using mposition:delay=high and every GPS fix 700 may be sent to the datum receiving facility.

The Moving\_Fast state 718 may reflect that the facility 300 may be receiving the GPS fix 700 from a satellite and may be associated with a speed, according to the fix's NMEA string 720, of greater than approximately 105 KPH. In this state, the facility 300 may sleep for 10 seconds and then may attempt to receive a GPS fix 700 using mposition: delay=high and every GPS fix may be sent to the datum receiving facility.

The Sleep State 704, as is mentioned above, may reflect that the facility 300 may have received five GPS fixes in a row in the Stopped State 710 or may have receive five GPS fixes in a row in the Inside State 708. In this state, the device may sleep for approximately two minutes and then attempt to receive a GPS fix 700 alternating with the use of mposition:delay=high and mposition:delay=low.

The state machine may also note a significant position change wherein a new GPS fix may generate a measured change in distance of greater than 10 kilometers. A check for the significant position change may be taken on every GPS fix 700 in the Sleep State 704 or Inside State 708.

When the portable electronic facility 300 is switched into to retrieve a GPS fix using an mposition:delay=low. If the facility 300 cannot receive a satellite GPS fix 700 on a first fix attempt, the facility 300 may immediately or soon thereafter make another attempt to receive a GPS fix 700 using mposition:delay=high. In either case, the facility 300 may consequently be considered to be initialized.

The facility 300 may, based upon its current state, make attempts to receive the GPS fix 700 at a rate, which may be periodic. In the event that the GPS fix 700 cannot be obtained or is invalid, the facility 300 may alert a user of the facility 300. In the event that a valid GPS fix 700 cannot be obtained during five consecutive attempts, the facility 300 may discontinue attempts to get the GPS fix 700, which may necessitate a manual restart of the facility 300 to renew attempts to obtain the GPS fix 700.

Once obtained or calculated, the location information, which may comprise the GPS fix 700, may be used in an application service including, but not limited to, an entertainment application service such as location-aware games, a commerce application service such as location-based transactions, an information application service such as mapping a route from an origin to a destination, or any other application service specified, mentioned, implied, or made apparent by this discussion.

Referring now to FIG. 9, as mentioned above, the location services facility may support a geofencing application that involves the geofence 900. In one case, the geofence 900 is the circumference of a circle that is defined by a user who specifies a geographic location 902 for its center and a radius. In general, the geofence 900 may be defined as any arbitrary boundary between one geographic area and another, wherein the boundary may be stationary or may move, wherein said movement either may be correlated to the movement of a physical object such as the portable electronic facility 300 or may be determined arbitrarily. In any case, the geofencing application may be the alert application and, therefore, may generate the alert when the portable electronic facility 300 crosses the geofence 900. This alert may be transmitted to the user who specified the crossing of the geofence 900 as an alert-generating event. Alternatively or additionally, this alert may be transmitted to a second user who either opted to receive the alert or who

was designated to receive the alert. Optionally, the alert may pertain to a facility in the vicinity of the geofence **900**, such as and without limitation an advertisement for a nearby restaurant.

In embodiments, the user may define and/or manipulate a 5 geofence **900** via the Web browser of the three-tier architecture. Alternatively, the user may define and/or manipulate a geofence **900** via the portable electronic facility **300**, for example and without limitation via the input facility **608** of the portable electronic facility **300**.

The location services facility may support a number of end uses. One end use may comprise a location based adaptable user interface. For example, in an embodiment, the portable electronic facility **300** may be a cell phone. A screen integral to the cell phone may display information to 15 the user of the cell phone. Under usual circumstances, the screen may display a small menu of options, such as show location and get directions. However, when the cell phone is within proximity of a restaurant, the screen may display an additional menu option make dinner reservation. This adap-20 tation to the menu of options is an example of a location based adaptable user interface.

Another end use may comprise the tracking of the location of the portable electronic facility **300**, which has been described above.

Yet another end use may comprise providing business information associated with the portable electronic facility. For example, a comprehensive stop report provided by the location services facility may comprise a plurality of entries comprising a stop identification, a time, a duration, and a 30 location. The stop identification may comprise a unique identifier comprising a number associated with a stop made by a delivery truck. The time may be associated with a time at which the delivery truck stopped. The duration may be associated with the time that the delivery trucked dwelled at 35 the stop. The location may be associated with the geographic location of the stop. In total, the comprehensive stop report may provide information useful to an operator of a business in monitoring the performance of a fleet of delivery trucks.

Still yet another end use may comprise remotely affecting 40 the portable electronic facility **300**. In one embodiment, the location services facility may start, stop, or change an application on the facility **300**. The application may comprise, without limitation, a map, a route, a to-do list, a calendar, a calculator, an expense report, a mileage tracker, 45 a phone book, and so forth.

Another end use may comprise outputting location information on the portable electronic facility 300. As is mentioned above, the portable electronic facility 300 may provide to the user location information associated with the 50 portable electronic facility 300, for example and without limitation, information in the form of a map. The portable electronic facility 300 may augment the information provided by the location services facility with information from the sensor. For example, the location services facility may 55 provide mapping information to the portable electronic facility 300 according to the location data provided by the facility **300** to the location services facility. Upon this map, the facility 300 may overlay an artificial horizon, which provides pitch and roll information to the user. This pitch 60 and roll information may be provided to the portable electronic facility 300 by the sensor.

Yet another end use may comprise outputting location information on the portable electronic facility **300**, wherein the location information itself depends upon the output 65 sensor. For example, in an embodiment wherein the sensor is a visible camera, images of surrounding terrain may be

captured by the camera and may be transmitted to the location services facility. The location services facility may analyze these images and transmit location information associated with the images back to the portable electronic facility **300**. This location information may then be output by the portable electronic facility **300** for presentation to the user.

More generally, a plurality of end uses may comprise presenting location based information to the user in response to the characteristics of a location. In one embodiment, as described above, the characteristics of a location may be the terrain in the vicinity of the location. In other embodiments, the characteristics of a location may, without limitation, comprise the barometric pressure, humidity, temperature, radioactivity, depth, infrared lighting, visible lighting, ultraviolet lighting, and so forth.

Another end use may comprise providing location information associated with a transaction. In one embodiment, a person may present a credit card associated with the user to a merchant at a point of sale. The merchant or merchant's bank may query the location services facility to determine the location of the portable electronic facility 300 associated with the user. If the portable electronic facility 300 is located at the merchant then the user may be presumed to be located at the merchant and the person may be presumed to be the user. Therefore, the transaction may be authorized. Conversely, if the portable electronic facility 300 is located at a location other than at the merchant then the location of the user may be deemed to be in question and the person is may not be deemed to be the user. As a result, the transaction may be denied or the merchant may be required to further verify the identity of the user.

Yet another end use may comprise tailoring information to the behavior of a user. In one embodiment, the location services facility may recognize that the route a user usually takes to and from work is suboptimal. In response to this behavior of the user, the location services facility may provide to the user a custom tailored, daily-commute route map.

More generally speaking, end uses of the location services facility may provide information to the portable electronic facility **300** based on information received from the portable electronic facility **300**, including but not limited to information associated with the user's behavior.

Referring now to FIG. 10, the present invention may provide an adaptable user interface 1000, which may transmit a current location 1002 of a portable electronic facility 300, such as to another device or system and may receive an electronic storage file 1004 or other indication of the current location of the portable electronic facility 300. The file or message may contain code the enables a specific user interface capability for the portable electronic facility 300, so that it displays a version of the user interface 1000 based on the contents of the electronic storage file 1004, message or other contents. The portable electronic facility 300 may take various forms, such as, without limitation, a mobile phone, a GPS enabled mobile phone, a CDMA enabled mobile phone, a GPRS enabled mobile phone, a mobile phone with a camera, a mobile phone with browser capabilities, a GPS unit, a tracking unit, a portable electronic device with a compass, a laptop computer, a personal digital assistant, an MP3 player, a camera, a handheld device, a pager, and/or a portable gaming device. The portable electronic facility 300 may be wearable.

The storage file **1004** may be transmitted from a remote location and may without limitation be in a format such as an XML document, a script, an HTML document, a pro-

gram, a database, a table, a message, a folder, an application, an animation and/or a text file. The storage file **1004** may contain user interface information, such as specific menus that may be for a specific location and/or specific allocations that may be for a specific location. The storage file **1004** may 5 be updatable, wherein the user may manually update the storage file **1004** with information or wherein the storage file **1004** may be automatically updated with information. The update may occur when a user stops at a location.

In embodiments, the storage file **1004** may be stored 10 locally and/or remotely. The storage file **1004** may contain similar locations, such as without limitation points of interest, which may be displayed based upon factors such as speed, location, and/or user preference. The user preference may be maintained in a user-preference file, which may be 15 stored locally and/or remotely, and which in certain embodiments may comprise the storage file **1004**.

In embodiments one feature of the adaptable user interface 1000 is that the user may modify the interface 1000. For example, a menu selection may be modified, automatically 20 and/or manually. Selections from the menu may be added, such as from a list of menu options. Another feature of the adaptable user interface 1000 is that an application selection may be modified, automatically and/or manually, wherein the modification may be the addition and/or removal of an 25 application, which may be selected from an available list. Yet another feature of the adaptable user interface 1000 is that it may maintain location specific information, wherein the information may be available near the location, wherein user orders may be created. The user orders may be based 30 without limitation on a user list; the proximity of a store; an order sent by text; an order sent by voice; or another order that may be transmitted. The locations in the storage file 1004 may be based on a coordinate system, such as and without limitation the Cartesian coordinate system; the polar 35 coordinate system; latitude and longitude; and/or latitude, longitude and altitude.

The adaptable user interface **1000** may produce results, such as an answer to a user's query. The results may be based on the location of the portable electronic facility **300**, 40 wherein the results may be sorted based on the speed and/or direction, preferences, and/or accessibility of locations of the portable electronic facility **300**. Web search results may be based upon the location of the portable electronic facility **300** and may be sorted based on portable electronic facility **300** and may be sorted based on portable electronic facility **300** speed, portable electronic facility **300** direction, preferences, and/or accessibility of locations. A localized search may be conducted based on the location of the portable electronic facility **300**, wherein the search results may be sorted based on portable electronic facility **300** speed, portable electronic facility **300** speed.

Referring now to FIG. 11, an adaptable user interface 1000 may provide for receiving location-based information 1100 associated with the portable electronic facility 300 and 55 outputting a version 1102 of such information 1100 through the portable electronic facility 300. The information 1100 may be received in response to a transmission of the location of the portable electronic facility 300. The output version 1100 of such information 1102 may without limitation be 60 visual, audio, a facsimile, an email, voice, a light, a change in the intensity of a light, a change in the color of a light, via SMS, via an instant message, via a text message, and/or an application that may only be available at certain locations. In some embodiments, at least one menu item may be changed 65 in response to the information 1100. Moreover, the user may modify the interface 1000.

The information **1100** may be defined in relation to an object and/or a location. Multiple networks may supply the information **1100**, which may be altered such as created, updated, supplemented, augmented, reduced, encoded, decoded, encrypted, decrypted, and/or deleted. Alterations may be at a frequency that may be based on the velocity of the portable electronic facility **300** and/or the location of the portable electronic facility **300**. The information **1100** may be a geocentric list.

The information 1100 may be specific to a user and may without limitation alter the look and feel of the facility 300, alter the functionality of the facility 300, be in an XML format, be in a database format, and/or be in a text file format.

An alert, which may relate to an item on a list, may be triggered in response to the information **1100**.

Referring now to FIG. 12, the present invention may provide for location tracking 1200, wherein a location 1202 of a portable electronic facility 300 may be transmitted, stored in a file 1204 (which, in embodiments, may comprise the electronic storage file 1004), stored with other information (such as and/or associated with aggregate data 102, datum 104, geographic location 902, and so forth) in the portable electronic facility 300, and reported along with an indication of the movement 1208 of the portable electronic facility 300. The file 1204 may be stored remotely (such as and without limitation in database 100, in a distributed database component 302, in a database server 500, and/or in a storage device 504). The file 1204 may maintain an archive 1210 of a plurality of locations 1202 associated with the portable electronic facility 300, which may be displayed and in which an indication of movement 1208 may be reported.

The information itself may be displayed on a map 1212 and may comprise an indication of speed and/or direction 1214. The location 1202 may be masked, wherein the masking may involve substituting a different location for the actual location 1202.

In applications, the location tracking facility **1200** may be used by families to track members of the family, such as children or elderly members of the family. For example, in tracking the location of a child, the tracking may identify a position, within a yard, upon the activation of certain triggers, such as upon request by another family member, if the child is lost, and/or only at specified times such as a day of the week and/or time of day. For example, in tracking the location of elderly, the tracking **1200** may be in a home, in a hospital, and/or in a care facility.

In other applications, the location tracking **1200** may be used to track driving and/or vehicle location. This tracking **1200** may comprise tracking location **1202**, speed, and/or a set path. An alarm, which may be an alert, may be sent when the driving is classified as speeding. An alert may also be sent if the vehicle position is outside a boundary, wherein the boundary is associated with shipping a hazardous material. In some applications, the location tracking may encompass the vehicle location of every vehicle in a fleet.

In general applications, the tracking **1200** may be remotely set, permanently enabled, and/or disabled only from a remote location. Thus, the portable electronic facility **300** may be controlled remotely, which may include the remote control of an application (such as and without limitation software application **618**) within the portable electronic facility **300**.

In yet another application, the tracking **1200** may be used for computer gaming, wherein one or more features of the game may be based on the real-world location **1202** of the portable electronic facility **300**. In embodiments the realworld location 1202 of the portable electronic facility 300 may be used to trigger other actions or events within the game. In such embodiments, the real-world location may be fed to a program or system that generates game conditions based on the location, such as from a table, database, or other 5 facility, or based on real-world information associated with the location, such as weather information, stored views of the location, maps of the location, or the like. For example, the current weather conditions in the environment surrounding the portable electronic facility 300 may be retrieved 10 from a server that obtains weather information, and a game operating on the portable electronic facility 300 may present similar conditions to the user of the portable electronic facility 300, such as in a role-playing game, a driving game, first person shooting game, or other simulation game. Simi- 15 larly, a map for area surrounding a user may be used to generate a simulated environment in the game that resembles the user's real world environment. For example, locations of buildings and roads can be used to create a "track" in a driving game, or to create obstacles or locations 20 in a role-playing game. In embodiments locations of other portable electronic facilities 300, such as those used by friends or family members of a user, can be used to generate game elements, such as to allow users to "race", "battle", or otherwise interact in a multi-player game that draws ele- 25 ments such as weather, roads, or buildings from the realworld environments of the users of the portable electronic facilities 300. Thus, in a variety of embodiments, a game on a portable electronic facility 300 may be location-based.

In still another application, the location tracking **1200** 30 may be used as a basis for selecting entertainment such as determining available shows, movies, and/or food facilities. For example, a menu of video or movie clips may be made available based on the location of the portable electronic facility **300**, such as showing movies that contain scenes that 35 depict areas that are in proximity to the current location of the facility **300**, showing tourist information for the area near the facility **300**, or the like.

In still yet another application, the tracking **1200** may be associated with a police activity, such as, without limitation, 40 tracking shoplifters, tracking criminals, placing a portable electronic facility **300** in a money bag, and/or placing a portable electronic facility **300** in a bank teller drawer.

In another application, the tracking **1200** may be associated with a security activity, such as and without limitation 45 tracking people within a facility, wherein the tracking may comprise tracking direction and/or speed; tracking personnel such as sales people, social workers, home health care workers; tracking dangerous substances; and/or tracking dangerous shipments. For example, a geofence may be 50 established around a particular location, so that an alert is sent if a person exits the area of the geofence, such as if a home health care worker leaves a scene, a worker enters a hazardous area, a shipment departs from a planned route, a social worker fails to appear at a designated location for an 55 appointment, a maintenance worker fails to appear at a designated location, or the like.

In still another application, the tracking **1200** may be associated with a pet, such as and without limitation tracking the pet within a yard and/or if lost. A geofence may be 60 established around the pet, so that an alert is sent if the pet departs the region of the geofence.

In yet still another application, the tracking **1200** may be associated with a school, such as and without limitation tracking students and/or employees at all times and/or only 65 if they leave school property. A geofence around the school can allow a teacher, administrator or parent know when a

child arrives at the school, leaves the school, or the like. Thus, portable electronic facilities **300** can be used to check attendance against the rolls of the school, and to determine the locations of absent students who possess such portable electronic facilities **300**.

In an embodiment, the tracking **1200** may be associated with health care, such as and without limitation tracking patients, doctors, and/or nurses. In this application, the tracking **1200** may be within a health care facility, outside a health care facility, and/or may comprise finding the closest doctor and/or nurse in an emergency. A geofence may be established, for example, indicating when a patient has left a hospital, or indicating when a doctor arrives or departs the proximity of the facility, such as to generate an alert if there are not enough staff available to handle an emergency.

In another application, the tracking **1200** may be associated with real estate, such as, without limitation, tracking a location of a house for sale, which may be associated with a picture, directions, and/or tracking visitors to the real estate. For example, a portable electronic facility **300** may be associated with a digital camera, and the location of a picture or recording, as determined by the tracking facility **1200**, may be embedded in the picture or recording for future retrieval of the location of the picture. Such a picture or recording location capability may be used to know the location of a real estate location, the location of an accident, the location where a photo was taken during a vacation, the location of a crime, or the location of another event that is recorded on the digital camera.

The capability to record the location of a picture or a recording may support transport logistics, the adjustment of traffic signals, the documentation of potholes, the documentation of defects in infrastructure, and/or an insurance purpose. The insurance purpose may comprise documenting the location of accident; capturing a picture or recording of an accident such as for the purpose of adjusting claims; storing driving habits on file such as for the purpose of determining safe driving, which may be associated with changes in insurance prices based on driving speed. The picture or recording location tracking may support bounty hunters, private investigators, police, detectives, or other in, for example, tracking people. For example, tracking 1200 may support tracking a stalker, for example, in determining a distance in relation to another person where, in some embodiments, an alert that may be sent to police is sent if the stalker is too close to a person.

In embodiments, the tracking **1200** may support a maid service in, for example, tracking the time that a maid spends at a location and, perhaps, comparing the actual billed charges to the tracked time.

In embodiments the tracking **1200** may support fleet management in, for example, tracking the dwell time of a vehicle in the fleet on a location and, perhaps, comparing an actual billed charge to the tracked dwell time at a location, which may be a tracked location **1202**. This tracking **1200** may serve a purpose in project accounting.

The tracking **1200** may support armored cars in, for example, tracking locations of the armored cars and, perhaps, tracking deviation from a set path. The tracking **1200** may support parole tracking such as the tracking of a person, perhaps with respect to an allowable zone, wherein if the person being tracked is outside an allowable zone (such as and without limitation a geofence **900**) an alert may be sent. The tracking **1200** may support emergency dispatching, which may be associated with a known location of a person and which may provide directions to the known location. The tracking **1200** may support roadside assistance dispatching, which may be associated with the known location of a person and which may provide directions to the known location. The tracking **1200** may support an alert, which may be an alert where the alert may be without limitation audio, visual, associated with a location that may be user detersmined, in response to a vehicle, via fax, via email, via instant message, via a text message, via SMS, via an Internet protocol, via voice, via voicemail, in the form of a vibration.

In embodiments, the tracking **1200** may be associated with the location of a lobster trap, wherein the tracking may be further associated with an indication of whether the lobster trap has been previously checked.

In embodiments the tracking **1200** may be associated with social networking, such as, without limitation, introducing certain people to each other; introducing certain groups of 15 people; communicating with at least one individual; and/or communicating with a group of individuals, such as informing them of an event at a location (which may be the location **1202**).

Referring now to FIG. 13, the present invention may 20 provide business information by storing the location of a plurality of portable electronic facilities 300, possibly in an electronic storage file 1004 or a location-containing file 1204, which may be remote. The invention may provide access to the storage file 1004 or 1204, which may contain 25 information pertaining to demographics, locations and motion of the portable electronic facilities. Access to the storage file 1004 or 1204 or information may be password protected and the storage file 1004 or 1204 or information may be an 30 XML document, a database, a table or a text file.

The invention may provide demographic information associated with the portable electronic facilities 300, such as the number and types of facilities 300 with particular demographic or other characteristics in a certain area or the 35 speed and location of the facilities 300. For example, location information may be associated with demographic information or information about past behavior of users of portable electronic facilities 300, to determine the characteristics of users in an area. For example, if many users 40 within a geofence 900 that is associated with a large retail store are shown to have high income and to be interested in electronics, then the store can make an announcement about a high-end electronics item that is for sale. Similarly, if many users within the area of a restaurant have a preference for a 45 particular food (based on past purchases), then the restaurant can prepare to serve that food, such as by ordering and offering that food. Thus, a system may include a geofence for establishing a proximity of a location and may track or take actions based on the characteristics of users within that 50 geofence, such as determined by past actions of those users, such as purchases, browsing, or other behavior performed by the users using their portable electronic facilities 300.

In embodiments, tracking information may constitute traffic patterns, and such traffic patterns may be compared to 55 historical traffic patterns for infrastructure design.

Referring now to FIG. 14, the present invention may provide methods and systems for effecting change on a portable electronic facility 300 in response to location information 1100. The method may involve receiving location information 1100 on the portable electronic facility 300 and effecting a change on the portable electronic facility based on the location information 1100. The change may involve activating the portable electronic device, powering off portable electronic device, placing the portable electronic 65 device in standby mode, starting an application, stopping an application or the output of information. The output may

involve audio, video, a picture related a location, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration, stimulation at least one of the five senses or an alert. The alert may involve fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or stimulation of at least one of the five senses.

In another embodiment the change may involve a reminder regarding an item on a list and the list may be a geocentric list. For example, the reminder may be to purchase an item at a location in close proximity to the portable electronic facility 300. For example, a user's grocery list may be presented in response to the user entering a geofence 900 that is defined around a grocery store. In another example, the reminder may be to perform a task at a location in close proximity to the portable electronic facility 300. For example, in arriving within a geofence 900 that is defined around a friend's home, a user may be reminded to drop off an item at the friend's house. Thus, the methods and systems described herein include location-based reminders, to do lists, and task lists, and in embodiments the location-based reminders are triggered by the proximity of a portable electronic facility 300 to a geofence 900 that is defined by a user of the portable electronic facility 300.

In another embodiment the change may involve a change to at least one item on a menu. For example, the change may be the removal or addition of a class of point of interest from or to a menu. For example, the class of point of interest may be a hotel, store or tourist location. For example, when a user is far from home, nearby locations of stores, tourist locations and hotels may be presented to a user in the user interface, but such locations may be removed from the menu when the user is close to home, on the assumption that a user is familiar with stores near the user's home and that the user will not need hotel or tourist information near home. In embodiments a portable electronic facility **300** may allow a user to modify preferences for what items are presented when a user is near a particular location or far from that location.

In another embodiment the change may affect the availability of an application. The change may also involve enabling free calling when within a certain geofence, such as within a home or a user defined geofence. Thus, a telecommunications system may track user locations through their portable electronic facilities **300**, and may determine the presence of a user within a geofence **900** associated, for example, with a home, business, school, or other location of the user. The telecommunications system may vary the rate charged to the user based on proximity to the geofence **900**.

In embodiments location information **1100** may relate to the accuracy of the location information or be stored in relation to a particular location, coordinate (such as Cartesian or polar coordinates), latitude, longitude or altitude. The information may refresh continuously, in accordance with set preferences or in response to a request. The frequency of the requests may be varied in response to speed, location, specified preferences, proximity to a point of interest, or changes in a geofence **900**. The frequency of the requests may also be varied in such a manner as to have the effect of extending the battery life of the portable electronic facility **300**. Thus, a power management application may manage the use of a location-based application based on the location of a user to preserve battery life in a portable electronic facility **300**.

In embodiments, a user may make a request, such as a request for help, such as in response to pressing a panic button or activating a panic mode on a portable electronic

facility 300. The request for help may include location information 1100, information relevant to the emergency or other information. The request may include a picture or recording taken by a camera of the portable electronic facility 300, and the picture or recording may have embed- 5 ded in it location information.

In embodiments the location information 1100 may be received via SMS, fax, email, instant message, text message, internet protocol, voice, voicemail, GPRS, CDMA, W AP protocol, internet, text or as a file.

Referring now to FIG. 15, the present invention may provide for methods and systems of triggering the output of location-based information 1100 involving receiving information via a portable electronic facility 300 and outputting location-based information 1100 based on the received 15 information.

The information 1100 may be received via a sensor 1502, which may measure the parameters of a device, facility 300 or vehicle. The sensor may provide information relating to the fuel-level of a vehicle. The fuel may be gasoline, diesel, 20 propane, hydrogen, alcohol-based or ethanol. The sensor may transmit the information via Bluetooth or by other means. In embodiments the location-based information 1100 may consist of a list of fueling stations in the area, fuel prices and hours of operation. The sensor may also enable moni- 25 toring and the location-based information 1100 may be relevant to the monitoring.

Referring to FIG. 16, the present invention may provide methods and systems for location determination involving capturing characteristics of a location 1202 using a portable 30 electronic facility 300, transmitting those characteristics and receiving location based information 1100. The characteristics may be captured as a picture, a photograph, verbally or using at least one sensor. The picture may be entered by a user. The photograph may be taken with a camera on the 35 portable electronic facility 300. The sensor may be a temperature sensor, a velocity sensor, a direction sensor, an altitude sensor, a pressure sensor, a fluid level sensor or a power level sensor. The characteristics may be transmitted via SMS, fax, email, instant message, text message, internet 40 protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet, text or as a file.

Referring to FIG. 17, the present invention may provide methods and systems of varying transmissions 1702 for a portable electronic facility 300 involving varying informa- 45 tion transmissions 1702 to a portable electronic facility 300 and varying information transmissions 1702 from a portable electronic facility 300. The length or frequency of the transmissions 1702 may be varied. The variation may be in response to velocity, direction, location, a point of interest, 50 an object, preferences, a location with respect to a geofence or changes in a geofence. The variation may result in increased battery life for the portable electronic facility 300. The data may be stored and transmitted all at one or it may be transmitted as it is updated. The data may be location 55 information 1100.

In an embodiment the information transmissions may be from multiple sources. The multiple sources may be different networks or different means of communication. The means of communication may be SMS, fax, email, instant 60 message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. The information may be transmitted in a costless manner, a cost reduced manner or in the form of a DNS lookup.

Referring again to FIG. 17, the present invention may 65 provide methods and systems of increasing the quality of location based information 1100 for a portable electronic

facility 300, involving varying information transmissions 1702 to a portable electronic facility 300 and varying information transmissions 1702 from a portable electronic facility 300. The length or frequency of the transmissions 1702 may be varied. The variation may be in response to velocity, direction, location, a point of interest, an object, preferences, a location with respect to a geofence or changes in a geofence. The variation may result in increased battery life for the portable electronic facility **300**. The data may be stored and transmitted all at one or it may be transmitted as it is updated. The data may be location information 1100.

In an embodiment the information transmissions may be from multiple sources. The multiple sources may be different networks or different means of communication. The means of communication may be SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. The information may be transmitted in a costless manner, a cost reduced manner or in the form of a DNS lookup.

Referring to FIG. 18, the present invention may provide methods and systems of increasing the quality of location based information 1100 for a portable electronic facility 300 involving obtaining multiple data points for a given item of information or a location 1202. The multiple data points may be analyzed and outliers dropped. The analysis may be performed using an algorithm. The item of information may relate to location, velocity or direction.

Referring to FIG. 19, the present invention may provide methods and systems of defining a geofence 900 on a portable electronic facility 300 involving inputting the geofence 900 using the portable electronic facility 300. The center and a radius of a geofence 900 may be entered on the portable electronic facility 300. The geofence 900 may be defined using a cursor on the display of the portable electronic facility 300. The geofence 900 may be defined using a touch screen on the portable electronic facility 300. The geofence 900 may be defined by the location of the portable electronic facility 300. The geofence 900 may be defined by placing the portable electronic facility 300 at certain points comprising the geofence 900. The geofence 900 may be defined in real time by placing the portable electronic facility 300 at certain points comprising the geofence 900. The geofence 900 may be manipulated using the portable electronic facility 300. The geofence 900 may be moved using the display of the portable electronic facility 300. The geofence 900 may be moved using the portable electronic facility 300. The geofence 900 may be a circle, a sphere, in the shape of any closed polygon, a closed volume, in two dimensions, in three dimensions or may travel with a person.

In certain embodiments the location of the portable electronic facility 300 with respect to the geofence 900 may result in the transmission of information 1702 to the portable electronic facility 300. The information may relate to a coupon, the weather or traffic conditions. In other embodiments the information and geofence 900 may be used for social networking. For example, all or certain of the portable electronic facilities 300 within a geofence 900 may receive information or all or certain of the portable electronic facilities 300 outside a geofence 900 may receive information.

In another embodiment, services may be linked to a geofence 900. For example, all or certain portable electronic facilities 300 located within a geofence 900 may receive or be eligible to receive certain services or all or certain of the portable electronic facilities 300 located outside a geofence 900 may receive or be eligible to receive certain services. The service may be a game, application or coupon. The price

for a service may be varied with the location of a portable electronic facility **300** in relation to a geofence **900**. For example, a cell phone may be allowed to place calls at no additional cost if located within a certain geofence **900**, for example a geofence **900** corresponding to the home of the 5 cell phone owner. In another example a portable electronic facility **300** may be able to receive and transmit information at no additional cost when located within a certain geofence, such as the home area of the portable electronic facility **300**.

Referring to FIG. 20, the present invention may provide 10 methods and systems of defining a geofence 900 on a computer screen or similar graphical user interface 2002 involving inputting the geofence 900 through a user interface. The geofence 900 may be defined or moved about the interface using a pointing device such as a mouse or stylus. 15 The radius, shape or dimensions of the geofence 900 may also be defined or changed using a pointing device such as a mouse or stylus. The user interface may be web-based and the geofence 900 may be defined on a server. The geofence 900 may be a circle, a sphere, in the shape of any closed 20 polygon, a closed volume, in two dimensions, in three dimensions or may travel with a person.

Referring to FIG. 21, the present invention may provide methods and systems of sending location-based alerts 2102 involving determining the location 1202 of a portable elec- 25 tronic facility 300 and sending an alert 2102 based on the location 1202 of the portable electronic facility 300. The alert 2102 may be in response to the location of a portable electronic facility 300 with respect to a geofence 900. The alert 2102 may be sent if the portable electronic facility 300 30 is within or outside a geofence 900 or within or outside a geofence 900 for a certain period of time. The alert 2102 may be sent if a portable electronic facility 300 enters or exits a geofence 900 or enters or exits a geofence 900 for a certain period of time. An alert 2102 may be contingent on 35 the location of other portable electronic facilities 300 or the location of other portable electronic facilities 300 with respect to a geofence 900. The alert 2102 may be affected by the location of other portable electronic facilities 300 or the location of other portable electronic facilities 300 with 40 respect to a geofence 900.

In one embodiment, the geofence **900** may define a place of business. The alert **2102** may be in response to a certain employee or employer arriving or not arriving at work. The alert **2102** may also be in response to a certain employee or 45 employer arriving or not arriving at work by a specified time.

In another embodiment, the geofence **900** may define a home. The alert **2102** may be in response to a certain child, teenager or vehicle arriving or not arriving at home. The <sup>50</sup> alert **2102** may also be in response to a certain child, teenager or vehicle arriving or not arriving at home by a specified time.

In another embodiment, the geofence **900** may define an airport. The alert **2102** may be in response to a passenger 55 arriving or departing. The geofence **900** may also define a city. The alert **2102** may be in response to a passenger or a shipment arriving or departing.

The alert **2102** may be via audio, video, fax, email, instant message, text message, SMS, internet protocol, voice, voicemail, vibration or may stimulate at least one of the five senses. The alert **2102** may be communicated via one of the following means of communication: SMS, fax, email, instant message, internet protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet or text. 65

Referring to FIG. 22, the present invention may provide methods and systems of analyzing information related to at

least one portable electronic facility **300** involving transmitting information from the at least one portable electronic facility **300** and analyzing such information using an analysis engine **2202**. The information from one or more portable electronic facilities **300** may be stored or aggregated. The analysis engine **2202** may provide the ability to view location history or analyze location history. The analysis engine **2202** may also request additional information or send alerts **2102**.

The analysis engine 2202 may perform analytics on location information such as demographic analysis, predictive analysis and descriptive analysis. The analysis may be for retail purposes, marketing purposes or security purposes. The analysis engine 2202 may determine the types of portable electronic facilities 300 or people at a given location. The analysis engine 2202 may determine the class of people at a given location. The class of people may be specified based on the following characteristics: income level, profession, race, ethnicity, gender, sex, sexual orientation, address, age, disposable income level, number of children, education level or health factors. The analysis engine 2202 may determine the route by which a person arrived at a location. The analysis engine 2202 may also determine the routes by which a class of people arrived at a location. The analysis engine 2202 may also determine the locations of a type of portable electronic facility 300. The information provided by the analysis engine 2202 may include purchasing information, personal preferences, demographics or consumer purchasing data relating to individual consumers or classes of consumers.

Access to the analysis engine **2202**, the system and information may be granted at different access levels. A user may be granted partial or restricted access via a guest login. It may be that whether a user is permitted to know the location of another user is determined based on the access levels of the users.

Referring to FIG. 23, methods and systems disclosed herein may include methods and systems for verifying a transaction using a portable electronic facility 300. In such embodiments, the location of a portable electronic facility 300 may be linked to a location of a transaction 2302, such as to verify the presence of a user in proximity to the use of the user's credit card, debit card, portable electronic transaction device, or other device. In embodiments the transaction is made using the Internet from a user's home computer, and the tracking information confirms the presence of the user at home by locating the user inside a home geofence 900.

Referring to FIG. 24, methods and systems disclosed herein may include methods and systems for tailoring information to the behavior of a user 2402, such as observing the behavior of a user 2402 and communicating information 2404 to the user by a portable electronic facility 300, such as information 2404 based on the observed behavior of a user 2402. The observed behavior 2402 may include behavior that is tied to locations, such as shopping behavior, purchasing behavior, or the like. In embodiments information may be presented to the user about alternate locations for shopping or purchasing for alternative, similar or complementary goods and services to those being shopped by the user at the tracked location. In embodiments the tracked behavior may indicate personal preferences, may constitute marketing information, or may be observed or inferred behavior based on past actions of the user.

Referring to FIG. 25, methods and systems disclosed herein may include methods and systems for providing information 2404 to a portable electronic facility 300 based

on information 2404 received from the portable electronic facility 300, including location information 1100. In embodiments the portable electronic facility 300 may have instant messaging capabilities, and an instant message may embed the location of the user such as a real-world location 5 or an indication of location, such as proximity to a geofence 900, such as designed as "home," "work," or the like.

Referring to FIG. 26, a network of portable electronic facilities 300 may be provided, allowing communication among portable electronic facilities 300, including informa- 10 tion based on the tracked locations of the portable electronic facilities 300. In embodiments information is communicated directly among the portable electronic facilities 300, without use of a central server. In embodiments information may be communicated by SMS, fax, email, instant message, internet 15 protocol, voice, voicemail, GPRS, CDMA, WAP protocol, internet and/or text. In embodiments the portable electronic facilities 300 may share information that includes or is based upon location information, such as a file, a music file, a movie, a game, an application, a ringtone, a text file, a 20 document, or an email.

FIGS. 27A-C present several examples of the possible graphical user interfaces 2702 that may be presented on a portable electronic facility 300, such as a mobile phone. The interface may display a map or a menu. FIG. 28 depicts a 25 graphical user interface 2802 providing an overview of the locations of all the users in a defined group. The users may be individual drivers in a fleet of delivery trucks. FIG. 29 provides another view 2902 of the locations of the users in FIG. 29. The view may involve the use of tiled maps. FIG. 30 30 depicts a detailed display 3002 of the location information for one particular user. The "today" and "yesterday" buttons 3004, 3008 may allow for the rapid toggling between data for different dates. FIG. 31 depicts a stop report 3102, as described above, for a particular user. 35

FIG. 32 depicts the definition of a geofence 900 using a map 3202. FIG. 33 shows several icons 3302 that may be assigned to various geofences 900, such as to distinguish different geofences 900 that are created or used for different purposes. For example, a geofence may be designated with 40 a star to signify its importance, or with an icon representing a house to indicate that it is a geofence 900 for a home. FIG. 34 depicts an address book 3402 that may be provided for a user. FIG. 35 presents a more detailed view of one of the entries 3502 in the address book 3402. FIG. 36 depicts a 45 graphical user interface 3602 that may be used to define alerts using the system. FIG. 37A-37C depict location details as both lists 3702 and maps 3704. FIG. 38A-38C depict several menus 3802 related to storing location-based information 1100, including a menu 3804 for finding saved 50 locations, such as by zip code or other data, a menu 3808 displaying detailed locations, and a menu 3810 for displaying options related to a location, such as an option to see a map, to send directions to the location from a particular location, and an option to send the location information to 55 wherein the altering the state of the application includes another user. FIG. 39A-39D depict several graphical user interfaces 3902 related to the presentation of points of interest on a portable electronic facility 300, such as an interface 3904 for finding particular types of location, such as hotels, restaurants, automated teller machines, or gas 60 stations, an interface 3908 for showing details of a particular type of location, an interface 3910 for offering options related to a particular type of location, such as the option to see a map, get directions, or call the location, and an interface 3912 for displaying the results, such as showing a 65 map of the location. FIG. 40 presents a graphical user interface 4002 that may allow a user to send location

information, such as via email or voice. FIG. 41 presents a graphical user interface 4102 that may allow a user to input a zip code while traveling. FIGS. 42A-42B present a graphical user interface with a setting menu 4202 that may allow a user to vary the settings of the portable electronic facility 300, such as allowing a user to vary the frequency with which a portable electronic device obtains location information using an interface 4204.

While the invention has been disclosed in connection with certain preferred embodiments, other embodiments will be recognized by those of ordinary skill in the art and are encompassed herein. All documents referenced herein are hereby incorporated by reference.

The invention claimed is:

1. A computer-implemented method executing on a mobile device, the method comprising:

- executing an application at the mobile device, the application causing display of a user interface at the mobile device.
- receiving, electronically over a network on the mobile device, data defining a geofence;
- monitoring, via sensors on the mobile device, a current location of the mobile device; and
- comparing the current location of the mobile device with boundaries of the geofence;
- determining, based on the comparing, that the current location of the mobile device is within the geofence; and
- in accordance with determining that the current location is within the geofence, altering a state of the application on the mobile device, wherein the altering the state of the application includes adding a user-interface element to the user interface, the user interface element unavailable outside of the geofence, the application stored in memory on the mobile device and executable on the mobile device.

2. The computer-implemented method of claim 1, wherein the altering the state of the application includes changing a user-interface function based at least in part on the current location, the user-interface function generated by the application.

3. The computer-implemented method of claim 2, wherein changing user-interface function includes adding a user-interface element not available outside of the geofence.

4. The computer-implemented method of claim 1, wherein the altering the state of the application includes initiating execution of the application on the mobile device.

5. The computer-implemented method of claim 4, further comprising:

- determining that the current location of the mobile device has exited the geofence; and
- altering the state of the application to stop execution of the application.

6. The computer-implemented method of claim 1, stopping execution of the application.

7. The computer-implemented method of claim 1, wherein the altering the state of the application includes causing the application that was previously available for execution on the mobile device to become unavailable for execution.

8. A non-transitory machine-readable storage medium including instructions that, when performed on a mobile device, cause the mobile device to perform operations comprising:

receive, electronically over a network on the mobile device, data defining a geofence;

10

- executing an application at the mobile device, the application causing display of a user interface at the mobile device;
- monitor, via sensors on the mobile device, a current location of the mobile device;
- compare the current location of the mobile device with boundaries of the geofence;
- determine, based on the comparison, that the current location of the mobile device is within the geofence; and
- in accordance with determining that the current location is within the geofence, alter a state of the application on the mobile device, wherein the altering the state of the application includes adding a user-interface element to the user interface, the user interface element unavail-15 able outside of the geofence, the application stored in memory on the mobile device and executable on the mobile device.

**9**. The non-transitory machine-readable storage medium of claim **8**, wherein the instructions to alter the state of the 20 application include instructions to change a user-interface function based at least in part on the current location, the user-interface function generated by the application.

**10**. The non-transitory machine-readable storage medium of claim **9**, wherein the instructions to change the user- 25 interface function includes instructions to add a user-interface element not available outside of the geofence.

11. The non-transitory machine-readable storage medium of claim 8, wherein the instructions to alter the state of the application include instructions to initiate execution of the 30 application on the mobile device.

12. The non-transitory machine-readable storage medium of claim 11, further comprising instructions to cause operations comprising:

- determine that the current location of the mobile device 35 has exited the geofence; and
- alter the state of the application to stop execution of the application.

**13.** The non-transitory machine-readable storage medium of claim **8**, wherein the instructions to alter the state of the 40 application include instructions to stop execution of the application.

14. The non-transitory machine-readable storage medium of claim 8, wherein the instructions to alter the state of the application include instructions to cause the application 45 previously available for execution on the mobile device to become unavailable for execution.

15. A portable electronic facility comprising:

a memory device;

a memory device;

a sensor; and

central processing unit coupled to the memory device and the sensor, the memory device containing instructions that, when executed by the central processing unit, cause the portable electronic facility to perform operations comprising:

30

receive, electronically over a network on the portable electronic facility, data defining a geofence;

- executing an application at the portable electronic facility, the application causing display of a user interface at the portable electronic facility;
- monitor, via sensors on the mobile device, a current location of the portable electronic facility;
- compare the current location of the portable electronic facility with boundaries of the geofence;

determine, based on the comparison, that the current location of the portable electronic facility is within the geofence; and

in accordance with determining that the current location is within the geofence, alter a state of the application on the portable electronic facility, wherein the altering the state of the application includes adding a user-interface element to the user interface, the user interface element unavailable outside of the geofence, the application stored in the memory device and executable on the portable electronic facility.

**16**. The portable electronic facility of claim **15**, wherein the instructions to alter the state of the application include instructions to change a user-interface function based at least in part on the current location, the user-interface function generated by the application.

17. The portable electronic facility of claim 16, wherein the instructions to change the user-interface function includes instructions to add a user-interface element not available outside of the geofence.

**18**. The portable electronic facility of claim **15**, wherein the instructions to alter the state of the application include instructions to initiate execution of the application on the portable electronic facility.

**19**. The portable electronic facility of claim **18**, further comprising instructions to cause operations comprising:

determine that the current location of the portable electronic facility has exited the geofence; and

alter the state of the application to stop executing the application.

**20**. The portable electronic facility of claim **15**, wherein the instructions to alter the state of the application include instructions to stop execution of the application.

\* \* \* \* \*